



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL385 G2 (AMD Opteron (TM) 2218)

SPECint_rate2000 = 84.4
SPECint_rate_base2000 = 78.2

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2006 Hardware Avail: Sep-2006 Software Avail: Apr-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	97.8	66.4	4	97.8	66.4
175.vpr	4	103	63.1	4	102	64.0
176.gcc	4	56.7	90.0	4	57.8	88.4
181.mcf	4	182	45.9	4	148	56.4
186.crafty	4	58.7	79.1	4	52.2	88.9
197.parser	4	112	74.8	4	113	73.9
252.eon	4	52.2	116	4	39.7	152
253.perlbnk	4	94.8	88.1	4	94.8	88.1
254.gap	4	59.9	85.2	4	59.9	85.2
255.vortex	4	73.2	120	4	66.0	133
256.bzip2	4	114	60.8	4	110	63.0
300.twolf	4	174	79.8	4	142	98.1

Hardware

CPU: AMD Opteron (TM) 2218
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Parallel: No
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 16 GB (8x2048 MB PC2-5300P CL5.0)
 Disk Subsystem: 1x36 GB 10 K SAS
 Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
 Compiler: Intel C++ Compiler for 32-bit applications, (version 9.1 Build 20060323Z) Microsoft Visual Studio .NET 7.0.9466 (for libraries) MicroQuill Smartheap Library 7.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes
Base tuning for C++ programs: -fast -Qcxx_features -arch:SSE2 +FDO ONESTEP=yes
Portability flags:
 176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
 164.gzip: basepeak=yes
 175.vpr: -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000
          -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 176.gcc: -fast -arch:SSE2 -Oi- -Qunroll3 +FDO
 181.mcf: -O3 -Qipo -QaxN +FDO ONESTEP=yes shlw32M.lib
 186.crafty: -fast -arch:SSE2 +FDO ONESTEP=yes
 197.parser: -arch:SSE2 -Oi- -Qipo +FDO ONESTEP=yes
 252.eon: -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000
          -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 253.perlbnk: basepeak=yes
 254.gap: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL385 G2 (AMD Opteron (TM) 2218)

SPECint_rate2000 = 84.4
SPECint_rate_base2000 = 78.2

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2006 Hardware Avail: Sep-2006 Software Avail: Apr-2006

Notes/Tuning Information (Continued)

```
255.vortex: -fast -arch:SSE2 -Oi- -Qoption,c,-ip_ninl_max_stats=2000
            -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes shlw32M.lib
256.bzip2:  -O3 -Qipo -QaxN -Qunroll2 shlw32M.lib
300.twolf:  -fast -arch:SSE2 -Qansi_alias +FDO ONESTEP=yes shlw32M.lib
```

BIOS Configuration Notes
Node Interleaving Disabled
Other Configuration Notes