



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX600 S3, Intel Xeon processor 7130M, 3.20 GHz

SPECfp_rate2000 = 96.6

SPECfp_rate_base2000 = 96.6

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Aug-2006 | Software Avail: Jan-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	133	112	8	133	112
171.swim	8	535	53.7	8	535	53.7
172.mgrid	8	318	52.6	8	318	52.6
173.applu	8	362	53.8	8	362	53.8
177.mesa	8	90.5	144	8	90.5	144
178.galgel	8	91.5	294	8	91.5	294
179.art	8	47.5	508	8	47.5	508
183.quake	8	221	54.5	8	221	54.5
187.facerec	8	135	131	8	135	131
188.amp	8	179	114	8	179	114
189.lucas	8	316	58.7	8	316	58.7
191.fma3d	8	304	64.2	8	304	64.2
200.sixtrack	8	177	57.8	8	177	57.8
301.apsi	8	250	96.4	8	250	96.4

Hardware

CPU: Intel Xeon processor 7130M (3.20 GHz, 2x1MB L2, 8MB L3, 800 MHz system bus)
CPU MHz: 3200
FPU: Integrated
CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2,4 chips
Parallel: No
Primary Cache: 12k micro-ops(I) + 16KB(D) on chip, per core
Secondary Cache: 1024KB(I+D) on chip, per core
L3 Cache: 8MB on chip, per chip
Other Cache: N/A
Memory: 16x1GB DDRII-RAM PC2-3200R (CAS 3-3-3)
Disk Subsystem: Fujitsu MAS3367NC (SCSI, 15krpm, 36GB)
Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 9 with SP3
Kernel 2.6.5-7.244-smp on an x86_64
Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T
Build 20060120 (for 64-bit applications)
File System: ext3
System State: Multi-user run level 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
PASS1: -prof_gen PASS2: -prof_use

Optimization flags

ONESTEP=yes set for all benchmarks

Portability flags

-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags

for Fortran and C programs: -fast +FDO

Peak tuning flags

same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX600 S3, Intel Xeon processor 7130M, 3.20 GHz

SPECfp_rate2000 = 96.6

SPECfp_rate_base2000 = 96.6

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Aug-2006 | Software Avail: Jan-2006

Notes/Tuning Information (Continued)

The system bus runs at 800 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

This result was measured on the PRIMERGY TX600 S3. The PRIMERGY TX600 S3 and the PRIMERGY RX600 S3 are electronically equivalent.

BIOS Configuration:

Adjacent Sector Prefetch = Disable

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>