



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**IBM Corporation**  
IBM System X 3105 (AMD Opteron (TM) 1212)

SPECfp2000 = **1859**  
SPECfp\_base2000 = **1705**

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Sep-2006 | Hardware Avail: Sep-2006 | Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	68.1	2351	60.8	2632	
171.swim	3100	123	2519	115	2690	
172.mgrid	1800	123	1465	108	1671	
173.applu	2100	114	1838	106	1976	
177.mesa	1400	93.5	1498	82.0	1708	
178.galgel	2900	105	2749	104	2778	
179.art	2600	105	2475	80.4	3233	
183.earthquake	1300	84.1	1546	78.7	1652	
187.facerec	1900	85.0	2234	81.4	2336	
188.amp	2200	177	1246	169	1304	
189.lucas	2000	104	1918	89.2	2242	
191.fma3d	2100	146	1443	147	1431	
200.sixtrack	1100	164	672	156	705	
301.apsi	2600	193	1346	180	1442	

### Hardware

CPU: AMD Opteron 1212  
 CPU MHz: 2000  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1 chip  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD (on chip) per core  
 Secondary Cache: 1024KB (I+D) (on chip) per core  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 4x1GB, PC2-5300  
 Disk Subsystem: SATA, 80GB 10K RPM  
 Other Hardware: None

### Software

Operating System: SuSE Linux 9.0 SP3 SLES 64 bit Kernel 2.6.5-7.244-smp  
 Compiler: PathScale EKO Compiler Suite, Release 2.4  
 PathScale EKOPATH(TM) Compiler Suite, Release 2.4  
 File System: Linux/reiserfs  
 System State: Multi-user, run level 3

## Notes/Tuning Information

+FDO: PASS1= -fb\_create fbdata PASS2= -fb\_opt fbdata

### Baseline optimization

C programs: -Ofast -WOPT:mem\_opnds=on +FDO  
 Fortran programs: -Ofast -LNO:fusion=2 -OPT:fast\_complex=on +FDO  
 Portability Flags:  
 178.galgel: -fixedform

### Peak Tuning:

168.wupwise: -Ofast -IPA:linear=on -LNO:prefetch Ahead=5:prefetch=3  
 -OPT:unroll\_times\_max=8:unroll\_size=128:IEEE\_NaN\_Inf=off:ro=3  
 171.swim: -Ofast -CG:local\_fwd\_sched=on -LNO:fusion=2 -m3dnow  
 172.mgrid: -Ofast -CG:gcm=off -OPT:IEEE\_arith=3:unroll\_size=200  
 -LNO:fusion=2:fission=1:blocking=off:prefetch Ahead=2  
 -WOPT:mem\_opnds=on:aggstr=0  
 173.applu: -Ofast -CG:local\_fwd\_sched=on -OPT:ro=3 -TENV:X=3  
 -LNO:fusion=2:fission=2:full\_unroll\_size=10000 +FDO



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation  
IBM System X 3105 (AMD Opteron (TM) 1212)

SPECfp2000 = 1859  
SPECfp\_base2000 = 1705

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Sep-2006 | Hardware Avail: Sep-2006 | Software Avail: Mar-2006

## Notes/Tuning Information (Continued)

```

177.mesa:      -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on -WOPT:mem_opnds=on +FDO
178.galgel:    -Ofast -OPT:fast_complex=on +FDO
179.art:       -O3 -OPT:Ofast -fno-math-errno -mno-sse2 -m32
183.quake:    -Ofast -CG:load_exe=2 -WOPT:mem_opnds=on -m32 +FDO
187.facerec:  -Ofast -IPA:plimit=1500 -LNO:fusion=2
              -OPT:IEEE_NaN_Inf=off:ro=3:unroll_size=0 +FDO
188.amp:      -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
              -GRA:optimize_boundary=on -fno-math-errno -TENV:X=4 +FDO
189.lucas:    -Ofast -OPT:ro=3:fast_nint=off:unroll_size=256 -WOPT:mem_opnds=on +FDO
191.fma3d:    -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
              -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack: -O3 -OPT:Ofast:early_intrinsics=on
              -fno-math-errno -CG:load_exe=1 +FDO
301.apsi:     -Ofast -CG:load_exe=0 -LNO:prefetch=0:simd=2

```