



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3500 (2.66 GHz Xeon 5150, 4MB L2 Cache)

SPECfp_rate2000 = --

SPECfp_rate_base2000 = 77.1

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	70.8	105			
171.swim	4	264	54.4			
172.mgrid	4	167	50.1			
173.applu	4	192	50.9			
177.mesa	4	56.4	115			
178.galgel	4	62.5	215			
179.art	4	61.2	197			
183.quake	4	89.2	67.6			
187.facerec	4	95.8	92.1			
188.amp	4	149	68.7			
189.lucas	4	175	53.0			
191.fma3d	4	165	59.1			
200.sixtrack	4	106	48.3			
301.apsi	4	209	57.6			

Hardware

CPU: Intel Xeon processor 5150 (2.66 GHz, 1333 MHz bus)
 CPU MHz: 2667
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1, 2 chips
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
 Secondary Cache: 4096KB(I+D) on chip (per chip)
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 x 1024 MB ECC PC2-5300F
 Disk Subsystem: 80GB SATA 10K RPM
 Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (32-bit)
 Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
 Build 20060323Z
 Microsoft Visual Studio 2005(for libraries)
 SmartHeap Library Version 8.0 from <http://www.microquill.com/>
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlW32M.lib
Portability:
178.galgel: -FI /F32000000
```

This result was measured on an IBM System X 3400. IBM System X 3500 and IBM System X 3400 are electronically equivalent.