




CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL45p G2 (AMD Opteron (TM) 8218)

SPECfp_rate2000 = 147
SPECfp_rate_base2000 = 133

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2006 Hardware Avail: Sep-2006 Software Avail: Apr-2006



Hardware

CPU: AMD Opteron (TM) 8218
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 8 cores, 4 chips, 2 cores/chip
 CPU(s) orderable: 2,4 chips
 Parallel: No
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 32 GB (16x2 GB PC2-5300P CL5.0)
 Disk Subsystem: 1x36 GB 10 K SAS
 Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
 Compiler: Intel C++ Compiler for 32-bit applications, (version 9.1 Build 20060323Z)
 Intel Fortran Compiler for 32-bit applications, (version 9.1 build 20060323Z)
 PGI Fortran compiler 6.0-8 for Windows XP (32-bit)
 PGI C compiler 6.0-8 for Windows XP (32-bit)
 Microsoft Visual Studio .NET 7.0.9466 (for libraries)
 AMD Core Math Library V3.5.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use (Intel compiler)
+FDO*: PASS1=-Mpfi PASS2=-Mpfo (PGI compiler)
+ACML is linking with AMD Core Math Library V3.5.0
ifort is the Intel Fortran compiler, icl is the Intel C++ compiler and
pgf90 is the PGI Fortran compiler, pgcc is the PGI C compiler.
Base tuning for C programs: pgcc -fastsse -Mipa=fast,inline
Base tuning for FORTRAN programs: pgf90 -fastsse -Mipa=fast,inline +FDO* ONESTEP=1
Portability flags:
  178.galgel: -Mfixed
Peak tuning:
  168.wupwise: pgf90 basepeak=yes
  171.swim: ifort -Qipo -O3 -QaxN -QxW +FDO -Qunroll0 ONESTEP=1
  172.mgrid: pgf90 basepeak=yes
  173.applu: ifort -Qipo -O3 -QaxN -QxW +FDO -auto ONESTEP=1
  177.mesa: icl -Qipo -arch:SSE2 +FDO -Qunroll1 -Qansi_alias ONESTEP=1
  -Qoption,c,-ip_ninl_max_stats=1500,-ip_ninl_max_total_stats=4500
  178.galgel: pgf90 -fastsse -Mipa=fast,safe RM_SOURCES=lapak.f90 -Munix +ACML ONESTEP=1
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL45p G2 (AMD Opteron (TM) 8218)

SPECfp_rate2000 = 147
SPECfp_rate_base2000 = 133

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Aug-2006 | Hardware Avail: Sep-2006 | Software Avail: Apr-2006

Notes/Tuning Information (Continued)

```

179.art:          pgcc -fastsse -Mipa=fast,inline
183.quake:       icl basepeak=yes
187.facerec:     ifort -Qipo -QxW +FDO -Qunroll3 ONESTEP=1
                  -Qoption,f,-ip_ninl_max_stats=2500,-ip_ninl_max_total_stats=7000
188.ampp:       icl -Oa -arch:SSE2 -Zp4 -Qansi_alias ONESTEP=1
189.lucas:      ifort -Qipo -QxW -Qunroll1 ONESTEP=1
191.fma3d:      ifort -Qipo -QaxN -QxW +FDO -Qansi-alias- ONESTEP=1
200.sixtrack:   pgf90 basepeak=yes
301.apsi:       pgf90 basepeak=yes

```

BIOS Configuration Notes

Node Interleaving is Disabled

Other Configuration Notes

The start /b /wait /affinity command is used to bind CPU(s) to processes.