



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell

PowerEdge 1950 (Intel Xeon processor X5355, 2.66 GHz)

SPECint_rate2000 = 200

SPECint_rate_base2000 = 200

SPEC license #: 55 | Tested by: Dell, Inc., Round Rock, TX | Test date: Nov-2006 | Hardware Avail: Dec-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	89.2	146	8	89.3	146
175.vpr	8	90.2	144	8	89.2	146
176.gcc	8	56.0	182	8	56.0	182
181.mcf	8	121	138	8	121	138
186.crafty	8	41.2	225	8	41.2	225
197.parser	8	94.3	177	8	94.1	177
252.eon	8	37.3	323	8	37.3	323
253.perlbnk	8	58.0	288	8	58.0	288
254.gap	8	71.8	142	8	71.2	143
255.vortex	8	51.6	342	8	51.6	342
256.bzip2	8	92.5	150	8	91.4	152
300.twolf	8	98.7	282	8	98.7	282

Hardware

CPU: Quad-Core Intel Xeon processor X5355 (1333 MHz system bus)
CPU MHz: 2666
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 8 MB I+D on chip, per chip (4 MB shared per 2 cores)
L3 Cache: N/A
Other Cache: N/A
Memory: 8 GB (8 x 1 GB 667 MHz CL5 FB-DIMM DDR2 SDRAM)
Disk Subsystem: 1 x 80GB SATA 7200 RPM
Other Hardware: None

Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
Compiler: Intel C++ Compiler 9.1 for IA32(20060519Z)
Microsoft Visual Studio .NET 2003(7.1.3088)
MicroQuill SmartHeap Library 8.0
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -fast +FDO shlw32M.lib
C++: -fast -Qcxx_features +FDO

PEAK TUNING

164.gzip: -fast +FDO
175.vpr: -fast +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Oa +FDO shlw32M.lib
197.parser: -fast +FDO
252.eon: -fast +FDO
253.perlbnk: basepeak=yes



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell

PowerEdge 1950 (Intel Xeon processor X5355, 2.66 GHz)

SPECint_rate2000 = 200

SPECint_rate_base2000 = 200

SPEC license #: 55 | Tested by: Dell, Inc., Round Rock, TX | Test date: Nov-2006 | Hardware Avail: Dec-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

```
254.gap:      -fast +FDO
255.vortex    basepeak=yes
256.bzip2:    -fast -Qunroll11 -Oa +FDO
300.twolf:    basepeak=yes
BIOS SETTINGS
  Adjacent Cache Line Prefetch disabled in BIOS
```