



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL385 G2 (AMD Opteron (TM) 2220SE)

SPECfp2000 = **2023**
SPECfp_base2000 = **1836**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Oct-2006 Hardware Avail: Jan-2007 Software Avail: Sep-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	55.9	2864	55.9	2864	
171.swim	3100	124	2501	120	2580	
172.mgrid	1800	105	1708	105	1708	
173.applu	2100	139	1508	122	1717	
177.mesa	1400	129	1088	63.9	2191	
178.galgel	2900	95.2	3046	88.6	3273	
179.art	2600	57.3	4540	57.3	4535	
183.quake	1300	76.5	1700	76.5	1700	
187.facerec	1900	91.1	2086	96.0	1980	
188.amp	2200	181	1214	149	1478	
189.lucas	2000	108	1857	90.8	2204	
191.fma3d	2100	127	1655	113	1852	
200.sixtrack	1100	130	845	130	845	
301.apsi	2600	164	1589	164	1589	

Hardware

CPU: AMD Opteron (TM) 2220SE
CPU MHz: 2800
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 64 KB I + 64 KB D on chip per core
Secondary Cache: 1 MB I+D on chip per core
L3 Cache: N/A
Other Cache: N/A
Memory: 8 GB (4x2 GB PC2-5300P CL5.0)
Disk Subsystem: 1x36 GB 10 K SAS
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (version 9.1 Build 20060816Z)
Intel Fortran Compiler for 32-bit applications, (version 9.1 build 20060816Z)
PGI Fortran compiler 6.0-8 for Windows XP (32-bit)
PGI C compiler 6.0-8 for Windows XP (32-bit)
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
AMD Core Math Library V3.5.0
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use (Intel compiler)
+FDO*: PASS1=-Mpfi PASS2=-Mpfo (PGI compiler)
+ACML is linking with AMD Core Math Library V3.5.0
ifort is the Intel Fortran compiler, icl is the Intel C++ compiler and
pgf90 is the PGI Fortran compiler, pgcc is the PGI C compiler.
Base tuning for C programs:      pgcc -fastsse -Mipa=fast,inline
Base tuning for FORTRAN programs: pgf90 -fastsse -Mipa=fast,inline +FDO* ONESTEP=1
Portability flags:
  178.galgel: -Mfixed
Peak tuning:
168.wupwise:      pgf90 basepeak=yes
171.swim:         ifort -Qipo -O3 -QaxN -QxW +FDO -Qunroll0 ONESTEP=1
172.mgrid:       pgf90 basepeak=yes
173.applu:       ifort -Qipo -O3 -QaxN -QxW +FDO -auto ONESTEP=1
177.mesa:        icl -Qipo -arch:SSE2 +FDO -Qunroll1 -Qansi_alias ONESTEP=1
                  -Qoption,c,-ip_ninl_max_stats=1500,-ip_ninl_max_total_stats=4500
178.galgel:      pgf90 -fastsse -Mipa=fast,safe RM_SOURCES=lapak.f90 -Munix +ACML ONESTEP=1
```



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL385 G2 (AMD Opteron (TM) 2220SE)

SPECfp2000 = 2023
SPECfp_base2000 = 1836

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Oct-2006 | Hardware Avail: Jan-2007 | Software Avail: Sep-2006

Notes/Tuning Information (Continued)

```

179.art:          pgcc -fastsse -Mipa=fast,inline
183.quake:       icl basepeak=yes
187.facerec:     ifort -Qipo -QxW +FDO -Qunroll3 ONESTEP=1
                  -Qoption,f,-ip_ninl_max_stats=2500,-ip_ninl_max_total_stats=7000
188.ampp:       icl -Oa -arch:SSE2 -Zp4 -Qansi_alias ONESTEP=1
189.lucas:      ifort -Qipo -QxW -Qunroll1 ONESTEP=1
191.fma3d:      ifort -Qipo -QaxN -QxW +FDO -Qansi-alias- ONESTEP=1
200.sixtrack:   pgf90 basepeak=yes
301.apsi:       pgf90 basepeak=yes

```

BIOS Configuration Notes
Node Interleaving is Disabled