



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Bull

NovaScale R460 (Intel Xeon processor 5110, 1.60 GHz)

SPECfp2000 = 1684

SPECfp_base2000 = 1659

SPEC license #: 20 Tested by: Bull Test date: Nov-2006 Hardware Avail: Nov-2006 Software Avail: Sep-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	59.6	2685	59.6	2685	
171.swim	3100	142	2177	142	2177	
172.mgrid	1800	170	1058	170	1058	
173.applu	2100	148	1419	148	1419	
177.mesa	1400	94.4	1484	94.4	1484	
178.galgel	2900	75.4	3848	75.4	3848	
179.art	2600	47.0	5528	47.0	5528	
183.quake	1300	73.7	1765	59.8	2173	
187.facerec	1900	117	1622	117	1622	
188.amp	2200	183	1203	183	1203	
189.lucas	2000	135	1486	135	1486	
191.fma3d	2100	163	1289	163	1289	
200.sixtrack	1100	172	638	172	638	
301.apsi	2600	252	1030	252	1030	

Hardware

CPU: Intel Xeon Processor 5110 (1066MHz bus)
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 2 cores/chip
CPU(s) orderable: 1 to 2 chips
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 4096KB(I+D) on chip per chip (shared)
L3 Cache: N/A
Other Cache: N/A
Memory: 8GB (8x1GB 533MHz ECC CL4 DDR2 FB-DIMM)
Disk Subsystem: 2x73GB SAS 15000 rpm
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (32 bits), Service Pack 1
Compiler: Intel(R) C++ Compiler for 32-bit app., Version 9.1, - Build 20060927Z Package ID: W_CC_C_9.1.032
Intel(R) Fortran Compiler for 32-bit app., Version 9.1, - Build 20060927Z Package ID: W_FC_C_9.1.032
Microsoft Visual Studio .NET 2003 (for libraries)
MicroQuill SmartHeap Library 8.0 (shlW32M.lib)
File System: NTFS
System State: Default

Notes/Tuning Information

Portability flags:

178.galgel: -FI /F32000000

Feedback optimization:

+FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Baseline Tuning Flags:

for C programs:
-fast -Qansi_alias +FDO
for Fortran programs:
-fast -Qansi_alias +FDO

Peak Tuning Flags:

168.wupwise: basepeak=yes
171.swim: basepeak=yes
172.mgrid: basepeak=yes
173.applu: basepeak=yes



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Bull

NovaScale R460 (Intel Xeon processor 5110, 1.60 GHz)

SPECfp2000 = 1684

SPECfp_base2000 = 1659

SPEC license #: 20 | Tested by: Bull | Test date: Nov-2006 | Hardware Avail: Nov-2006 | Software Avail: Sep-2006

Notes/Tuning Information (Continued)

```
177.mesa: basepeak=yes
178.galgel: basepeak=yes
179.art: basepeak=yes
183.quake: -fast -Oa -Qrcd +FDO ONESTEP=yes shlW32M.lib
187.facerec: basepeak=yes
188.ammmp: basepeak=yes
189.lucas: basepeak=yes
191.fma3d: basepeak=yes
200.sixtrack: basepeak=yes
301.apsi: basepeak=yes
```

Other Configuration Notes

/NUMPROC=1 flag was added to boot.ini to invoke uniprocessor environment

For information about Bull please see:
<http://www.bull.com>