



CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) DG965WH motherboard(3.0 GHz, Intel(R) Pentium(TM) D processor 930)

SPECint_rate2000 = 34.6

SPECint_rate_base2000 = 34.6

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

70 60 50 40 30 20 10				Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
				164.gzip	2	135	24.0	2	135	24.0
				175.vpr	2	137	23.8	2	135	24.0
				176.gcc	2	63.3	40.3	2	63.3	40.3
				181.mcf	2	105	39.9	2	105	39.9
				186.crafty	2	88.7	26.2	2	89.2	26.0
				197.parser	2	152	27.5	2	152	27.6
				252.eon	2	63.9	47.2	2	64.2	47.0
				253.perlbnk	2	99.1	42.1	2	99.4	42.0
				254.gap	2	65.8	38.8	2	65.8	38.8
				255.vortex	2	70.7	62.3	2	70.7	62.3
				256.bzip2	2	132	26.4	2	132	26.3
				300.twolf	2	196	35.5	2	196	35.4

Hardware

CPU: Intel(R) Pentium(TM) D processor 930(3.0 GHz, 800 MHz bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12K micro-ops1 + 16KBD per core, on chip
Secondary Cache: 2 MB(I+D) per core, on chip
L3 Cache: None
Other Cache: None
Memory: 2 GB (2 1GB Micron MT16HTF12864AY-80ED4 DDR2 800, CL5)
Disk Subsystem: Maxtor DiamondMax 10 6B300S0 300GB NCQ Serial ATA (7200 RPM, 16MB cache)
Other Hardware: SoundBlaster Live! PCI card

Software

Operating System: Windows XP Professional SP2
Compiler: Intel C++ Compiler 9.1 for 32-bit applications
Build 20060323Z Package ID: W_CC_P_9.1.020
Microsoft Visual Studio 2005(for libraries)
SmartHeap Library Version 8.0 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) DG965WH motherboard(3.0 GHz, Intel(R) Pentium(TM) D processor 930)

SPECint_rate2000 = 34.6

SPECint_rate_base2000 = 34.6

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll1 +FDO

300.twolf: -fast -O3 +FDO shlw32M.lib

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply

Product description located as of 1/2007:

<http://www.intel.com/products/motherboard/DG965WH/index.htm>

The system bus runs at 1066 MHz