



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850GB motherboard (1.9 GHz, Pentium 4 processor)

SPECfp2000 = 696

SPECfp_base2000 = 687

SPEC license #: 13 Tested by: Intel Corporation Test date: Aug-2001 Hardware Avail: Aug-2001 Software Avail: Jun-2001

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	172	931	171	937	
171.swim	3100	244	1272	242	1280	
172.mgrid	1800	266	676	257	701	
173.applu	2100	275	764	270	777	
177.mesa	1400	183	764	182	768	
178.galgel	2900	333	872	331	877	
179.art	2600	489	532	484	537	
183.quake	1300	172	758	164	792	
187.facerec	1900	236	805	238	800	
188.amp	2200	555	396	549	401	
189.lucas	2000	212	942	212	942	
191.fma3d	2100	348	603	348	603	
200.sixtrack	1100	318	346	305	361	
301.apsi	2600	514	505	513	507	

Hardware

CPU: Pentium 4 processor (1.9 GHz, 400 MHz bus)
 CPU MHz: 1900
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 12k micro-ops I + 8KBD on chip
 Secondary Cache: 256KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 256 MB (2 128 MB PC800 RDRAM non-ECC modules)
 Disk Subsystem: IBM DTLA-307030 ATA-100
 Other Hardware: None

Software

Operating System: Windows 2000(Build 2195, SP2)
 Compiler: Intel C++ Compiler 5.0.1 Build 010525Z
 Intel Fortran Compiler 5.0.1 Build 010525Z
 Microsoft Visual C++ 6.0 SP5(for libraries)
 MicroQuill SmartHeap library V6.0
 File System: FAT32
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning: -Qipo -QxW -O3 +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxW -O3 +FDO
171.swim: -Qipo -QxW -O3 +FDO
172.mgrid: -Qipo -QaxW -O3 +FDO
173.applu: -Qipo -QxW -O3 -Qscalar_rep- -Qauto +FDO
177.mesa: -Qipo -Oa -QxW -O3 +FDO
178.galgel: -Qipo -QxW -O3 +FDO
179.art: -Qipo -QxW -O3 -Oa +FDO
183.quake: -Qipo -QxW -Oa -Qrcd +FDO
187.facerec: -Qipo -QxW -O3 +FDO
187.facerec: LIBS=libIEPCF90.lib libintrins.lib libF90.lib
libqwin.lib libm.lib shlw32M.lib LIBC.lib
libirc.lib OLDNAMES.lib
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850GB motherboard (1.9 GHz, Pentium 4 processor)

SPECfp2000 = 696

SPECfp_base2000 = 687

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Aug-2001 | Hardware Avail: Aug-2001 | Software Avail: Jun-2001

Notes/Tuning Information (Continued)

188. ammp: -Qipo -QxW -O3 -Oa +FDO
189. lucas: -Qipo -QxW -O3 +FDO
191. fma3d: -Qipo -QxW -O3 +FDO
200. sixtrack: -Qipo -QxW +FDO
301. apsi: -Qipo -QxW -O3 +FDO

LIBS=libIEPCF90.lib libintrins.lib libF90.lib libqwind.lib libm.lib shlw32M.lib
LIBC.lib libirc.lib OLDNAMES.lib

shlw32M.lib is the SmartHeap library V6.0 from Microquill:

<http://www.microquill.com>

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B

Product description located as of 11/2000:

http://developer.intel.com/design/motherbd/gb/gb_ds.htm

Motherboard is available through Intel OEM Distribution Channel. See

<http://channel.intel.com/business/ibp/boards/d850gb.htm> for more information

The system bus runs at 400 MHz