



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V880

SPECint_rate2000 = 23.9
SPECint_rate_base2000 = 21.1

SPEC license #: 6 Tested by: Sun Microsystems, Palo Alto Test date: May-2002 Hardware Avail: Jun-2002 Software Avail: May-2002

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	385	16.9	4	350	18.5
175.vpr	4	362	17.9	4	323	20.1
176.gcc	4	228	22.4	4	195	26.2
181.mcf	4	378	22.1	4	299	27.9
186.crafty	4	203	22.9	4	171	27.1
197.parser	4	432	19.3	4	350	23.9
252.eon	4	265	22.8	4	257	23.5
253.perlbnk	4	392	21.3	4	363	23.0
254.gap	4	358	14.3	4	353	14.5
255.vortex	4	304	29.0	4	233	37.8
256.bzip2	4	280	24.8	4	268	25.9
300.twolf	4	602	23.1	4	536	26.0

Hardware

CPU: UltraSPARC III Cu
 CPU MHz: 900
 FPU: Integrated
 CPU(s) enabled: 4 cores, 4 chips, 1 core/chip
 CPU(s) orderable: 2,4,8
 Parallel: No
 Primary Cache: 32KBI+64KBD on chip
 Secondary Cache: 8MB(I+D) off chip
 L3 Cache: None
 Other Cache: None
 Memory: 8GB
 Disk Subsystem: 12 x 36GB
 Other Hardware: None

Software

Operating System: Solaris 8 02/02
 Compiler: Sun ONE Studio 7
 with patch 111704-01
 Sun Performance Library 7
 File System: ufs
 System State: Single-User

Notes/Tuning Information

Portability:

```
176.gcc: -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
252.eon: -library=iostream
253.perlbnk: -DSPEC_CPU2000_SOLARIS
254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
        -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO
```

-xprofile: PASS1=-xprofile=collect, PASS2=-xprofile=use

Base Flags:

```
Base C flags: -fast -xcrossfile -l12amm -xprofile
Base C++ flags: -fast -xcrossfile -xprofile
```

Peak Flags:

```
164.gzip: -xO5 -xtarget=native -xalias_level=std -W2,-whole -xcrossfile -W2,-Ainline -xprofile
175.vpr: -fast -xalias_level=std -xcrossfile -xsfpcnst -W2,-whole
        -Wc,-Qeps:enabled=1,-Qeps:do_spec_load=1,-Qeps:rp_filtering_margin=100
        -xregs=syst -lmopt -xprofile
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V880

SPECint_rate2000 = 23.9
SPECint_rate_base2000 = 21.1

SPEC license #: 6 | Tested by: Sun Microsystems, Palo Alto | Test date: May-2002 | Hardware Avail: Jun-2002 | Software Avail: May-2002

Notes/Tuning Information (Continued)

```

176.gcc: -fast -xcrossfile -W2,-whole -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -l12amm -xprofile
181.mcf: -fast -xcrossfile -Wc,-Qms_pipe-pref,-Qlp=1-fa=1-av=64-t=3-fl=1
        -lprism32 -xprofile
186.crafty: -fast -xF -xinline= -xcrossfile -Wc,-Qgsched-trace_late=1,-Qgsched-T4
        -xalias_level=strong -xregs=syst -W2,-Ashort_ldst,-Aivel:duplicate_loops
        -xprofile
197.parser: -fast -xprefetch=no%auto -xcrossfile -xregs=syst
        -Wc,-Qgsched-trace_late=1,-Qgsched-T4 -xalias_level=strong -Wc,-Qipa:valueprediction -xprofile
252.eon: -fast -xcrossfile -xalias_level=compatible -xsafe=mem -Qoption iropt -Mt500,-xrestrict
        -Qoption cg -Qgsched-trace_late=1,-Qgsched-T4 -lmopt -xprofile
253.perlbnk: -xO5 -xtarget=native -xcrossfile -xalias_level=std -xsafe=mem
        -Wc,-Qgsched-trace_late=1,-Qgsched-T4,-Qgsched-trace_spec_load=1
        -Wc,-Qinline_memcpy=32 -Wc,-Qiselect-funcalign=32,-Qicache-chbab=1
        -Wc,-Qiselect-sw_pf_tbl_th=20 -xprofile
254.gap: -fast -xcrossfile -xalias_level=std -xprefetch -W2,-whole -lprism32 -xprofile
255.vortex: -fast -xcrossfile -Wc,-Qeps:enabled=1,-Qeps:do_spec_load=1
        -Wc,-Qinline_memcpy=32 -W2,-Aheap,-reroll=1,-Aunroll,-Ms1,-Mt500,-Mr6000,-crit
        -Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=32
        -Wc,-Qpeep-Sh0 -xrestrict -l12amm -lprism32 -xprofile
256.bzip2: -fast -W2,-Abopt -xcrossfile -xalias_level=strong
        -Wc,-Qiselect-funcalign=32 -xregs=syst -xprofile
300.twolf: -fast -xalias_level=strong -xsafe=mem -xcrossfile -xprefetch=no%auto
        -Wc,-Qms_pipe+intdivusefp -xprofile
ONESTEP=yes for all benchmarks in base and peak

```

Shell Environments:

```

LD_LIBRARY_PATH=/usr/lib:/opt/SUNWspro/lib/v8plusb:/opt/SUNWspro/prod/lib/v8plusb
PRISM_HEAP=268435456
PRISM_MODE=2

```

Stack size set to unlimited via "ulimit -s unlimited"

Kernel Parameters (/etc/system):

```

set shmsys:shminfo_shmmin=1
set shmsys:shminfo_shmmax=1477846784
set shmsys:shminfo_shmmni=256
set shmsys:shminfo_shmseg=400

```

System configuration details located (as of Jun 2002) at
<http://www.sun.com/servers/entry/>