



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMVR motherboard (2.67 GHz, Pentium 4 processor)

SPECfp2000 = 1024

SPECfp_base2000 = 1012

SPEC license #: 13 Tested by: Intel Corporation Test date: Jul-2002 Hardware Avail: Oct-2002 Software Avail: Apr-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	127	1259	127	1260	
171.swim	3100	174	1777	172	1800	
172.mgrid	1800	185	975	183	982	
173.applu	2100	194	1081	190	1106	
177.mesa	1400	136	1030	135	1035	
178.galgel	2900	204	1425	202	1437	
179.art	2600	383	679	377	689	
183.quake	1300	109	1191	104	1253	
187.facerec	1900	158	1199	157	1209	
188.ammmp	2200	335	656	332	662	
189.lucas	2000	137	1455	137	1455	
191.fma3d	2100	210	999	210	1001	
200.sixtrack	1100	226	487	221	499	
301.apsi	2600	344	755	344	755	

Hardware

CPU: Pentium 4 processor (2.67 GHz, 533 MHz bus)
 CPU MHz: 2666
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 12k micro-ops I + 8KBD on chip
 Secondary Cache: 512KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 256 MB (2 128 MB PC1066-32 RDRAM non-ECC modules)
 Disk Subsystem: IBM 120GXP 80 GB IC35L080AVVA07-0 ATA-100
 Other Hardware: None

Software

Operating System: Windows XP Professional(Build 2600)
 Compiler: Intel C++ Compiler 6.0 Build 020321Z
 Intel Fortran Compiler 6.0 Build 020321Z
 Microsoft Visual C++ 6.0 SP5(for libraries)
 File System: FAT32
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning: -Qipo -QxW -O3 +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxW -O3 +FDO
171.swim: -Qipo -QxW -O3 +FDO
172.mgrid: -Qipo -QaxW -O3 +FDO
173.applu: -Qipo -QxW -O3 -Qscalar_rep- -Qauto +FDO
177.mesa: -Qipo -Oa -QxW -O3 +FDO
178.galgel: -Qipo -QxW -O3 +FDO
179.art: -Qipo -QxW -O3 -Oa +FDO
183.quake: -Qipo -QxW -Oa -Qrcd +FDO
187.facerec: -Qipo -QxW -O3 +FDO
188.ammmp: -Qipo -QxW -O3 -Oa +FDO
189.lucas: -Qipo -QxW -O3 +FDO
191.fma3d: -Qipo -QxW -O3 +FDO
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMVR motherboard (2.67 GHz, Pentium 4 processor)

SPECfp2000 = 1024

SPECfp_base2000 = 1012

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Jul-2002 | Hardware Avail: Oct-2002 | Software Avail: Apr-2002

Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxW +FDO

301.apsi: -Qipo -QxW -O3 +FDO

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B

Product description located as of 10/2002:

<http://developer.intel.com/design/motherbd/mv2/index.htm>

Motherboard ordering information is available at:

<http://program.intel.com/shared/products/boards/d850emv2/index.htm>

The system bus runs at 533 MHz