



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation
IBM eServer p5 570 (1900 MHz, 1 CPU)

SPECfp2000 = 2702
SPECfp_base2000 = 2576

SPEC license #: 11 Tested by: IBM Test date: Jun-2004 Hardware Avail: Sep-2004 Software Avail: Oct-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	66.0	2422	50.3	3179
171.swim	3100	79.9	3878	79.9	3878
172.mgrid	1800	68.7	2622	68.7	2622
173.applu	2100	82.4	2549	84.3	2490
177.mesa	1400	117	1195	117	1195
178.galgel	2900	57.6	5036	44.4	6537
179.art	2600	26.2	9927	26.2	9927
183.quake	1300	26.2	4960	26.2	4960
187.facerec	1900	80.1	2371	80.1	2371
188.amp	2200	160	1374	159	1386
189.lucas	2000	51.4	3889	49.7	4025
191.fma3d	2100	120	1745	120	1745
200.sixtrack	1100	130	849	126	874
301.apsi	2600	160	1627	147	1771

Hardware

CPU: POWER5
 CPU MHz: 1900
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 2 cores/chip (SMT off)
 CPU(s) orderable: 2,4,8,12,16
 Parallel: No
 Primary Cache: 64KBI+32KBD (on chip)/core
 Secondary Cache: 1920KB unified (on chip)/chip
 L3 Cache: 36MB unified (off chip)/DCM, 2 DCM/SUT
 Other Cache: none
 Memory: 16x1 GB DDR2
 Disk Subsystem: 1x36GB SCSI, 15K RPM
 Other Hardware:

Software

Operating System: AIX 5L V5.3
 Compiler: XL C/C++ Enterprise Edition Version 7.0 for AIX
 XL Fortran Enterprise Edition V9.1 for AIX
 Other Software: IBM Engineering and Scientific Subroutine Library for AIX, Version 4 Release 2
 File System: AIX/JFS2
 System State: Multi-User

Notes/Tuning Information

Portability Flags

-qfixed used in: 168.wupwise, 171.swim, 172.mgrid, 173.applu,
 178.galgel, 200.sixtrack, 301.apsi
 -qsuffix=f=f90 used in: 178.galgel, 187.facerec, 189.lucas, 191.fma3d

Base Optimization Flags:

C: -qpdf1/pdf2 -O5 -blpdata -qalign=natural
 Fortran: -qpdf1/pdf2 -O5 -blpdata -lmass

Peak Optimization Flags

168.wupwise: -O5 -qarch=pwr3 -qtune=pwr3 -blpdata -lmass
 F77 = xlf
 171.swim: basepeak = 1
 172.mgrid: basepeak = 1
 173.applu: -O5 -blpdata -lmass



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

IBM Corporation
IBM eServer p5 570 (1900 MHz, 1 CPU)

SPECfp2000 = 2702
SPECfp_base2000 = 2576

SPEC license #: 11 | Tested by: IBM | Test date: Jun-2004 | Hardware Avail: Sep-2004 | Software Avail: Oct-2004

Notes/Tuning Information (Continued)

```

177.mesa:      basepeak = 1
178.galgel:    -O5 -blpdata -qessl -lessl
179.art:       basepeak = 1
183.earthquake: basepeak = 1
187.facerec:   basepeak = 1
188.ammp:      -qpdl1/pdf2
               -O5 -blpdata -qalign=natural -D_ILS_MACROS
189.lucas:     -O5 -blpdata -lmass
191.fma3d:     basepeak = 1
200.sixtrack:  fdpr -quiet -R3
               -O3 -qhot -qarch=pwr5 -qtune=pwr5 -qfdpr
301.apsi:      -O5 -lmass -qessl -lessl -blpdata -qsave

```

SMT: Acronym for "Simultaneous Multi-Threading". A processor technology that allows the simultaneous execution of multiple thread contexts within a single processor core. (Enabled by default)

DCM: Acronym for "Dual-Chip Module" (one dual-core processor chip + one L3-cache chip)

SUT: Acronym for "System Under Test"

ulimits set to unlimited.

Large page mode was set as follows:

```

vmo -r -o lpgg_regions=400 -o lpgg_size=16777216
chuser capabilities=CAP_BYPASS_RAC_VMM,CAP_PROPAGATE $USER
reboot -q

```

Three cores were deconfigured and SMT disabled at the open-firmware prompt, using the command

```

boot -s cpu=1 -s smt_off

```