



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated
Altos R510 (3.0 GHz Intel Xeon)

SPECint2000 = 1303
SPECint_base2000 = 1300

SPEC license #: 97 Tested by: Acer Incorporated Test date: May-2005 Hardware Avail: May-2005 Software Avail: Oct-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	1000 2000 3000 4000			
164.gzip	1400	140	1000	140	1000	[Bar chart showing ratio 1000]			
175.vpr	1400	171	817	168	832	[Bar chart showing ratio 832]			
176.gcc	1100	70.1	1569	70.1	1569	[Bar chart showing ratio 1569]			
181.mcf	1800	175	1027	175	1027	[Bar chart showing ratio 1027]			
186.crafty	1000	90.0	1111	90.0	1111	[Bar chart showing ratio 1111]			
197.parser	1800	159	1131	159	1131	[Bar chart showing ratio 1131]			
252.eon	1300	69.0	1885	68.7	1893	[Bar chart showing ratio 1893]			
253.perlbmk	1800	105	1710	105	1712	[Bar chart showing ratio 1712]			
254.gap	1100	68.7	1602	68.7	1602	[Bar chart showing ratio 1602]			
255.vortex	1900	88.4	2148	88.4	2148	[Bar chart showing ratio 2148]			
256.bzip2	1500	166	903	165	907	[Bar chart showing ratio 907]			
300.twolf	3000	214	1404	214	1403	[Bar chart showing ratio 1403]			

Hardware

CPU: Intel Xeon (3.0 GHz, 1MB L2, 800MHz system bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip(Hyper-Threading Technology disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12KB(I) micro-ops + 16KB(D) on chip
Secondary Cache: 1024KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 6 x 512MB ECC DDR-333 SDRAM
Disk Subsystem: 1 x 80GB 7200RPM SATA HDD
Other Hardware:

Software

Operating System: Microsoft Windows Server 2003 Enterprise Edition (Build 3790)
Compiler: Intel C++ Compiler 8.1 Build 20041019Z
Microsoft Visual Studio .Net 2003(7.1.3091, for libraries)
SmartHeap Library Version 7.4 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlW32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafy: -DNT_i386
252.eon: Approved stdcpp src.alt used
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: basepeak=yes
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: basepeak=yes
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbmk: -fast -Qansi_alias +FDO shlW32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Acer Incorporated
Altos R510 (3.0 GHz Intel Xeon)

SPECint2000 =	1303
SPECint_base2000 =	1300

SPEC license #: 97	Tested by: Acer Incorporated	Test date: May-2005	Hardware Avail: May-2005	Software Avail: Oct-2004
--------------------	------------------------------	---------------------	--------------------------	--------------------------

Notes/Tuning Information (Continued)

256.bzip2: -fast -Oa -Qunroll1 +FDO
300.twolf: -fast -O3 +FDO shlw32M.lib
Enable hardware prefetching and adjacent cache line prefetch BIOS setting
Product description located at <http://www.acer.com>