



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) D975XBX motherboard(3.73 GHz, Intel(R) Pentium(R) processor Extreme Edition 965)

SPECint_rate2000 = 43.7

SPECint_rate_base2000 = 43.7

SPEC license #: 13 Tested by: Intel(R) Corporation Test date: Mar-2006 Hardware Avail: Mar-2006 Software Avail: Apr-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	168	38.6	4	170	38.2
175.vpr	4	230	28.3	4	226	28.7
176.gcc	4	85.9	59.4	4	85.9	59.4
181.mcf	4	276	30.3	4	276	30.3
186.crafty	4	141	32.9	4	141	32.9
197.parser	4	194	43.2	4	193	43.4
252.eon	4	113	53.6	4	113	53.2
253.perlbnk	4	174	48.1	4	174	47.9
254.gap	4	106	48.0	4	106	48.0
255.vortex	4	124	71.1	4	124	71.1
256.bzip2	4	179	38.8	4	180	38.8
300.twolf	4	270	51.5	4	270	51.6

Hardware

CPU: Intel(R) Pentium(R) processor Extreme Edition 965(3.73 GHz, 1066 MHz bus)
CPU MHz: 3733
FPU: Integrated
CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip (Hyper-Threading Technology enabled)
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 16KBD per core
Secondary Cache: 2MB(I+D) per core
L3 Cache: N/A
Other Cache: N/A
Memory: 1 GB (2 512MB Micron MT16HTF6464AY-667B3 DDR2 667 CL5-5-5 DIMMs)
Disk Subsystem: Maxtor DiamondMax 10 6B300S0 300GB NCO Serial ATA (7200 RPM, 16MB cache)
Other Hardware: ATI Radeon X1900 XTX PCI express

Software

Operating System: Windows XP Professional SP2
Compiler: Intel(R) C++ Compiler 9.0 for 32-bit Build 20050430Z
Microsoft Visual Studio .Net 2003(for libraries)
SmartHeap Library Version 7.4 from <http://www.microquill.com/>
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast -Qansi_alias -Oa +FDO
175.vpr: -fast -Qansi_alias +FDO
176.gcc: basepeak=yes
181.mcf: basepeak=yes
186.crafty: -fast -Qansi_alias -Oa +FDO
197.parser: -fast -Qansi_alias +FDO
252.eon: -fast +FDO
253.perlbnk: -fast -Qansi_alias +FDO shlw32M.lib
254.gap: basepeak=yes
255.vortex basepeak=yes
Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Intel(R) Corporation

Intel(R) D975XBX motherboard(3.73 GHz, Intel(R) Pentium(R) processor Extreme Edition 965)

SPECint_rate2000 = 43.7

SPECint_rate_base2000 = 43.7

SPEC license #: 13 | Tested by: Intel(R) Corporation | Test date: Mar-2006 | Hardware Avail: Mar-2006 | Software Avail: Apr-2005

Notes/Tuning Information (Continued)

Product description located as of 03/2006
<http://www.intel.com/products/motherboard/D975XBX/index.htm>
The system bus runs at 1066 MHz