



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL460c (1.60 GHz, Intel Xeon processor 5110)

SPECint_rate2000 = **71.3**
SPECint_rate_base2000 = **71.0**

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2006 Hardware Avail: Jun-2006 Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	144	45.0	4	144	45.0
175.vpr	4	127	51.2	4	121	53.5
176.gcc	4	63.2	80.8	4	63.2	80.8
181.mcf	4	114	73.2	4	114	73.1
186.crafty	4	68.4	67.8	4	68.5	67.8
197.parser	4	145	57.7	4	144	58.0
252.eon	4	62.3	96.9	4	62.4	96.6
253.perlbnk	4	95.9	87.1	4	95.5	87.4
254.gap	4	72.5	70.4	4	72.0	70.9
255.vortex	4	74.5	118	4	74.3	119
256.bzip2	4	135	51.6	4	135	51.6
300.twolf	4	165	84.4	4	165	84.4

Hardware

CPU: Intel Xeon processor 5110 (1.60 GHz, 4 MB L2 shared, 1066 MHz bus)
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2 chips
Parallel: No
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4 MB I+D on chip per chip
L3 Cache: N/A
Other Cache: N/A
Memory: 16 GB (8x2048 MB PC2-5300F)
Disk Subsystem: 2x36 GB 10 K SAS
Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
Compiler: Intel C++ Compiler for 32-bit applications, (Version 9.1 Build 20060323Z) Microsoft Visual Studio .NET 7.0.9466 (for libraries) MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO ONESTEP=yes shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO ONESTEP=yes
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -fast +FDO ONESTEP=yes
175.vpr: -fast +FDO ONESTEP=yes
176.gcc: basepeak=1
181.mcf: -fast +FDO ONESTEP=yes shlw32M.lib
186.crafty: -fast -Oa +FDO ONESTEP=yes shlw32M.lib
197.parser: -fast +FDO ONESTEP=yes
252.eon: -fast +FDO
253.perlbnk: -fast -Oa +FDO ONESTEP=yes shlw32M.lib
254.gap: -fast +FDO ONESTEP=yes
255.vortex: -fast +FDO ONESTEP=yes shlw32M.lib
256.bzip2: basepeak=1
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant BL460c (1.60 GHz, Intel Xeon processor 5110)

SPECint_rate2000 = 71.3
SPECint_rate_base2000 = 71.0

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Aug-2006 Hardware Avail: Jun-2006 Software Avail: May-2006

Notes/Tuning Information (Continued)

300.twolf: -fast +FDO shlw32M.lib
BIOS Configuration Notes
Power Regulator set to Static High Performance Mode
Adjacent Sector Prefetch Disabled