



CFP2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

IBM Corporation

IBM System X 3550 (2.00 GHz Xeon E5335, 8MB L2 Cache)

SPECfp2000 = --

SPECfp_base2000 = 2023

SPEC license #: 11 Tested by: IBM Corporation Test date: Jan-2007 Hardware Avail: Feb-2007 Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	54.9	2917		
171.swim	3100	120	2585		
172.mgrid	1800	138	1307		
173.applu	2100	135	1561		
177.mesa	1400	72.4	1934		
178.galgel	2900	59.8	4846		
179.art	2600	37.5	6936		
183.earthquake	1300	51.0	2549		
187.facerec	1900	95.9	1980		
188.amp	2200	151	1459		
189.lucas	2000	111	1799		
191.fma3d	2100	138	1521		
200.sixtrack	1100	138	800		
301.apsi	2600	217	1197		

Hardware

CPU: Intel Xeon processor E5335 (2.0 GHz, 1333 MHz bus)
 CPU MHz: 2000
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1, 2 chips
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
 Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 x 1024 MB ECC PC2-5300F
 Disk Subsystem: 73GB SATA 10k RPM
 Other Hardware:

Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
 Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications
 Build 20060323Z
 Microsoft Visual Studio 2005(for libraries)
 SmartHeap Library Version 8.0 from <http://www.microquill.com/>
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlw32M.lib
Portability:
178.galgel: -FI /F32000000
```