



CINT2000 Result

Copyright ©1999-2007, Standard Performance Evaluation Corporation

IBM Corporation

IBM BladeCenter HS21 XM (1.86 GHz Xeon 5120, 4MB L2 Cache)

SPECint_rate2000 = --

SPECint_rate_base2000 = 79.3

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Jan-2007 | Hardware Avail: Feb-2007 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	124	52.4			
175.vpr	4	114	57.0			
176.gcc	4	59.6	85.7			
181.mcf	4	113	74.0			
186.crafty	4	57.8	80.2			
197.parser	4	136	61.4			
252.eon	4	53.8	112			
253.perlbnk	4	82.3	101			
254.gap	4	66.0	77.4			
255.vortex	4	67.0	132			
256.bzip2	4	120	58.1			
300.twolf	4	141	98.8			

Hardware

CPU: Intel Xeon processor 5120 (1.86 GHz, 1066 MHz bus)
 CPU MHz: 1866
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1, 2
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip (per core)
 Secondary Cache: 4096KB(I+D) on chip (per chip)
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 x 2048 MB ECC PC2-5300F
 Disk Subsystem: 73GB SAS 10K RPM
 Other Hardware:

Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
 Compiler: Intel C++ Compiler 9.1 for 32-bit applications
 Build 20060323Z
 Microsoft Visual Studio 2005(for libraries)
 SmartHeap Library Version 8.0 from <http://www.microquill.com/>
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast +FDO shlw32M.lib
Base tuning for C++ programs: -fast -Qcxx_features +FDO shlw32M.lib
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
252.eon: -DHAS_ERRLIST
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
```