



SPEC[®] CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECint[®]2006 = 16.9

Bull Escala PL160 (4.2 GHz, 1 core)

SPECint_base2006 = 14.5

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Feb-2008

Hardware Availability: Mar-2008

Software Availability: Feb-2008



Hardware

CPU Name: POWER6
 CPU Characteristics:
 CPU MHz: 4200
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1 core
 Primary Cache: 64 KB I + 64 KB D on chip per chip
 Secondary Cache: 4 MB I+D on chip per chip
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8x2 GB) DDR2 667 MHz
 Disk Subsystem: 2x73 GB SAS 15K RPM
 Other Hardware: None

Software

Operating System: IBM AIX V6.1 Updated to SP3
 Compiler: XL C/C++ Enterprise Edition V9 for AIX Updated with the Oct2007 PTF.
 Auto Parallel: No
 File System: AIX/JFS2
 System State: Multi-user
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: --



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECint2006 = **16.9**

Bull Escala PL160 (4.2 GHz, 1 core)

SPECint_base2006 = **14.5**

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Feb-2008
Hardware Availability: Mar-2008
Software Availability: Feb-2008

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	951	10.3	953	10.3	<u>952</u>	<u>10.3</u>	<u>880</u>	<u>11.1</u>	880	11.1	880	11.1
401.bzip2	<u>884</u>	<u>10.9</u>	884	10.9	885	10.9	675	14.3	675	14.3	<u>675</u>	<u>14.3</u>
403.gcc	636	12.7	637	12.6	<u>636</u>	<u>12.6</u>	551	14.6	<u>551</u>	<u>14.6</u>	551	14.6
429.mcf	380	24.0	<u>381</u>	<u>24.0</u>	381	24.0	363	25.1	<u>363</u>	<u>25.1</u>	364	25.1
445.gobmk	759	13.8	759	13.8	<u>759</u>	<u>13.8</u>	662	15.8	<u>662</u>	<u>15.8</u>	662	15.8
456.hmmer	<u>869</u>	<u>10.7</u>	869	10.7	868	10.7	611	15.3	610	15.3	<u>610</u>	<u>15.3</u>
458.sjeng	<u>964</u>	<u>12.5</u>	964	12.5	965	12.5	862	14.0	<u>862</u>	<u>14.0</u>	862	14.0
462.libquantum	497	41.7	<u>497</u>	<u>41.7</u>	497	41.7	392	52.8	392	52.8	<u>392</u>	<u>52.8</u>
464.h264ref	882	25.1	882	25.1	<u>882</u>	<u>25.1</u>	802	27.6	<u>801</u>	<u>27.6</u>	800	27.7
471.omnetpp	627	9.96	628	9.96	<u>628</u>	<u>9.96</u>	554	11.3	<u>554</u>	<u>11.3</u>	554	11.3
473.astar	703	9.98	<u>703</u>	<u>9.98</u>	703	9.98	<u>610</u>	<u>11.5</u>	610	11.5	610	11.5
483.xalancbmk	522	13.2	<u>522</u>	<u>13.2</u>	521	13.2	463	14.9	462	14.9	<u>463</u>	<u>14.9</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

See flags file of details on following settings.
all ulimits set to unlimited.
Environment variables set before executing benchmarks:
MALLOCOPTIONS=pool
MEMORY_AFFINITY=MCM
XLFRTOPTS=intrinthds=1
System set to "Enhanced" mode when defining partition on HMC.
500 16M large pages defined with vmo command
Remote console disabled in /etc/inittab.
fdpr binary optimization tool used for:
400.perlbench 401.bzip2 403.gcc 429.mcf 456.hmmer
458.sjeng 462.libquantum 464.h264ref 473.astar
Measurement has been done on a PL260 with one core disabled by HMC.
PL260 and PL160 are identical machines; the only difference is that
PL160 uses a single core POWER6 chip instead a dual core chip.

Base Compiler Invocation

C benchmarks:
/usr/vac/bin/xlc -qlanglvl=extc99

C++ benchmarks:
/usr/vacpp/bin/xlC



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECint2006 = 16.9

Bull Escala PL160 (4.2 GHz, 1 core)

SPECint_base2006 = 14.5

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Feb-2008
Hardware Availability: Mar-2008
Software Availability: Feb-2008

Base Portability Flags

400.perlbench: -DSPEC_CPU_AIX
462.libquantum: -DSPEC_CPU_AIX
464.h264ref: -DSPEC_CPU_AIX -qchars=signed
483.xalancbmk: -DSPEC_CPU_AIX

Base Optimization Flags

C benchmarks:
-bmaxdata:0x50000000 -O5 -qlargepage -D_ILS_MACROS -qalias=noansi
-qalloca -blpdata

C++ benchmarks:
-bmaxdata:0x20000000 -O5 -qlargepage -D_ILS_MACROS -qrtti=all
-blpdata

Base Other Flags

C benchmarks:
-qipa=noobject -qipa=threads -qsuppress=1500-036

C++ benchmarks:
-qipa=noobject -qipa=threads -qsuppress=1500-036

Peak Compiler Invocation

C benchmarks:
/usr/vac/bin/xlc -qlanglvl=extc99

C++ benchmarks:
/usr/vacpp/bin/xlC

Peak Portability Flags

400.perlbench: -DSPEC_CPU_AIX
403.gcc: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_AIX
464.h264ref: -DSPEC_CPU_AIX -qchars=signed
483.xalancbmk: -DSPEC_CPU_AIX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECint2006 = 16.9

Bull Escala PL160 (4.2 GHz, 1 core)

SPECint_base2006 = 14.5

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Feb-2008
Hardware Availability: Mar-2008
Software Availability: Feb-2008

Peak Optimization Flags

C benchmarks:

400.perlbench: -bmaxdata:0x50000000 -qpdf1(pass 1) -qpdf2(pass 2) -O4
-qlargepage -qenablevmx -qvecnvols -D_ILS_MACROS
-qalias=noansi -qfdpr -blpdata

401.bzip2: -bmaxdata:0x4ffffffc -qpdf1(pass 1) -qpdf2(pass 2) -O5
-qlargepage -qenablevmx -qvecnvols -D_ILS_MACROS -qfdpr
-blpdata

403.gcc: -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qlargepage
-D_ILS_MACROS -qalloca -qfdpr -q64 -blpdata

429.mcf: -bmaxdata:0x50000000 -O5 -qlargepage -qenablevmx
-qvecnvols -D_ILS_MACROS -qfdpr -blpdata

445.gobmk: -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qlargepage -qenablevmx
-qvecnvols -D_ILS_MACROS -blpdata

456.hmmr: -O5 -qlargepage -D_ILS_MACROS -qfdpr -blpdata

458.sjeng: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qlargepage -qenablevmx
-qvecnvols -D_ILS_MACROS -qfdpr -blpdata

462.libquantum: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qlargepage -qenablevmx
-qvecnvols -D_ILS_MACROS -q64 -qfdpr -blpdata

464.h264ref: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -q64 -D_ILS_MACROS
-qenablevmx -qvecnvols -qfdpr -bdatapsize:64K
-bstacksize:64K -btextpsize:64K

C++ benchmarks:

471.omnetpp: -bmaxdata:0x20000000 -qpdf1(pass 1) -qpdf2(pass 2) -O5
-qlargepage -qenablevmx -qvecnvols -D_ILS_MACROS
-qalign=natural -qrtti=all -qinlglue -blpdata

473.astar: -bmaxdata:0x20000000 -qpdf1(pass 1) -qpdf2(pass 2) -O5
-qlargepage -D_ILS_MACROS -qfdpr -qinlglue
-qalign=natural -blpdata

483.xalancbmk: -bmaxdata:0x20000000 -qpdf1(pass 1) -qpdf2(pass 2) -O5
-qlargepage -D_ILS_MACROS -qinlglue -D__IBM_FAST_VECTOR
-blpdata



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

SPECint2006 = 16.9

Bull Escala PL160 (4.2 GHz, 1 core)

SPECint_base2006 = 14.5

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Feb-2008
Hardware Availability: Mar-2008
Software Availability: Feb-2008

Peak Other Flags

C benchmarks:

-qipa=noobject -qipa=threads -qsuppress=1500-036

C++ benchmarks:

-qipa=noobject -qipa=threads -qsuppress=1500-036

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090713.06.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090713.06.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 18:19:10 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 15 April 2008.