



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

SPECfp®2006 = 16.5

IBM System x3200 M2 (Intel Core 2 Duo E4600)

SPECfp\_base2006 = 15.6

CPU2006 license: 11


Test date: Feb-2008

Test sponsor: IBM Corporation

Hardware Availability: Feb-2008

Tested by: IBM Corporation

Software Availability: Nov-2007



**Hardware**

CPU Name: Intel Core 2 Duo E4600  
 CPU Characteristics: 800MHz system bus  
 CPU MHz: 2400  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 2 MB I+D on chip per chip

Continued on next page

**Software**

Operating System: SuSE Linux Enterprise Server 10 (x86\_64) SP1, Kernel 2.6.16.46-0.12-smp  
 Compiler: Intel C++ and Fortran Compiler 10.1 for Linux Build 20070913 Package ID: l\_cc\_p\_10.1.008, l\_fc\_p\_10.1.008  
 Auto Parallel: Yes  
 File System: ReiserFS  
 System State: Multi-user, run level 3  
 Base Pointers: 64-bit

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

SPECfp2006 = **16.5**

IBM System x3200 M2 (Intel Core 2 Duo E4600)

SPECfp\_base2006 = **15.6**

CPU2006 license: 11  
Test sponsor: IBM Corporation  
Tested by: IBM Corporation

Test date: Feb-2008  
Hardware Availability: Feb-2008  
Software Availability: Nov-2007

L3 Cache: None  
Other Cache: None  
Memory: 8 GB (4 x 2 GB DDR2-5300 ECC)  
Disk Subsystem: 1 x 146 GB SAS, 15000 RPM  
Other Hardware: None

Peak Pointers: 32/64-bit  
Other Software: Binutils 2.17.50.0.15

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	542	25.1	<b><u>541</u></b>	<b><u>25.1</u></b>	540	25.2	538	25.3	537	25.3	<b><u>538</u></b>	<b><u>25.3</u></b>
416.gamess	1145	17.1	<b><u>1147</u></b>	<b><u>17.1</u></b>	1148	17.1	<b><u>1137</u></b>	<b><u>17.2</u></b>	1136	17.2	1139	17.2
433.milc	850	10.8	854	10.7	<b><u>851</u></b>	<b><u>10.8</u></b>	848	10.8	865	10.6	<b><u>865</u></b>	<b><u>10.6</u></b>
434.zeusmp	<b><u>671</u></b>	<b><u>13.6</u></b>	671	13.6	670	13.6	656	13.9	656	13.9	<b><u>656</u></b>	<b><u>13.9</u></b>
435.gromacs	481	14.9	480	14.9	<b><u>480</u></b>	<b><u>14.9</u></b>	<b><u>474</u></b>	<b><u>15.1</u></b>	474	15.1	475	15.0
436.cactusADM	456	26.2	457	26.2	<b><u>457</u></b>	<b><u>26.2</u></b>	421	28.4	424	28.2	<b><u>422</u></b>	<b><u>28.3</u></b>
437.leslie3d	714	13.2	715	13.1	<b><u>714</u></b>	<b><u>13.2</u></b>	714	13.2	715	13.1	<b><u>714</u></b>	<b><u>13.2</u></b>
444.namd	<b><u>629</u></b>	<b><u>12.7</u></b>	630	12.7	629	12.8	624	12.9	626	12.8	<b><u>625</u></b>	<b><u>12.8</u></b>
447.dealII	<b><u>493</u></b>	<b><u>23.2</u></b>	492	23.3	494	23.1	459	24.9	<b><u>463</u></b>	<b><u>24.7</u></b>	464	24.7
450.soplex	687	12.1	<b><u>689</u></b>	<b><u>12.1</u></b>	690	12.1	634	13.2	<b><u>635</u></b>	<b><u>13.1</u></b>	637	13.1
453.povray	<b><u>271</u></b>	<b><u>19.6</u></b>	271	19.6	271	19.7	230	23.1	<b><u>230</u></b>	<b><u>23.1</u></b>	230	23.1
454.calculix	645	12.8	<b><u>645</u></b>	<b><u>12.8</u></b>	645	12.8	446	18.5	<b><u>447</u></b>	<b><u>18.5</u></b>	447	18.5
459.GemsFDTD	<b><u>850</u></b>	<b><u>12.5</u></b>	850	12.5	852	12.4	<b><u>843</u></b>	<b><u>12.6</u></b>	842	12.6	845	12.6
465.tonto	654	15.1	<b><u>655</u></b>	<b><u>15.0</u></b>	663	14.8	626	15.7	<b><u>627</u></b>	<b><u>15.7</u></b>	629	15.6
470.lbm	1109	12.4	<b><u>1110</u></b>	<b><u>12.4</u></b>	1112	12.4	986	13.9	<b><u>988</u></b>	<b><u>13.9</u></b>	989	13.9
481.wrf	<b><u>611</u></b>	<b><u>18.3</u></b>	611	18.3	610	18.3	644	17.3	<b><u>644</u></b>	<b><u>17.3</u></b>	643	17.4
482.sphinx3	1205	16.2	<b><u>1204</u></b>	<b><u>16.2</u></b>	1202	16.2	1137	17.1	1171	16.6	<b><u>1148</u></b>	<b><u>17.0</u></b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

All benchmarks compiled in 64-bit mode except 450.soplex, 470.lbm and 482.sphinx3, at peak, are compiled in 32-bit mode  
OMP\_NUM\_THREADS set to number of cores  
KMP\_AFFINITY set to physical,0  
KMP\_STACKSIZE set to 200M

## Base Compiler Invocation

C benchmarks:  
icc

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp2006 = 16.5

IBM System x3200 M2 (Intel Core 2 Duo E4600)

SPECfp\_base2006 = 15.6

CPU2006 license: 11

Test date: Feb-2008

Test sponsor: IBM Corporation

Hardware Availability: Feb-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

## Base Compiler Invocation (Continued)

C++ benchmarks:  
icpc

Fortran benchmarks:  
ifort

Benchmarks using both Fortran and C:  
icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
 416.gamess: -DSPEC\_CPU\_LP64  
 433.milc: -DSPEC\_CPU\_LP64  
 434.zeusmp: -DSPEC\_CPU\_LP64  
 435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
 436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
 437.leslie3d: -DSPEC\_CPU\_LP64  
 444.namd: -DSPEC\_CPU\_LP64  
 447.dealII: -DSPEC\_CPU\_LP64  
 450.soplex: -DSPEC\_CPU\_LP64  
 453.povray: -DSPEC\_CPU\_LP64  
 454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
 459.GemsFDTD: -DSPEC\_CPU\_LP64  
 465.tonto: -DSPEC\_CPU\_LP64  
 470.lbm: -DSPEC\_CPU\_LP64  
 481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
 482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:  
-fast -parallel

C++ benchmarks:  
-fast -parallel

Fortran benchmarks:  
-fast -parallel

Benchmarks using both Fortran and C:  
-fast -parallel



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp2006 = 16.5

IBM System x3200 M2 (Intel Core 2 Duo E4600)

SPECfp\_base2006 = 15.6

CPU2006 license: 11

Test date: Feb-2008

Test sponsor: IBM Corporation

Hardware Availability: Feb-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

## Peak Compiler Invocation

C benchmarks (except as noted below):

```
/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include
```

```
433.milc: icc
```

C++ benchmarks (except as noted below):

```
icpc
```

```
450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include
```

Fortran benchmarks:

```
ifort
```

Benchmarks using both Fortran and C:

```
icc ifort
```

## Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

## Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32
```

```
470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-scalar-req- -prefetch -opt-malloc-options=3
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp2006 = 16.5

IBM System x3200 M2 (Intel Core 2 Duo E4600)

SPECfp\_base2006 = 15.6

CPU2006 license: 11

Test date: Feb-2008

Test sponsor: IBM Corporation

Hardware Availability: Feb-2008

Tested by: IBM Corporation

Software Availability: Nov-2007

## Peak Optimization Flags (Continued)

482.sphinx3: -fast -unroll2

### C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32

447.dealIII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast  
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4  
-ansi-alias

### Fortran benchmarks:

410.bwaves: -fast -prefetch -parallel

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: basepeak = yes

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-prefetch -parallel

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

### Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -parallel -prefetch -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090713.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090713.xml>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp2006 = 16.5

IBM System x3200 M2 (Intel Core 2 Duo E4600)

SPECfp\_base2006 = 15.6

CPU2006 license: 11

Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Feb-2008

Hardware Availability: Feb-2008

Software Availability: Nov-2007

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 18:23:46 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 15 April 2008.