



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## SGI

SGI Altix XE 250 (Intel Xeon X5272 3.4GHz)

SPECfp<sup>®</sup>\_rate2006 = 62.3

SPECfp\_rate\_base2006 = 55.6

CPU2006 license: 4


Test sponsor: SGI

Tested by: SGI

Test date: May-2008

Hardware Availability: Feb-2008

Software Availability: Apr-2008



### Hardware

CPU Name: Intel Xeon X5272  
 CPU Characteristics: Dual Core, 3.4 GHz  
 CPU MHz: 3391  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 6 MB I+D on chip per chip

Continued on next page

### Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP1  
 Kernel 2.6.16.46-0.12-smp  
 Compiler: Intel C++ and Fortran Compiler for Linux  
 Version 10.1, Build 20070913  
 Auto Parallel: Yes  
 File System: xfs  
 System State: Multi-user, run level 3  
 Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## SGI

SGI Altix XE 250 (Intel Xeon X5272 3.4GHz)

SPECfp\_rate2006 = 62.3

SPECfp\_rate\_base2006 = 55.6

CPU2006 license: 4

Test sponsor: SGI

Tested by: SGI

Test date: May-2008

Hardware Availability: Feb-2008

Software Availability: Apr-2008

L3 Cache: None  
Other Cache: None  
Memory: 8 GB (4\*2GB PC2-6400 CL5-5-5 FB-DIMMs)  
Disk Subsystem: 1 x 300 GB SAS (Seagate Cheetah 15000rpm)  
Other Hardware: None

Other Software: SGI ProPack 5 for Linux Service Pack 5  
Binutils 2.17

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	1310	41.5	1299	41.9	<b>1303</b>	<b>41.7</b>	4	1268	42.9	1262	43.1	<b>1267</b>	<b>42.9</b>
416.gamess	4	784	99.9	<b>785</b>	<b>99.8</b>	786	99.7	4	774	101	776	101	<b>774</b>	<b>101</b>
433.milc	4	1281	28.7	<b>1275</b>	<b>28.8</b>	1275	28.8	4	1294	28.4	1284	28.6	<b>1287</b>	<b>28.5</b>
434.zeusmp	4	605	60.1	604	60.3	<b>605</b>	<b>60.2</b>	4	<b>599</b>	<b>60.8</b>	596	61.1	600	60.7
435.gromacs	4	329	86.7	330	86.5	<b>330</b>	<b>86.6</b>	4	327	87.5	326	87.5	<b>326</b>	<b>87.5</b>
436.cactusADM	4	798	59.9	<b>790</b>	<b>60.5</b>	789	60.6	1	164	72.7	164	73.0	<b>164</b>	<b>72.8</b>
437.leslie3d	4	1167	32.2	1154	32.6	<b>1162</b>	<b>32.4</b>	4	1097	34.3	<b>1096</b>	<b>34.3</b>	1092	34.4
444.namd	4	447	71.7	450	71.2	<b>447</b>	<b>71.7</b>	4	445	72.0	445	72.2	<b>445</b>	<b>72.1</b>
447.dealII	4	460	99.5	<b>460</b>	<b>99.6</b>	459	99.6	4	435	105	<b>435</b>	<b>105</b>	436	105
450.soplex	4	910	36.7	914	36.5	<b>912</b>	<b>36.6</b>	4	816	40.9	<b>815</b>	<b>40.9</b>	815	40.9
453.povray	4	184	116	<b>185</b>	<b>115</b>	186	114	4	158	135	<b>158</b>	<b>135</b>	158	135
454.calculix	4	<b>469</b>	<b>70.4</b>	468	70.5	470	70.3	4	323	102	<b>328</b>	<b>101</b>	329	100
459.GemsFDTD	4	<b>1378</b>	<b>30.8</b>	1348	31.5	1383	30.7	4	1287	33.0	1300	32.6	<b>1298</b>	<b>32.7</b>
465.tonto	4	<b>469</b>	<b>84.0</b>	468	84.2	470	83.8	4	457	86.2	<b>458</b>	<b>86.0</b>	459	85.8
470.lbm	4	<b>2602</b>	<b>21.1</b>	2602	21.1	2601	21.1	2	601	45.7	<b>609</b>	<b>45.1</b>	610	45.0
481.wrf	4	<b>752</b>	<b>59.4</b>	751	59.5	752	59.4	4	751	59.5	752	59.4	<b>752</b>	<b>59.4</b>
482.sphinx3	4	1415	55.1	<b>1402</b>	<b>55.6</b>	1396	55.9	2	642	60.7	<b>633</b>	<b>61.6</b>	629	62.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

Bios settings:

Snoop Filter: Enabled

Hardware Prefetcher: Enabled

Adjacent Sector Prefetch: Enabled

All benchmarks compiled in 64-bit mode except 437.leslie3d, 450.soplex, 470.lbm, and 482.sphinx3, at peak, are compiled in 32-bit mode

The taskset utility was used to bind processes to cores

Parallel settings for 436.cactusADM peak:

OMP\_NUM\_THREADS = 4

KMP\_AFFINITY = physical,0

KMP\_STACKSIZE = 64M



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## SGI

SGI Altix XE 250 (Intel Xeon X5272  
3.4GHz)

SPECfp\_rate2006 = 62.3

SPECfp\_rate\_base2006 = 55.6

CPU2006 license: 4

Test sponsor: SGI

Tested by: SGI

Test date: May-2008

Hardware Availability: Feb-2008

Software Availability: Apr-2008

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
 416.gamess: -DSPEC\_CPU\_LP64  
 433.milc: -DSPEC\_CPU\_LP64  
 434.zeusmp: -DSPEC\_CPU\_LP64  
 435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
 436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
 437.leslie3d: -DSPEC\_CPU\_LP64  
 444.namd: -DSPEC\_CPU\_LP64  
 447.dealII: -DSPEC\_CPU\_LP64  
 450.soplex: -DSPEC\_CPU\_LP64  
 453.povray: -DSPEC\_CPU\_LP64  
 454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
 459.GemsFDTD: -DSPEC\_CPU\_LP64  
 465.tonto: -DSPEC\_CPU\_LP64  
 470.lbm: -DSPEC\_CPU\_LP64  
 481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
 482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## SGI

SGI Altix XE 250 (Intel Xeon X5272  
3.4GHz)

SPECfp\_rate2006 = 62.3

SPECfp\_rate\_base2006 = 55.6

CPU2006 license: 4

Test sponsor: SGI

Tested by: SGI

Test date: May-2008

Hardware Availability: Feb-2008

Software Availability: Apr-2008

## Peak Compiler Invocation

C benchmarks (except as noted below):

```
/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib  
-I/opt/intel/cc/10.1.008/include
```

433.milc: icc

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib  
-I/opt/intel/cc/10.1.008/include
```

Fortran benchmarks (except as noted below):

ifort

```
437.leslie3d: /opt/intel/fc/10.1.008/bin/ifort -L/opt/intel/fc/10.1.008/lib  
-I/opt/intel/fc/10.1.008/include
```

Benchmarks using both Fortran and C:

icc ifort

## Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64  
416.gamess: -DSPEC_CPU_LP64  
433.milc: -DSPEC_CPU_LP64  
434.zeusmp: -DSPEC_CPU_LP64  
435.gromacs: -DSPEC_CPU_LP64 -nofor_main  
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main  
444.namd: -DSPEC_CPU_LP64  
447.deallI: -DSPEC_CPU_LP64  
453.povray: -DSPEC_CPU_LP64  
454.calculix: -DSPEC_CPU_LP64 -nofor_main  
459.GemsFDTD: -DSPEC_CPU_LP64  
465.tonto: -DSPEC_CPU_LP64  
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

## Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32
```

```
470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-scalar-rep- -prefetch -opt-malloc-options=3
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## SGI

SGI Altix XE 250 (Intel Xeon X5272  
3.4GHz)

SPECfp\_rate2006 = 62.3

SPECfp\_rate\_base2006 = 55.6

CPU2006 license: 4

Test sponsor: SGI

Tested by: SGI

Test date: May-2008

Hardware Availability: Feb-2008

Software Availability: Apr-2008

## Peak Optimization Flags (Continued)

482.sphinx3: -fast -unroll2

### C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32

447.dealIII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast  
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4  
-ansi-alias

### Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

### Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.03.html>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## SGI

SGI Altix XE 250 (Intel Xeon X5272  
3.4GHz)

**SPECfp\_rate2006 = 62.3**

**SPECfp\_rate\_base2006 = 55.6**

**CPU2006 license:** 4

**Test sponsor:** SGI

**Tested by:** SGI

**Test date:** May-2008

**Hardware Availability:** Feb-2008

**Software Availability:** Apr-2008

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.03.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 17:26:40 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 11 June 2008.