



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

### SPECint®\_rate2006 = 46.9

### PRIMERGY TX150 S6, Intel Xeon L3110, 3.0 GHz

### SPECint\_rate\_base2006 = 43.6

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Jan-2009

Hardware Availability: Feb-2009

Software Availability: Nov-2008



### Hardware

CPU Name: Intel Xeon L3110  
 CPU Characteristics: 1333 MHz system bus  
 CPU MHz: 3000  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 6 MB I+D on chip per chip  
 L3 Cache: None  
 Other Cache: None  
 Memory: 8 GB (4x2 GB PC2-6400E, 2 rank, CL6-6-6, ECC)  
 Disk Subsystem: 1x SATA, 160 GB, 7200 rpm  
 Other Hardware: None

### Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP2, Kernel 2.6.16.60-0.21-smp  
 Compiler: Intel C++ Compiler 11.0 for Linux Build 20080730 Package ID: l\_cproc\_b\_11.0.066  
 Auto Parallel: No  
 File System: ext3  
 System State: Multi-User Run Level 3  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Microquill SmartHeap Library, Version 8.1 Binutils 2.18.50.0.7.20080502



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

SPECint\_rate2006 = 46.9

PRIMERGY TX150 S6, Intel Xeon L3110, 3.0 GHz

SPECint\_rate\_base2006 = 43.6

CPU2006 license: 22

Test date: Jan-2009

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Feb-2009

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2008

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	2	459	42.6	457	42.8	<b>458</b>	<b>42.7</b>	2	396	49.4	<b>393</b>	<b>49.7</b>	393	49.8
401.bzip2	2	612	31.6	<b>602</b>	<b>32.1</b>	600	32.2	2	572	33.8	<b>570</b>	<b>33.8</b>	570	33.9
403.gcc	2	434	37.1	429	37.5	<b>433</b>	<b>37.2</b>	2	434	37.1	429	37.5	<b>433</b>	<b>37.2</b>
429.mcf	2	369	49.4	368	49.6	<b>368</b>	<b>49.5</b>	2	355	51.4	355	51.3	<b>355</b>	<b>51.4</b>
445.gobmk	2	<b>516</b>	<b>40.6</b>	516	40.7	518	40.5	2	<b>484</b>	<b>43.4</b>	483	43.4	484	43.4
456.hammer	2	<b>462</b>	<b>40.4</b>	462	40.4	462	40.4	2	<b>358</b>	<b>52.1</b>	359	52.0	358	52.1
458.sjeng	2	586	41.3	588	41.1	<b>587</b>	<b>41.2</b>	2	<b>560</b>	<b>43.2</b>	563	43.0	559	43.3
462.libquantum	2	<b>344</b>	<b>120</b>	343	121	351	118	2	<b>344</b>	<b>120</b>	343	121	351	118
464.h264ref	2	664	66.7	663	66.7	<b>664</b>	<b>66.7</b>	2	634	69.8	<b>635</b>	<b>69.8</b>	635	69.7
471.omnetpp	2	447	28.0	449	27.9	<b>448</b>	<b>27.9</b>	2	406	30.8	406	30.8	<b>406</b>	<b>30.8</b>
473.astar	2	534	26.3	<b>533</b>	<b>26.3</b>	533	26.3	2	469	30.0	<b>469</b>	<b>29.9</b>	470	29.9
483.xalancbmk	2	<b>295</b>	<b>46.7</b>	295	46.7	296	46.7	2	<b>295</b>	<b>46.7</b>	295	46.7	296	46.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
taskset has been used to bind processes to cores

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

## Platform Notes

BIOS configuration:  
Adjacent Sector Prefetch = Disable

## General Notes

For information about Fujitsu Siemens Computers please see:  
<http://www.fujitsu-siemens.com>

## Base Compiler Invocation

C benchmarks:  
icc

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint\_rate2006 = 46.9

PRIMERGY TX150 S6, Intel Xeon L3110, 3.0 GHz

SPECint\_rate\_base2006 = 43.6

CPU2006 license: 22

Test date: Jan-2009

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Feb-2009

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2008

## Base Compiler Invocation (Continued)

C++ benchmarks:  
icpc

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:  
-xSSE4.1 -ipo -O3 -no-prec-div -static -inline-alloc  
-opt-malloc-options=3 -opt-prefetch

C++ benchmarks:  
-xSSE4.1 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs  
-L/spec/cpu2006.1.1/lib -lsmartheap

## Base Other Flags

C benchmarks:  
403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):  
icc

401.bzip2: /opt/intel/Compiler/11.0/066/bin/intel64/icc  
456.hmmer: /opt/intel/Compiler/11.0/066/bin/intel64/icc

C++ benchmarks:  
icpc



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

SPECint\_rate2006 = 46.9

PRIMERGY TX150 S6, Intel Xeon L3110, 3.0 GHz

SPECint\_rate\_base2006 = 43.6

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: Jan-2009

Hardware Availability: Feb-2009

Software Availability: Nov-2008

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
 401.bzip2: -DSPEC\_CPU\_LP64  
 456.hmmer: -DSPEC\_CPU\_LP64  
 462.libquantum: -DSPEC\_CPU\_LINUX  
 483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
 -no-prec-div -static -ansi-alias -opt-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
 -no-prec-div -static -opt-prefetch -ansi-alias

403.gcc: basepeak = yes

429.mcf: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
 -no-prec-div -static -opt-prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -O2 -ipo  
 -no-prec-div -ansi-alias

456.hmmer: -xSSE4.1 -ipo -O3 -no-prec-div -static -unroll2  
 -ansi-alias

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
 -no-prec-div -static -unroll4

462.libquantum: basepeak = yes

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
 -no-prec-div -static -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
 -no-prec-div -ansi-alias -opt-ra-region-strategy=block  
 -Wl,-z,muldefs -L/spec/cpu2006.1.1/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
 -no-prec-div -ansi-alias -opt-ra-region-strategy=routine  
 -Wl,-z,muldefs -L/spec/cpu2006.1.1/lib -lsmartheap

483.xalancbmk: basepeak = yes



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

**SPECint\_rate2006 = 46.9**

**PRIMERGY TX150 S6, Intel Xeon L3110, 3.0 GHz**

**SPECint\_rate\_base2006 = 43.6**

**CPU2006 license:** 22

**Test sponsor:** Fujitsu Siemens Computers

**Tested by:** Fujitsu Siemens Computers

**Test date:** Jan-2009

**Hardware Availability:** Feb-2009

**Software Availability:** Nov-2008

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revA.20090710.04.html>

<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090710.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revA.20090710.04.xml>

<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090710.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Tue Jul 22 23:04:02 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 3 March 2009.