



# SPEC® CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## Oracle Corporation

SPECint®\_rate2006 = 788

Sun Fire X4470 (Intel Xeon X7560 2.26GHz)

SPECint\_rate\_base2006 = 724

CPU2006 license: 6


Test date: May-2010

Test sponsor: Oracle Corporation

Hardware Availability: Aug-2010

Tested by: Oracle Corporation

Software Availability: Jun-2010



### Hardware

CPU Name: Intel Xeon X7560  
 CPU Characteristics: Intel Turbo Boost Technology up to 2.67 GHz  
 CPU MHz: 2266  
 FPU: Integrated  
 CPU(s) enabled: 32 cores, 4 chips, 8 cores/chip, 2 threads/core  
 CPU(s) orderable: 2,4 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 24 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 256 GB (64x4GB, DDR3-1066 CL7 dual-rank ECC Reg)  
 Disk Subsystem: 1 x 500 GB, SATA, 7200 RPM  
 Other Hardware: None

### Software

Operating System: Oracle Solaris 10 10/09  
 Compiler: Oracle Solaris Studio Express 6/10  
 Auto Parallel: No  
 File System: zfs  
 System State: Default  
 Base Pointers: 32/64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: MicroQuill SmartHeap Library 9.01 for x64



# SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Oracle Corporation

SPECint\_rate2006 = 788

Sun Fire X4470 (Intel Xeon X7560 2.26GHz)

SPECint\_rate\_base2006 = 724

CPU2006 license: 6

Test date: May-2010

Test sponsor: Oracle Corporation

Hardware Availability: Aug-2010

Tested by: Oracle Corporation

Software Availability: Jun-2010

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	64	1082	578	<b><u>1127</u></b>	<b><u>555</u></b>	1139	549	64	850	736	880	710	<b><u>877</u></b>	<b><u>713</u></b>
401.bzip2	64	1248	495	<b><u>1250</u></b>	<b><u>494</u></b>	1251	494	64	<b><u>1231</u></b>	<b><u>502</u></b>	1239	499	1231	502
403.gcc	64	895	576	<b><u>897</u></b>	<b><u>574</u></b>	902	571	64	<b><u>850</u></b>	<b><u>606</u></b>	854	603	847	608
429.mcf	64	721	809	714	817	<b><u>718</u></b>	<b><u>813</u></b>	64	551	1060	<b><u>552</u></b>	<b><u>1060</u></b>	556	1050
445.gobmk	64	997	673	994	675	<b><u>996</u></b>	<b><u>674</u></b>	64	866	775	864	777	<b><u>865</u></b>	<b><u>776</u></b>
456.hammer	64	<b><u>491</u></b>	<b><u>1220</u></b>	499	1200	486	1230	64	<b><u>491</u></b>	<b><u>1220</u></b>	499	1200	486	1230
458.sjeng	64	1186	653	1187	653	<b><u>1187</u></b>	<b><u>653</u></b>	64	1105	701	1111	697	<b><u>1110</u></b>	<b><u>698</u></b>
462.libquantum	64	<b><u>663</u></b>	<b><u>2000</u></b>	663	2000	663	2000	64	661	2010	661	2000	<b><u>661</u></b>	<b><u>2010</u></b>
464.h264ref	64	1549	914	<b><u>1547</u></b>	<b><u>916</u></b>	1533	924	64	<b><u>1498</u></b>	<b><u>946</u></b>	1483	955	1511	937
471.omnetpp	64	893	448	<b><u>894</u></b>	<b><u>448</u></b>	894	447	64	<b><u>774</u></b>	<b><u>517</u></b>	777	515	774	517
473.astar	64	930	483	926	485	<b><u>926</u></b>	<b><u>485</u></b>	64	918	489	<b><u>919</u></b>	<b><u>489</u></b>	920	488
483.xalancbmk	64	576	767	<b><u>579</u></b>	<b><u>762</u></b>	580	761	64	554	797	561	788	<b><u>558</u></b>	<b><u>791</u></b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.

## Operating System Notes

```
ulimit -s unlimited (shell)

/etc/system parameters
tune_t_fsflushr=10
autoup=900
zfs:zfs_arc_max = 0x10000000
lpg_alloc_prefer=1
```

## Platform Notes

Default BIOS settings used.

## Base Compiler Invocation

C benchmarks:  
cc

C++ benchmarks:  
CC



# SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Oracle Corporation

SPECint\_rate2006 = 788

Sun Fire X4470 (Intel Xeon X7560 2.26GHz)

SPECint\_rate\_base2006 = 724

CPU2006 license: 6

Test sponsor: Oracle Corporation

Tested by: Oracle Corporation

Test date: May-2010

Hardware Availability: Aug-2010

Software Availability: Jun-2010

## Base Portability Flags

```

400.perlbench: -DSPEC_CPU_SOLARIS_X64 -DSPEC_CPU_LP64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_SOLARIS -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_SOLARIS -DSPEC_CPU_LP64
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_SOLARIS

```

## Base Optimization Flags

```

C benchmarks:
-fast -xipo=2 -m64 -xaddr32=yes -xpagesize=2M

C++ benchmarks:
-fast -xipo=2 -xpagesize=2M -xalias_level=compatible
-L/data1/SmartHeap_9/lib -R/data1/SmartHeap_9/lib -lsmarheap
-library=stlport4

```

## Base Other Flags

```

C benchmarks:
-V -# -xjobs=64

C++ benchmarks:
-verbose=diags,version -xjobs=64

```

## Peak Compiler Invocation

```

C benchmarks:
cc

C++ benchmarks:
CC

```

## Peak Portability Flags

```

400.perlbench: -DSPEC_CPU_SOLARIS_X64 -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64 -DSPEC_CPU_SOLARIS

```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Oracle Corporation

SPECint\_rate2006 = 788

Sun Fire X4470 (Intel Xeon X7560 2.26GHz)

SPECint\_rate\_base2006 = 724

CPU2006 license: 6

Test date: May-2010

Test sponsor: Oracle Corporation

Hardware Availability: Aug-2010

Tested by: Oracle Corporation

Software Availability: Jun-2010

## Peak Portability Flags (Continued)

456.hmmcr: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_SOLARIS  
483.xalancbmk: -DSPEC\_CPU\_SOLARIS

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -xipo=1 -m64  
-xalias\_level=std -lbsdmalloc

401.bzip2: -fast -xipo=2 -m64 -xpagesize=2M -xalias\_level=std  
-lumem

403.gcc: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -xipo=2  
-xpagesize=2M -W2,-Rujam -W2,-Rtile -m64  
-xalias\_level=std

429.mcf: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m32  
-xpagesize=2M -xalias\_level=strong -xprefetch=no%auto  
-lbsdmalloc

445.gobmk: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -m64 -xpagesize=2M  
-xrestrict -xalias\_level=strong

456.hmmcr: basepeak = yes

458.sjeng: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64  
-xpagesize=2M -xalias\_level=strong

462.libquantum: -fast -xipo=2 -m64 -xalias\_level=std

464.h264ref: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64  
-xalias\_level=strong -xrestrict

C++ benchmarks:

471.omnetpp: -xprofile=collect:./feedback(pass 1)  
-xprofile=use:./feedback(pass 2) -fast -xipo=2  
-xpagesize=2M -library=stlport4  
-I/data1/SmartHeap\_9/lib -R/data1/SmartHeap\_9/lib -lsmartheap

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

Oracle Corporation

SPECint\_rate2006 = 788

Sun Fire X4470 (Intel Xeon X7560 2.26GHz)

SPECint\_rate\_base2006 = 724

CPU2006 license: 6

Test date: May-2010

Test sponsor: Oracle Corporation

Hardware Availability: Aug-2010

Tested by: Oracle Corporation

Software Availability: Jun-2010

## Peak Optimization Flags (Continued)

```
473.astar: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64
-xpagesize=2M -xalias_level=compatible -library=stlport4
-L/data1/SmartHeap_9/lib -R/data1/SmartHeap_9/lib -lsmartheap64
```

```
483.xalancbmk: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -xunroll=2
-xpagesize=2M -xalias_level=compatible -library=stlport4
-m32
-L/data1/SmartHeap_9/lib -R/data1/SmartHeap_9/lib -lsmartheap
```

## Peak Other Flags

C benchmarks:  
-V -# -xjobs=64

C++ benchmarks:  
-verbose=diags,version -xjobs=64

The flags file that was used to format this result can be browsed at

[http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio-x86\\_64.html](http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio-x86_64.html)

You can also download the XML flags source by saving the following link:

[http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio-x86\\_64.xml](http://www.spec.org/cpu2006/flags/Oracle-Solaris-Studio-x86_64.xml)

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Tue Sep 13 11:40:40 2016 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 8 July 2010.