



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

SGI

SPECint®_rate2006 = 8190

SGI Altix UV 1000 (Intel Xeon X7542, 2.66 GHz)

SPECint_rate_base2006 = 7660

CPU2006 license: 4


Test sponsor: SGI

Tested by: SGI

Test date: Aug-2010

Hardware Availability: Jun-2010

Software Availability: Jun-2010



Hardware

CPU Name: Intel Xeon X7542
 CPU Characteristics: Intel Turbo Boost Technology up to 2.80 GHz
 CPU MHz: 2667
 FPU: Integrated
 CPU(s) enabled: 384 cores, 64 chips, 6 cores/chip
 CPU(s) orderable: 2-256 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 18 MB I+D on chip per chip
 Other Cache: None
 Memory: 2 TB (512 x 4GB dual-rank DDR3-1066 CL7 RDIMMs)
 Disk Subsystem: None
 Other Hardware: None

Software

Operating System: SUSE Linux Enterprise Server 11 (x86_64) SP1, Kernel 2.6.32.12-0.7.1.1381.0.PTF-default
 Compiler: Intel C++ Professional Compiler for IA32 and Intel 64, Version 11.1 Build 20091130 Package ID: l_cproc_p_11.1.064
 Auto Parallel: No
 File System: tmpfs
 System State: Run Level 3 (multi-user)
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: Microquill SmartHeap V8.1



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

SGI

SPECint_rate2006 = 8190

SGI Altix UV 1000 (Intel Xeon X7542, 2.66 GHz)

SPECint_rate_base2006 = 7660

CPU2006 license: 4

Test sponsor: SGI

Tested by: SGI

Test date: Aug-2010

Hardware Availability: Jun-2010

Software Availability: Jun-2010

Results Table

| Benchmark | Base | | | | | | Peak | | | | | | | |
|----------------|--------|------------|--------------|------------|--------------|------------|--------------|--------|------------|-------------|------------|--------------|------------|--------------|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 400.perlbench | 384 | 541 | 6930 | <u>542</u> | <u>6930</u> | 543 | 6910 | 384 | <u>460</u> | <u>8150</u> | 460 | 8160 | 461 | 8140 |
| 401.bzip2 | 384 | 767 | 4830 | <u>765</u> | <u>4840</u> | 765 | 4850 | 384 | 716 | 5180 | 714 | 5190 | <u>715</u> | <u>5180</u> |
| 403.gcc | 384 | <u>535</u> | <u>5780</u> | 534 | 5790 | 535 | 5780 | 384 | 536 | 5770 | 538 | 5750 | <u>536</u> | <u>5760</u> |
| 429.mcf | 384 | 376 | 9310 | <u>376</u> | <u>9320</u> | 374 | 9360 | 384 | 374 | 9370 | 373 | 9380 | <u>374</u> | <u>9370</u> |
| 445.gobmk | 384 | 573 | 7040 | <u>572</u> | <u>7040</u> | 572 | 7050 | 384 | <u>540</u> | <u>7470</u> | 539 | 7470 | 540 | 7470 |
| 456.hammer | 384 | 287 | 12500 | 288 | 12400 | <u>287</u> | <u>12500</u> | 384 | 246 | 14600 | 245 | 14600 | <u>245</u> | <u>14600</u> |
| 458.sjeng | 384 | 677 | 6860 | 680 | 6830 | <u>678</u> | <u>6860</u> | 384 | 620 | 7490 | <u>620</u> | <u>7490</u> | 620 | 7490 |
| 462.libquantum | 384 | 415 | 19200 | <u>416</u> | <u>19100</u> | 419 | 19000 | 384 | 395 | 20200 | <u>394</u> | <u>20200</u> | 393 | 20200 |
| 464.h264ref | 384 | <u>724</u> | <u>11700</u> | 724 | 11700 | 724 | 11700 | 384 | 689 | 12300 | <u>690</u> | <u>12300</u> | 691 | 12300 |
| 471.omnetpp | 384 | <u>557</u> | <u>4310</u> | 557 | 4310 | 558 | 4300 | 384 | 521 | 4600 | <u>522</u> | <u>4600</u> | 522 | 4600 |
| 473.astar | 384 | 591 | 4560 | 590 | 4570 | <u>591</u> | <u>4560</u> | 384 | <u>539</u> | <u>5000</u> | 539 | 5000 | 542 | 4980 |
| 483.xalancbmk | 384 | <u>312</u> | <u>8500</u> | 311 | 8510 | 312 | 8500 | 384 | <u>312</u> | <u>8500</u> | 311 | 8510 | 312 | 8500 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.
numactl was used to bind copies to the cores

Operating System Notes

Tmpfs filesystem set up with:
mkdir -p /mnt/shm
mount -t tmpfs -o size=2048g,rw,mpol=interleave tmpfs /mnt/shm/
The mpol=interleave option sets the NUMA memory allocation policy for all files to allocate from each node in turn.

Platform Notes

OS on 300 GB SAS disk

General Notes

Binaries were compiled on SLES 10 with Binutils 2.18.50.0.7.20080502

Base Compiler Invocation

C benchmarks:
icc -m32

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

SGI

SPECint_rate2006 = 8190

SGI Altix UV 1000 (Intel Xeon X7542, 2.66 GHz)

SPECint_rate_base2006 = 7660

CPU2006 license: 4

Test date: Aug-2010

Test sponsor: SGI

Hardware Availability: Jun-2010

Tested by: SGI

Software Availability: Jun-2010

Base Compiler Invocation (Continued)

C++ benchmarks:
icpc -m32

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

C++ benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.1.ic11.1/libic11.1-32bit -lsmartheap

Base Other Flags

C benchmarks:
403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc -m32

401.bzip2: icc -m64

456.hmmer: icc -m64

458.sjeng: icc -m64

462.libquantum: icc -m64

C++ benchmarks (except as noted below):
icpc -m32

473.astar: icpc -m64



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

SGI

SPECint_rate2006 = 8190

SGI Altix UV 1000 (Intel Xeon X7542, 2.66 GHz)

SPECint_rate_base2006 = 7660

CPU2006 license: 4

Test date: Aug-2010

Test sponsor: SGI

Hardware Availability: Jun-2010

Tested by: SGI

Software Availability: Jun-2010

Peak Portability Flags

```

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

```

Peak Optimization Flags

C benchmarks:

```

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
               -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
               -prof-use(pass 2) -ansi-alias

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
            -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
            -prof-use(pass 2) -opt-prefetch -ansi-alias -auto-ilp32

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div -static

429.mcf: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2) -O2
            -ipo -no-prec-div -ansi-alias

456.hmmer: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2
            -ansi-alias -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
            -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
            -prof-use(pass 2) -unroll4 -auto-ilp32

462.libquantum: -xSSE4.2 -ipo -O3 -no-prec-div -static -auto-ilp32
                -opt-prefetch

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
              -O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
              -prof-use(pass 2) -unroll2 -ansi-alias

```

C++ benchmarks:

```

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
              -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
              -ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs
              -L/home/cmplr/usr3/alrahate/cpu2006.1.1.ic11.1/libic11.1-32bit -lsmartheap

```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

SGI

SPECint_rate2006 = 8190

SGI Altix UV 1000 (Intel Xeon X7542, 2.66 GHz)

SPECint_rate_base2006 = 7660

CPU2006 license: 4

Test date: Aug-2010

Test sponsor: SGI

Hardware Availability: Jun-2010

Tested by: SGI

Software Availability: Jun-2010

Peak Optimization Flags (Continued)

```

473.astar: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
          -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
          -ansi-alias -opt-ra-region-strategy=routine -Wl,-z,muldefs
          -L/home/cmplr/usr3/alrahate/cpu2006.1.1.ic11.1/libic11.1-64bit -lsmartheap64

```

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revE.20100316.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revE.20100316.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 12:14:26 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 31 August 2010.