



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation


SPECfp[®]_rate2006 = 2550

IBM Power 780 (3.86 GHz, 64 core, RedHat)

SPECfp_rate_base2006 = 2280

CPU2006 license: 11
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Oct-2010
Hardware Availability: Mar-2010
Software Availability: Nov-2010



Hardware

CPU Name: POWER7
CPU Characteristics: Intelligent Energy Optimization enabled, up to 3.94 GHz
CPU MHz: 3860
FPU: Integrated
CPU(s) enabled: 64 cores, 8 chips, 8 cores/chip, 4 threads/core
CPU(s) orderable: 8,16,24,32,48,64 cores
Primary Cache: 32 KB I + 32 KB D on chip per core

Continued on next page

Software

Operating System: Red Hat Enterprise Linux Server release 6.0 (ppc64), Kernel 2.6.32-71.el6.ppc64
Compiler: IBM XL C/C++ for Linux, V11.1 Updated with the Nov2010 PTF
IBM XL Fortran for Linux, V13.1 Updated with the Nov2010 PTF
Auto Parallel: No
File System: ext2
System State: Run level 3 (multi-user)

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 2550

IBM Power 780 (3.86 GHz, 64 core, RedHat)

SPECfp_rate_base2006 = 2280

CPU2006 license: 11

Test date: Oct-2010

Test sponsor: IBM Corporation

Hardware Availability: Mar-2010

Tested by: IBM Corporation

Software Availability: Nov-2010

Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 4 MB I+D on chip per core
 Other Cache: None
 Memory: 512 GB (64x8 GB) DDR3 1066 MHz
 Disk Subsystem: 3x146.8 GB Software RAID-0 SAS SFF 15K RPM
 Other Hardware: None

Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: -Post-Link Optimization for Linux on POWER, Version 5.5.0-3
 -MicroQuill SmartHeap 9
 -Apache C++ Standard Library 4.2.1

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	256	1084	3210	<u>1112</u>	<u>3130</u>	1121	3100	256	1084	3210	<u>1112</u>	<u>3130</u>	1121	3100
416.gamess	256	<u>2469</u>	<u>2030</u>	2466	2030	2478	2020	256	<u>2266</u>	<u>2210</u>	2272	2210	2266	2210
433.milc	256	752	3120	774	3040	<u>766</u>	<u>3070</u>	64	188	3130	187	3140	<u>187</u>	<u>3140</u>
434.zeusmp	256	<u>1046</u>	<u>2230</u>	1042	2240	1053	2210	256	<u>1046</u>	<u>2230</u>	1042	2240	1053	2210
435.gromacs	256	1087	1680	<u>1094</u>	<u>1670</u>	1106	1650	256	834	2190	853	2140	<u>841</u>	<u>2170</u>
436.cactusADM	256	1107	2760	<u>1109</u>	<u>2760</u>	1115	2740	128	487	3140	483	3170	<u>483</u>	<u>3160</u>
437.leslie3d	256	1227	1960	<u>1275</u>	<u>1890</u>	1279	1880	256	1227	1960	<u>1275</u>	<u>1890</u>	1279	1880
444.namd	256	<u>761</u>	<u>2700</u>	761	2700	762	2690	256	738	2780	<u>737</u>	<u>2790</u>	736	2790
447.dealII	256	794	3690	<u>804</u>	<u>3640</u>	806	3640	256	<u>601</u>	<u>4870</u>	602	4860	600	4880
450.soplex	256	1099	1940	<u>1148</u>	<u>1860</u>	1152	1850	256	1099	1940	<u>1148</u>	<u>1860</u>	1152	1850
453.povray	256	<u>740</u>	<u>1840</u>	742	1840	732	1860	256	567	2400	573	2380	<u>568</u>	<u>2400</u>
454.calculix	256	1075	1960	1067	1980	<u>1071</u>	<u>1970</u>	256	1066	1980	1049	2010	<u>1050</u>	<u>2010</u>
459.GemsFDTD	256	1616	1680	<u>1627</u>	<u>1670</u>	1631	1670	256	1616	1680	<u>1627</u>	<u>1670</u>	1631	1670
465.tonto	256	1708	1480	1725	1460	<u>1722</u>	<u>1460</u>	256	<u>913</u>	<u>2760</u>	911	2770	914	2760
470.lbm	256	805	4370	<u>886</u>	<u>3970</u>	888	3960	256	805	4370	<u>886</u>	<u>3970</u>	888	3960
481.wrf	256	1378	2080	<u>1432</u>	<u>2000</u>	1433	2000	256	<u>1266</u>	<u>2260</u>	1253	2280	1270	2250
482.sphinx3	256	1881	2650	<u>1983</u>	<u>2520</u>	2020	2470	256	1881	2650	<u>1983</u>	<u>2520</u>	2020	2470

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Peak Tuning Notes

IBM Post-Link Optimization tool with options "-O4 -nodp" used for 433.milc 435.gromacs 450.soplex 482.sphinx3
 options "-O4 -vrox -nodp" used for 434.zeusmp
 options "-O3 -lu -l -nodp -sdp 9" used for 437.leslie3d 444.namd
 options "-O4" used for 465.tonto



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 2550

IBM Power 780 (3.86 GHz, 64 core, RedHat)

SPECfp_rate_base2006 = 2280

CPU2006 license: 11

Test date: Oct-2010

Test sponsor: IBM Corporation

Hardware Availability: Mar-2010

Tested by: IBM Corporation

Software Availability: Nov-2010

Submit Notes

The config file option 'submit' was used.
Benchmarks bound to a processor using numactl on the submit command.

Operating System Notes

ulimit -s (stack) set to 1048576.
Large pages reserved as follows by root user:
echo 18000 > /proc/sys/vm/nr_hugepages
The following environment variables were set before the runspec command:
XLFRTLOPTS=intrinths=1
HUGETLB_VERBOSE=0
HUGETLB_MORECORE=yes
HUGETLB_ELFMAP=RW
447.dealII (peak): "apache_stdccxx_4_2_1" src.alt was used.
447.dealII (base): "apache_stdccxx_4_2_1" src.alt was used.

Base Compiler Invocation

C benchmarks:
xlc -qlanglvl=extc99
C++ benchmarks:
x1C
Fortran benchmarks:
xlf95
Benchmarks using both Fortran and C:
xlc -qlanglvl=extc99 xlf95

Base Portability Flags

410.bwaves: -qfixed
416.gamess: -qfixed
434.zeusmp: -qfixed
435.gromacs: -qfixed -qextname
436.cactusADM: -qfixed -qextname
437.leslie3d: -qfixed
454.calculix: -qfixed -qextname
481.wrf: -DNOUNDERSCORE
482.sphinx3: -qchars=signed



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 2550

IBM Power 780 (3.86 GHz, 64 core, RedHat)

SPECfp_rate_base2006 = 2280

CPU2006 license: 11

Test date: Oct-2010

Test sponsor: IBM Corporation

Hardware Availability: Mar-2010

Tested by: IBM Corporation

Software Availability: Nov-2010

Base Optimization Flags

C benchmarks:

```
-O5 -qarch=pwr7 -qtune=pwr7 -B/usr/share/libhugetlbfs/ -tl  
-Wl,--hugetlbfs-align
```

C++ benchmarks:

```
-O5 -qarch=pwr7 -qtune=pwr7 -qrtti -B/usr/share/libhugetlbfs/ -tl  
-Wl,--hugetlbfs-align
```

Fortran benchmarks:

```
-O5 -qarch=pwr7 -qtune=pwr7 -qsmallstack=dynlenonheap -qalias=nostd  
-B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-align
```

Benchmarks using both Fortran and C:

```
-O5 -qarch=pwr7 -qtune=pwr7 -B/usr/share/libhugetlbfs/ -tl  
-Wl,--hugetlbfs-align -qsmallstack=dynlenonheap -qalias=nostd
```

Base Other Flags

C benchmarks:

```
-qipa=threads
```

C++ benchmarks:

```
-qipa=threads
```

Fortran benchmarks:

```
-qipa=threads
```

Benchmarks using both Fortran and C:

```
-qipa=threads
```

Peak Compiler Invocation

C benchmarks:

```
xlc -qlanglvl=extc99
```

C++ benchmarks:

```
x1C
```

Fortran benchmarks:

```
x1f95
```

Benchmarks using both Fortran and C:

```
xlc -qlanglvl=extc99 x1f95
```



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 2550

IBM Power 780 (3.86 GHz, 64 core, RedHat)

SPECfp_rate_base2006 = 2280

CPU2006 license: 11

Test date: Oct-2010

Test sponsor: IBM Corporation

Hardware Availability: Mar-2010

Tested by: IBM Corporation

Software Availability: Nov-2010

Peak Portability Flags

410.bwaves: -qfixed
 416.gamess: -qfixed
 434.zeusmp: -qfixed
 435.gromacs: -qfixed -qextname
 436.cactusADM: -DSPEC_CPU_LP64 -qfixed -qextname
 437.leslie3d: -qfixed
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -qfixed -qextname
 481.wrf: -DNOUNDERSCORE
 482.sphinx3: -qchars=signed

Peak Optimization Flags

C benchmarks:

433.milc: -Wl,-q -O5 -qarch=pwr7 -qtune=pwr7 -lhugetlbfs

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qarch=pwr7
-qtune=pwr7 -lhugetlbfs

447.dealIII: -O4 -qarch=pwr7 -qtune=pwr7 -qrtti
-qcpp_stdinc=/autobench/sources/stdcxx-4.2.1/dist/include/ansi:/autobench/sources/stdcxx-4.2.1/dist/include:/opt/ibmcomp/vacpp/11.1/incl
-lsmartheap -L/autobench/sources/stdcxx-4.2.1/dist/lib
-R/autobench/sources/stdcxx-4.2.1/dist/lib -lstd8d

450.soplex: basepeak = yes

453.povray: -Wl,-q -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qarch=pwr7
-qtune=pwr7 -qsimd -q64 -lsmartheap64

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qarch=pwr7 -qtune=pwr7
-qalias=nostd -lhugetlbfs

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 2550

IBM Power 780 (3.86 GHz, 64 core, RedHat)

SPECfp_rate_base2006 = 2280

CPU2006 license: 11

Test date: Oct-2010

Test sponsor: IBM Corporation

Hardware Availability: Mar-2010

Tested by: IBM Corporation

Software Availability: Nov-2010

Peak Optimization Flags (Continued)

459.GemsFDTD: basepeak = yes

465.tonto: -Wl, -q -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qarch=pwr7
-qtune=pwr7 -qsimd -lhugetlbfs

Benchmarks using both Fortran and C:

435.gromacs: -Wl, -q -qpdf1(pass 1) -qpdf2(pass 2) -O4 -qarch=pwr7
-qtune=pwr7 -qsimd -lhugetlbfs

436.cactusADM: -O4 -qarch=pwr7 -qtune=pwr7 -qsimd -qnostrict -q64
-lhugetlbfs

454.calculix: -qpdf1(pass 1) -qpdf2(pass 2) -O5 -qarch=pwr7 -qtune=pwr7
-B/usr/share/libhugetlbfs/ -tl -Wl,--hugetlbfs-align

481.wrf: -O3 -qarch=pwr7 -qtune=pwr7 -q64 -lhugetlbfs

Peak Other Flags

C benchmarks:
-qipa=threads

C++ benchmarks:
-qipa=threads

Fortran benchmarks:
-qipa=threads

Benchmarks using both Fortran and C (except as noted below):
-qipa=threads

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/IBM-Linux-XL.20101123.01.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/IBM-Linux-XL.20101123.01.xml>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

SPECfp_rate2006 = 2550

IBM Power 780 (3.86 GHz, 64 core, RedHat)

SPECfp_rate_base2006 = 2280

CPU2006 license: 11

Test date: Oct-2010

Test sponsor: IBM Corporation

Hardware Availability: Mar-2010

Tested by: IBM Corporation

Software Availability: Nov-2010

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 14:25:11 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 23 November 2010.