



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei

Tecal RH5885 V2 (8-sockets, Intel Xeon E7-8870)

SPECfp_rate2006 = 1110

CPU2006 license: 3175


Test date: Feb-2013

Test sponsor: Huawei

Hardware Availability: Dec-2012

Tested by: Huawei

Software Availability: Oct-2012



Hardware

CPU Name: Intel Xeon E7-8870
CPU Characteristics: Intel Turbo Boost Technology up to 2.80 GHz
CPU MHz: 2400
FPU: Integrated
CPU(s) enabled: 80 cores, 8 chips, 10 cores/chip, 2 threads/core
CPU(s) orderable: 8 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 256 KB I+D on chip per core

Software

Operating System: Red Hat Enterprise Linux Server release 6.2 (Santiago)
Compiler: 2.6.32-220.el6.x86_64
C/C++: Version 13.0.0.079 of Intel C++ Studio XE for Linux;
Fortran: Version 13.0.0.079 of Intel Fortran Studio XE for Linux
Auto Parallel: No
File System: ext4

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei

SPECfp_rate2006 = 1110

Tecal RH5885 V2 (8-sockets, Intel Xeon E7-8870)

SPECfp_rate_base2006 = 1090

CPU2006 license: 3175

Test date: Feb-2013

Test sponsor: Huawei

Hardware Availability: Dec-2012

Tested by: Huawei

Software Availability: Oct-2012

L3 Cache:	30 MB I+D on chip per chip
Other Cache:	None
Memory:	2 TB (128 x 16 GB 4Rx4 PC3-10600R-9, ECC, running at 1066 MHz)
Disk Subsystem:	2 x 500 GB (SATA, 7200RPM, RAID1)
Other Hardware:	None

System State:	Run level 3 (multi-user)
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	None

Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	160	3815	570	<u>3819</u>	<u>569</u>	3832	567	160	3815	570	<u>3819</u>	<u>569</u>	3832	567		
416.gamess	160	1968	1590	<u>1951</u>	<u>1610</u>	1937	1620	160	<u>1859</u>	<u>1690</u>	1872	1670	1842	1700		
433.milc	160	<u>2163</u>	<u>679</u>	2164	679	2163	679	160	<u>2160</u>	<u>680</u>	2162	679	2160	680		
434.zeusmp	160	1099	1330	1114	1310	<u>1107</u>	<u>1320</u>	160	1099	1330	1114	1310	<u>1107</u>	<u>1320</u>		
435.gromacs	160	577	1980	<u>577</u>	<u>1980</u>	578	1980	160	<u>581</u>	<u>1970</u>	580	1970	<u>582</u>	1960		
436.cactusADM	160	<u>1433</u>	<u>1330</u>	1424	1340	1454	1310	160	<u>1433</u>	<u>1330</u>	1424	1340	1454	1310		
437.leslie3d	160	<u>2944</u>	<u>511</u>	2946	510	2944	511	160	2942	511	2944	511	<u>2943</u>	<u>511</u>		
444.namd	160	876	1470	875	1470	<u>875</u>	<u>1470</u>	160	<u>860</u>	<u>1490</u>	866	1480	860	1490		
447.dealII	160	749	2440	<u>740</u>	<u>2470</u>	737	2480	160	749	2440	<u>740</u>	<u>2470</u>	737	2480		
450.soplex	160	2399	556	<u>2398</u>	<u>556</u>	2398	557	160	2373	562	<u>2374</u>	<u>562</u>	2376	562		
453.povray	160	375	2270	<u>377</u>	<u>2260</u>	378	2250	160	327	2610	<u>329</u>	<u>2590</u>	330	2580		
454.calculix	160	<u>987</u>	<u>1340</u>	1010	1310	976	1350	160	<u>987</u>	<u>1340</u>	1010	1310	976	1350		
459.GemsFDTD	160	3176	534	<u>3174</u>	<u>535</u>	3170	536	160	3176	534	<u>3174</u>	<u>535</u>	3170	536		
465.tonto	160	942	1670	<u>942</u>	<u>1670</u>	942	1670	160	<u>910</u>	<u>1730</u>	917	1720	899	1750		
470.lbm	160	<u>2012</u>	<u>1090</u>	2010	1090	2014	1090	160	<u>2012</u>	<u>1090</u>	2010	1090	2014	1090		
481.wrf	160	2047	873	<u>2048</u>	<u>873</u>	2049	872	160	<u>2022</u>	<u>884</u>	2019	885	2025	882		
482.sphinx3	160	<u>4019</u>	<u>776</u>	4018	776	4019	776	160	<u>3931</u>	<u>793</u>	3927	794	3933	793		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei

SPECfp_rate2006 = 1110

Tecal RH5885 V2 (8-sockets, Intel Xeon E7-8870)

SPECfp_rate_base2006 = 1090

CPU2006 license: 3175

Test date: Feb-2013

Test sponsor: Huawei

Hardware Availability: Dec-2012

Tested by: Huawei

Software Availability: Oct-2012

Platform Notes

BIOS configuration:

Power Technology set to Custom, Performance/Watt set to Traditional
Sysinfo program /home/cpu2006/config/sysinfo.rev6818
\$Rev: 6818 \$ \$Date:: 2012-07-17 #\$ 5569a0425e2ad530534e4c79a46e4d28
running on 5885-8P-15 Fri Feb 1 08:23:46 2013

This section contains SUT (System Under Test) info as seen by
some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
From /proc/cpuinfo
    model name : Intel(R) Xeon(R) CPU E7- 8870 @ 2.40GHz
        8 "physical id"s (chips)
        160 "processors"
    cores, siblings (Caution: counting these is hw and system dependent. The
    following excerpts from /proc/cpuinfo might not be reliable. Use with
    caution.)
        cpu cores : 10
        siblings : 20
    physical 0: cores 0 1 2 8 9 16 17 18 24 25
    physical 1: cores 0 1 2 8 9 16 17 18 24 25
    physical 2: cores 0 1 2 8 9 16 17 18 24 25
    physical 3: cores 0 1 2 8 9 16 17 18 24 25
    physical 4: cores 0 1 2 8 9 16 17 18 24 25
    physical 5: cores 0 1 2 8 9 16 17 18 24 25
    physical 6: cores 0 1 2 8 9 16 17 18 24 25
    physical 7: cores 0 1 2 8 9 16 17 18 24 25
    cache size : 30720 KB
```

```
From /proc/meminfo
    MemTotal:      2117589300 kB
    HugePages_Total:       0
    Hugepagesize:     2048 kB
```

```
/usr/bin/lsb_release -d
    Red Hat Enterprise Linux Server release 6.2 (Santiago)
```

```
From /etc/*release* /etc/*version*
    redhat-release: Red Hat Enterprise Linux Server release 6.2 (Santiago)
    system-release: Red Hat Enterprise Linux Server release 6.2 (Santiago)
    system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server
```

```
uname -a:
    Linux 5885-8P-15 2.6.32-220.el6.x86_64 #1 SMP Wed Nov 9 08:03:13 EST 2011
    x86_64 x86_64 x86_64 GNU/Linux
```

```
run-level 3 Jan 31 11:19
```

```
SPEC is set to: /home/cpu2006
    Filesystem      Type  Size  Used Avail Use% Mounted on
    /dev/mapper/vg_58858p15-lv_home
        ext4        434G  149G  263G  37%  /home
Continued on next page
```



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei

Tecal RH5885 V2 (8-sockets, Intel Xeon E7-8870)

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

SPECfp_rate2006 = 1110

SPECfp_rate_base2006 = 1090

Test date: Feb-2013

Hardware Availability: Dec-2012

Software Availability: Oct-2012

Platform Notes (Continued)

Additional information from dmidecode:

BIOS American Megatrends Inc. RGPUC-BIOS-V052 01/16/2013

Memory:

128x 16 GB

128x Hyundai HMT42GR7BMR4C-H9 16 GB 1067 MHz 4 rank

(End of data from sysinfo program)

Descriptions about memory generated by sysinfo are not correct,
only 128 DIMMs are installed not 256, see descriptions below.

Memory:

128x Hyundai HMT42GR7BMR4C-H9 16 GB 1067 MHz 4 rank

General Notes

Environment variables set by runspec before the start of the run:
`LD_LIBRARY_PATH = "/home/cpu2006/libs/32:/home/cpu2006/libs/64"`

Binaries compiled on a system with 4x Xeon E7-8870 CPU + 1024GB
memory using RHEL6.2

Transparent Huge Pages disabled with:

`echo never > /sys/kernel/mm/redhat_transparent_hugepage/enable`

Filesystem page cache cleared with:

`echo 1> /proc/sys/vm/drop_caches`

runspec command invoked through numactl i.e.:

`numactl --interleave=all runspec <etc>`

Base Compiler Invocation

C benchmarks:

`icc -m64`

C++ benchmarks:

`icpc -m64`

Fortran benchmarks:

`ifort -m64`

Benchmarks using both Fortran and C:

`icc -m64 ifort -m64`

Base Portability Flags

410.bwaves: `-DSPEC_CPU_LP64`

416.gamess: `-DSPEC_CPU_LP64`

433.milc: `-DSPEC_CPU_LP64`

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei

Tecal RH5885 V2 (8-sockets, Intel Xeon E7-8870)

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

SPECfp_rate2006 = 1110

SPECfp_rate_base2006 = 1090

Test date: Feb-2013

Hardware Availability: Dec-2012

Software Availability: Oct-2012

Base Portability Flags (Continued)

```
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```

Base Optimization Flags

C benchmarks:

```
-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3
```

C++ benchmarks:

```
-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3
```

Fortran benchmarks:

```
-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch
```

Benchmarks using both Fortran and C:

```
-xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -auto-p32
-ansi-alias -opt-mem-layout-trans=3
```

Peak Compiler Invocation

C benchmarks (except as noted below):

```
icc -m64
```

```
482.sphinx3: icc -m32
```

C++ benchmarks (except as noted below):

```
icpc -m64
```

```
450.soplex: icpc -m32
```

Fortran benchmarks:

```
ifort -m64
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei

Tecal RH5885 V2 (8-sockets, Intel Xeon E7-8870)

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

SPECfp_rate2006 = 1110

SPECfp_rate_base2006 = 1090

Test date: Feb-2013

Hardware Availability: Dec-2012

Software Availability: Oct-2012

Peak Compiler Invocation (Continued)

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Peak Portability Flags

```

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
 435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
 437.leslie3d: -DSPEC_CPU_LP64
    444.namd: -DSPEC_CPU_LP64
    447.dealII: -DSPEC_CPU_LP64
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

```

Peak Optimization Flags

C benchmarks:

```

433.milc: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
  -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
  -prof-use(pass 2) -static -auto-ilp32

```

470.lbm: basepeak = yes

```

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -opt-mem-layout-trans=3
  -unroll2

```

C++ benchmarks:

```

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
  -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
  -prof-use(pass 2) -fno-alias -auto-ilp32

```

447.dealII: basepeak = yes

```

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
  -no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
  -prof-use(pass 2) -opt-malloc-options=3

```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei

Tecal RH5885 V2 (8-sockets, Intel Xeon E7-8870)

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

SPECfp_rate2006 = 1110

SPECfp_rate_base2006 = 1090

Test date: Feb-2013

Hardware Availability: Dec-2012

Software Availability: Oct-2012

Peak Optimization Flags (Continued)

453.povray: -xsSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xsSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: -xsSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

459.GemsFDTD: basepeak = yes

465.tonto: -xsSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -auto
-inline-calloc -opt-malloc-options=3

Benchmarks using both Fortran and C:

435.gromacs: -xsSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -opt-mem-layout-trans=3(pass 2)
-prof-use(pass 2) -opt-prefetch -static -auto-ilp32

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: -xsSE4.2 -ipo -O3 -no-prec-div -static -auto-ilp32

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.html>
<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-revG.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20111122.xml>
<http://www.spec.org/cpu2006/flags/Huawei-Platform-Settings-revG.xml>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Huawei

Tecal RH5885 V2 (8-sockets, Intel Xeon E7-8870)

CPU2006 license: 3175

Test sponsor: Huawei

Tested by: Huawei

SPECfp_rate2006 = 1110

SPECfp_rate_base2006 = 1090

Test date: Feb-2013

Hardware Availability: Dec-2012

Software Availability: Oct-2012

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.

Report generated on Thu Jul 24 15:19:28 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 26 February 2013.