



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS B260 M4 (Intel Xeon E7-4890 v2 @ 2.80GHz)

SPECfp®_rate2006 = Not Run

SPECfp_rate_base2006 = 865

CPU2006 license: 9019


Test date: Feb-2014

Test sponsor: Cisco Systems

Hardware Availability: May-2014

Tested by: Cisco Systems

Software Availability: Sep-2013



Hardware

CPU Name: Intel Xeon E7-4890 v2
CPU Characteristics: Intel Turbo Boost Technology up to 3.40 GHz
CPU MHz: 2800
FPU: Integrated
CPU(s) enabled: 30 cores, 2 chips, 15 cores/chip, 2 threads/core
CPU(s) orderable: 1,2 Chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 256 KB I+D on chip per core

Software

Operating System: Red Hat Enterprise Linux Server release 6.4 (Santiago)
Compiler: 2.6.32-358.el6.x86_64
C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux;
Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux
Auto Parallel: No
File System: ext4

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS B260 M4 (Intel Xeon E7-4890 v2 @ 2.80GHz)

SPECfp_rate2006 = Not Run

SPECfp_rate_base2006 = 865

CPU2006 license: 9019

Test date: Feb-2014

Test sponsor: Cisco Systems

Hardware Availability: May-2014

Tested by: Cisco Systems

Software Availability: Sep-2013

L3 Cache: 37.5 MB I+D on chip per chip
 Other Cache: None
 Memory: 256 GB (32 x 8 GB 2Rx4 PC3-12800R-11, ECC, and CL11)
 Disk Subsystem: 1 x 300 GB SAS SATA 15K RPM
 Other Hardware: None

System State: Run level 3 (multi-user)
 Base Pointers: 32/64-bit
 Peak Pointers: Not Applicable
 Other Software: None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	60	1176	694	1175	694	1177	693							
416.gamess	60	1123	1050	1124	1040	1123	1050							
433.milc	60	825	667	825	667	826	667							
434.zeusmp	60	575	949	576	948	576	947							
435.gromacs	60	349	1230	350	1220	349	1230							
436.cactusADM	60	709	1010	711	1010	714	1000							
437.leslie3d	60	1224	461	1224	461	1222	462							
444.namd	60	582	827	576	836	583	826							
447.dealII	60	403	1700	407	1690	404	1700							
450.soplex	60	1074	466	1073	467	1073	466							
453.povray	60	225	1420	225	1420	226	1410							
454.calculix	60	336	1470	336	1470	335	1480							
459.GemsFDTD	60	1514	420	1514	420	1514	421							
465.tonto	60	593	995	586	1010	587	1010							
470.lbm	60	982	839	981	840	983	839							
481.wrf	60	817	820	820	817	817	821							
482.sphinx3	60	1451	806	1452	805	1455	804							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS B260 M4 (Intel Xeon E7-4890 v2 @ 2.80GHz)

SPECfp_rate2006 = Not Run

SPECfp_rate_base2006 = 865

CPU2006 license: 9019

Test date: Feb-2014

Test sponsor: Cisco Systems

Hardware Availability: May-2014

Tested by: Cisco Systems

Software Availability: Sep-2013

Platform Notes

```
CPU performance set to Enterprise
Power Technology set to Custom
CPU Power State C6 set to Disabled
CPU Power State C1 Enhanced set to Disabled
Package C State Limit set to C0/C1 State
Energy Performance policy set to Performance
Memory RAS configuration set to Maximum Performance
DRAM Clock Throttling Set to Performance
LV DDR Mode set to Performance-mode
DRAM Refresh Rate Set to Auto
Sysinfo program /opt/cpu2006-1.4/config/sysinfo.rev6818
$Rev: 6818 $ $Date:: 2012-07-17 #$ e86d102572650a6e4d596a3cee98f191
running on SPEccpu-YOS Tue Feb 11 18:42:44 2014
```

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
From /proc/cpuinfo
model name : Intel(R) Xeon(R) CPU E7-4890 v2 @ 2.80GHz
        2 "physical id"s (chips)
        60 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
        cpu cores : 15
        siblings : 30
        physical 0: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
        physical 1: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14
cache size : 38400 KB
```

```
From /proc/meminfo
MemTotal:      264231092 kB
HugePages_Total:       0
Hugepagesize:     2048 kB
```

```
/usr/bin/lsb_release -d
Red Hat Enterprise Linux Server release 6.4 (Santiago)
```

```
From /etc/*release* /etc/*version*
redhat-release: Red Hat Enterprise Linux Server release 6.4 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.4 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server
```

```
uname -a:
Linux SPEccpu-YOS 2.6.32-358.el6.x86_64 #1 SMP Tue Jan 29 11:47:41 EST 2013
x86_64 x86_64 x86_64 GNU/Linux
```

```
run-level 3 Feb 11 18:29
```

```
SPEC is set to: /opt/cpu2006-1.4
Filesystem      Type    Size  Used Avail Use% Mounted on
Continued on next page
```



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS B260 M4 (Intel Xeon E7-4890 v2 @ 2.80GHz)

SPECfp_rate2006 = Not Run

SPECfp_rate_base2006 = 865

CPU2006 license: 9019

Test date: Feb-2014

Test sponsor: Cisco Systems

Hardware Availability: May-2014

Tested by: Cisco Systems

Software Availability: Sep-2013

Platform Notes (Continued)

```
/dev/sda1      ext4      275G   10G   251G   4%   /
```

Additional information from dmidecode:

```
BIOS Cisco Systems, Inc. EXM4-1.2.2.1.12.012920142034 01/29/2014
```

Memory:

```
32x 8 GB
```

```
32x 0xCE00 M393B1K70QB0-YK0 8 GB 1333 MHz 2 rank
```

```
16x NO DIMM NO DIMM
```

(End of data from sysinfo program)

General Notes

Environment variables set by runspec before the start of the run:

```
LD_LIBRARY_PATH = "/opt/cpu2006-1.4/libs/32:/opt/cpu2006-1.4/libs/64:/opt/cpu2006-1.4/sh"
```

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RedHat EL 6.4

Transparent Huge Pages enabled with:

```
echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled
```

Filesystem page cache cleared with:

```
echo 1> /proc/sys/vm/drop_caches
```

runspec command invoked through numactl i.e.:

```
numactl --interleave=all runspec <etc>
```

Base Compiler Invocation

C benchmarks:

```
icc -m64
```

C++ benchmarks:

```
icpc -m64
```

Fortran benchmarks:

```
ifort -m64
```

Benchmarks using both Fortran and C:

```
icc -m64 ifort -m64
```

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64

416.gamess: -DSPEC_CPU_LP64

433.milc: -DSPEC_CPU_LP64

434.zeusmp: -DSPEC_CPU_LP64

435.gromacs: -DSPEC_CPU_LP64 -nofor_main

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS B260 M4 (Intel Xeon E7-4890 v2 @ 2.80GHz)

SPECfp_rate2006 = Not Run

SPECfp_rate_base2006 = 865

CPU2006 license: 9019

Test date: Feb-2014

Test sponsor: Cisco Systems

Hardware Availability: May-2014

Tested by: Cisco Systems

Software Availability: Sep-2013

Base Portability Flags (Continued)

```
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main  
437.leslie3d: -DSPEC_CPU_LP64  
444.namd: -DSPEC_CPU_LP64  
447.dealII: -DSPEC_CPU_LP64  
450.soplex: -DSPEC_CPU_LP64  
453.povray: -DSPEC_CPU_LP64  
454.calculix: -DSPEC_CPU_LP64 -nofor_main  
459.GemsFDTD: -DSPEC_CPU_LP64  
465.tonto: -DSPEC_CPU_LP64  
470.lbm: -DSPEC_CPU_LP64  
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX  
482.sphinx3: -DSPEC_CPU_LP64
```

Base Optimization Flags

C benchmarks:

```
-xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32 -ansi-alias  
-opt-mem-layout-trans=3
```

C++ benchmarks:

```
-xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32 -ansi-alias  
-opt-mem-layout-trans=3
```

Fortran benchmarks:

```
-xAVX -ipo -O3 -no-prec-div -opt-prefetch
```

Benchmarks using both Fortran and C:

```
-xAVX -ipo -O3 -no-prec-div -opt-prefetch -auto-p32 -ansi-alias  
-opt-mem-layout-trans=3
```

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html>

<http://www.spec.org/cpu2006/flags/Cisco-Platform-Settings-V1.2.20140311.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml>

<http://www.spec.org/cpu2006/flags/Cisco-Platform-Settings-V1.2.20140311.xml>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Cisco Systems

Cisco UCS B260 M4 (Intel Xeon E7-4890 v2 @ 2.80GHz)

SPECfp_rate2006 = Not Run

SPECfp_rate_base2006 = 865

CPU2006 license: 9019

Test date: Feb-2014

Test sponsor: Cisco Systems

Hardware Availability: May-2014

Tested by: Cisco Systems

Software Availability: Sep-2013

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.

Report generated on Thu Jul 24 21:23:25 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 11 March 2014.