



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Quanta Computer Inc. S400-X44E

SPECfp[®]2006 = **87.2**

SPECfp_base2006 = **83.3**

CPU2006 license: 9050


Test sponsor: Quanta Computer Inc.

Tested by: Quanta Computer Inc.

Test date: Jul-2014

Hardware Availability: Jul-2014

Software Availability: Jul-2014



Hardware

CPU Name: Intel Xeon E5-4657L v2
 CPU Characteristics: Intel Turbo Boost Technology up to 2.90 GHz
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 48 cores, 4 chips, 12 cores/chip, 2 threads/core
 CPU(s) orderable: 1,2,3,4 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Red Hat Enterprise Linux Server release 6.5 (Santiago)
 2.6.32-431.el6.x86_64
 Compiler: C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux;
 Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux
 Auto Parallel: Yes
 File System: ext4

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Quanta Computer Inc.
S400-X44E

SPECfp2006 = 87.2
SPECfp_base2006 = 83.3

CPU2006 license: 9050
Test sponsor: Quanta Computer Inc.
Tested by: Quanta Computer Inc.
Test date: Jul-2014
Hardware Availability: Jul-2014
Software Availability: Jul-2014

L3 Cache: 30 MB I+D on chip per chip
Other Cache: None
Memory: 256 GB (32 x 8 GB 1Rx4 PC3-14900R-13, ECC)
Disk Subsystem: 690 GB add more disk info here
Other Hardware: None
System State: Run level 3 (multi user mode)
Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	<u>21.6</u>	<u>628</u>	21.2	640	23.4	580	<u>21.6</u>	<u>628</u>	21.2	640	23.4	580
416.gamess	<u>707</u>	<u>27.7</u>	707	27.7	706	27.7	628	31.2	<u>628</u>	<u>31.2</u>	628	31.2
433.milc	167	54.9	167	55.0	<u>167</u>	<u>54.9</u>	165	55.7	165	55.8	<u>165</u>	<u>55.7</u>
434.zeusmp	69.1	132	<u>69.1</u>	<u>132</u>	69.5	131	69.1	132	<u>69.1</u>	<u>132</u>	69.5	131
435.gromacs	207	34.4	208	34.4	<u>207</u>	<u>34.4</u>	207	34.4	208	34.4	<u>207</u>	<u>34.4</u>
436.cactusADM	32.2	371	<u>31.8</u>	<u>376</u>	31.8	376	32.2	371	<u>31.8</u>	<u>376</u>	31.8	376
437.leslie3d	50.3	187	<u>50.9</u>	<u>185</u>	51.7	182	50.3	187	<u>50.9</u>	<u>185</u>	51.7	182
444.namd	403	19.9	403	19.9	<u>403</u>	<u>19.9</u>	<u>394</u>	<u>20.4</u>	394	20.4	394	20.3
447.dealII	250	45.7	<u>250</u>	<u>45.7</u>	250	45.7	250	45.7	<u>250</u>	<u>45.7</u>	250	45.7
450.soplex	209	39.9	<u>208</u>	<u>40.0</u>	208	40.2	209	39.9	<u>208</u>	<u>40.0</u>	208	40.2
453.povray	137	38.7	<u>138</u>	<u>38.7</u>	140	37.9	116	46.1	<u>116</u>	<u>46.0</u>	116	45.7
454.calculix	231	35.8	<u>231</u>	<u>35.7</u>	232	35.6	<u>204</u>	<u>40.4</u>	204	40.4	204	40.4
459.GemsFDTD	<u>59.7</u>	<u>178</u>	59.9	177	59.3	179	56.4	188	55.4	192	<u>55.4</u>	<u>192</u>
465.tonto	<u>324</u>	<u>30.3</u>	323	30.5	334	29.4	<u>253</u>	<u>38.9</u>	255	38.5	253	38.9
470.lbm	<u>13.4</u>	<u>1020</u>	14.6	940	13.2	1040	<u>13.4</u>	<u>1020</u>	14.6	940	13.2	1040
481.wrf	126	88.7	<u>128</u>	<u>87.5</u>	129	86.9	126	88.7	<u>128</u>	<u>87.5</u>	129	86.9
482.sphinx3	321	60.8	<u>321</u>	<u>60.8</u>	322	60.6	322	60.5	318	61.4	<u>319</u>	<u>61.1</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

Platform Notes

Sysinfo program /root/speccpu_linux/config/sysinfo.rev6818
\$Rev: 6818 \$ \$Date:: 2012-07-17 #\$ e86d102572650a6e4d596a3cee98f191
running on localhost.localdomain Sat Jul 5 10:45:55 2014

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo
model name : Intel(R) Xeon(R) CPU E5-4657L v2 @ 2.40GHz
Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Quanta Computer Inc.
S400-X44E

SPECfp2006 = 87.2

SPECfp_base2006 = 83.3

CPU2006 license: 9050

Test sponsor: Quanta Computer Inc.

Tested by: Quanta Computer Inc.

Test date: Jul-2014

Hardware Availability: Jul-2014

Software Availability: Jul-2014

Platform Notes (Continued)

```

4 "physical id"s (chips)
96 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
cpu cores : 12
siblings  : 24
physical 0: cores 0 1 2 3 4 5 8 9 10 11 12 13
physical 1: cores 0 1 2 3 4 5 8 9 10 11 12 13
physical 2: cores 0 1 2 3 4 5 8 9 10 11 12 13
physical 3: cores 0 1 2 3 4 5 8 9 10 11 12 13
cache size : 30720 KB

```

```

From /proc/meminfo
MemTotal:      264494508 kB
HugePages_Total:      0
Hugepagesize:    2048 kB

```

```

/usr/bin/lsb_release -d
Red Hat Enterprise Linux Server release 6.5 (Santiago)

```

```

From /etc/*release* /etc/*version*
redhat-release: Red Hat Enterprise Linux Server release 6.5 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.5 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server

```

```

uname -a:
Linux localhost.localdomain 2.6.32-431.el6.x86_64 #1 SMP Sun Nov 10 22:19:54
EST 2013 x86_64 x86_64 x86_64 GNU/Linux

```

run-level 3 Jul 4 15:28

```

SPEC is set to: /root/speccpu_linux
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sda2        ext4  690G  15G  640G   3% /

```

```

Additional information from dmidecode:
BIOS American Megatrends Inc. S4E_4A06 06/27/2014
Memory:

```

```

1x ChannelA_Dimm2_Manufacturer ChannelA_Dimm2_PartNum
1x ChannelB_Dimm2_Manufacturer ChannelB_Dimm2_PartNum
1x ChannelC_Dimm2_Manufacturer ChannelC_Dimm2_PartNum
1x ChannelD_Dimm2_Manufacturer ChannelD_Dimm2_PartNum
1x ChannelE_Dimm2_Manufacturer ChannelE_Dimm2_PartNum
1x ChannelF_Dimm2_Manufacturer ChannelF_Dimm2_PartNum
1x ChannelG_Dimm2_Manufacturer ChannelG_Dimm2_PartNum
1x ChannelH_Dimm2_Manufacturer ChannelH_Dimm2_PartNum
1x ChannelJ_Dimm2_Manufacturer ChannelJ_Dimm2_PartNum
1x ChannelK_Dimm2_Manufacturer ChannelK_Dimm2_PartNum
1x ChannelL_Dimm2_Manufacturer ChannelL_Dimm2_PartNum
1x ChannelM_Dimm2_Manufacturer ChannelM_Dimm2_PartNum
1x ChannelN_Dimm2_Manufacturer ChannelN_Dimm2_PartNum
Continued on next page

```



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Quanta Computer Inc.
S400-X44E

SPECfp2006 = 87.2
SPECfp_base2006 = 83.3

CPU2006 license: 9050
Test sponsor: Quanta Computer Inc.
Tested by: Quanta Computer Inc.

Test date: Jul-2014
Hardware Availability: Jul-2014
Software Availability: Jul-2014

Platform Notes (Continued)

1x ChannelP_Dimm2_Manufacturer ChannelP_Dimm2_PartNum
1x ChannelR_Dimm2_Manufacturer ChannelR_Dimm2_PartNum
1x ChannelT_Dimm2_Manufacturer ChannelT_Dimm2_PartNum
32x Samsung M393B1G70QH0-CMA 8 GB 1866 MHz 1 rank

(End of data from sysinfo program)

General Notes

Environment variables set by runspec before the start of the run:

```
KMP_AFFINITY = "granularity=fine,compact,1,0"  
LD_LIBRARY_PATH = "/root/speccpu_linux/libs/32:/root/speccpu_linux/libs/64:/root/speccpu_linux/sh"  
OMP_NUM_THREADS = "48"
```

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB
memory using RedHat EL 6.4
Transparent Huge Pages enabled with:
echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled
runspec command invoked through numactl i.e.:
numactl --interleave=all runspec <etc>

Base Compiler Invocation

C benchmarks:
icc -m64

C++ benchmarks:
icpc -m64

Fortran benchmarks:
ifort -m64

Benchmarks using both Fortran and C:
icc -m64 ifort -m64

Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64  
416.gamess: -DSPEC_CPU_LP64  
433.milc: -DSPEC_CPU_LP64  
434.zeusmp: -DSPEC_CPU_LP64  
435.gromacs: -DSPEC_CPU_LP64 -nofor_main  
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main  
437.leslie3d: -DSPEC_CPU_LP64  
444.namd: -DSPEC_CPU_LP64  
447.dealII: -DSPEC_CPU_LP64
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Quanta Computer Inc.
S400-X44E

SPECfp2006 = 87.2

SPECfp_base2006 = 83.3

CPU2006 license: 9050

Test sponsor: Quanta Computer Inc.

Tested by: Quanta Computer Inc.

Test date: Jul-2014

Hardware Availability: Jul-2014

Software Availability: Jul-2014

Base Portability Flags (Continued)

450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch -ansi-alias
C++ benchmarks:
-xAVX -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias
Fortran benchmarks:
-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch
Benchmarks using both Fortran and C:
-xAVX -ipo -O3 -no-prec-div -parallel -opt-prefetch -ansi-alias

Peak Compiler Invocation

C benchmarks:
icc -m64
C++ benchmarks:
icpc -m64
Fortran benchmarks:
ifort -m64
Benchmarks using both Fortran and C:
icc -m64 ifort -m64

Peak Portability Flags

Same as Base Portability Flags



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Quanta Computer Inc.
S400-X44E

SPECfp2006 = 87.2
SPECfp_base2006 = 83.3

CPU2006 license: 9050

Test sponsor: Quanta Computer Inc.

Tested by: Quanta Computer Inc.

Test date: Jul-2014

Hardware Availability: Jul-2014

Software Availability: Jul-2014

Peak Optimization Flags

C benchmarks:

433.milc: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -auto-ilp32
-ansi-alias

470.lbm: basepeak = yes

482.sphinx3: -xAVX -ipo -O3 -no-prec-div -unroll2 -ansi-alias
-parallel

C++ benchmarks:

444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias
-auto-ilp32

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc
-opt-malloc-options=3 -auto -unroll4

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Quanta Computer Inc.
S400-X44E

SPECfp2006 = 87.2

SPECfp_base2006 = 83.3

CPU2006 license: 9050

Test sponsor: Quanta Computer Inc.

Tested by: Quanta Computer Inc.

Test date: Jul-2014

Hardware Availability: Jul-2014

Software Availability: Jul-2014

Peak Optimization Flags (Continued)

454.calculix: -xAVX -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html>

<http://www.spec.org/cpu2006/flags/Quanta-Computer-Inc-Platform-Settings-V1.0.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml>

<http://www.spec.org/cpu2006/flags/Quanta-Computer-Inc-Platform-Settings-V1.0.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Fri Aug 8 10:40:28 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 8 August 2014.