



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Quanta Computer Inc.

SPECfp[®]2006 = **111**

T21P-4U (Intel Xeon E5-2698 v3)

SPECfp_base2006 = **105**

CPU2006 license: 9050


Test date: Nov-2014

Test sponsor: Quanta Computer Inc.

Hardware Availability: Nov-2014

Tested by: Quanta Computer Inc.

Software Availability: Nov-2013



Hardware

CPU Name: Intel Xeon E5-2698 v3
 CPU Characteristics: Intel Turbo Boost Technology up to 3.60 GHz
 CPU MHz: 2300
 FPU: Integrated
 CPU(s) enabled: 32 cores, 2 chips, 16 cores/chip, 2 threads/core
 CPU(s) orderable: 1,2 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Red Hat Enterprise Linux Server release 6.5 (Santiago)
 2.6.32-431.el6.x86_64
 Compiler: C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux;
 Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux
 Auto Parallel: Yes
 File System: ext4

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Quanta Computer Inc.

SPECfp2006 = 111

T21P-4U (Intel Xeon E5-2698 v3)

SPECfp_base2006 = 105

CPU2006 license: 9050

Test date: Nov-2014

Test sponsor: Quanta Computer Inc.

Hardware Availability: Nov-2014

Tested by: Quanta Computer Inc.

Software Availability: Nov-2013

L3 Cache: 40 MB I+D on chip per chip
Other Cache: None
Memory: 128 GB (8 x 16 GB 2Rx4 PC4-2133P-R)

System State: Run level 3 (multi-user)
Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: None

Disk Subsystem: 197 GB 1 x 240 GB SATA, SSD
Other Hardware: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	22.2	612	22.2	612	<u>22.2</u>	<u>612</u>	22.2	612	22.2	612	<u>22.2</u>	<u>612</u>
416.gamess	597	32.8	<u>598</u>	<u>32.8</u>	600	32.6	461	42.5	461	42.4	<u>461</u>	<u>42.4</u>
433.milc	125	73.7	<u>125</u>	<u>73.7</u>	125	73.5	124	73.9	<u>124</u>	<u>73.8</u>	125	73.6
434.zeusmp	<u>47.6</u>	<u>191</u>	47.6	191	47.8	190	<u>47.6</u>	<u>191</u>	47.6	191	47.8	190
435.gromacs	<u>192</u>	<u>37.2</u>	192	37.2	196	36.5	<u>192</u>	<u>37.2</u>	192	37.2	196	36.5
436.cactusADM	15.3	783	15.5	773	<u>15.3</u>	<u>783</u>	15.3	783	15.5	773	<u>15.3</u>	<u>783</u>
437.leslie3d	30.2	311	28.6	328	<u>28.8</u>	<u>326</u>	30.2	311	28.6	328	<u>28.8</u>	<u>326</u>
444.namd	285	28.1	285	28.2	<u>285</u>	<u>28.2</u>	276	29.1	<u>276</u>	<u>29.1</u>	276	29.1
447.dealII	196	58.4	<u>195</u>	<u>58.7</u>	195	58.7	196	58.4	<u>195</u>	<u>58.7</u>	195	58.7
450.soplex	186	44.7	<u>186</u>	<u>44.9</u>	184	45.4	186	44.7	<u>186</u>	<u>44.9</u>	184	45.4
453.povray	96.3	55.3	<u>95.1</u>	<u>56.0</u>	94.3	56.4	<u>85.0</u>	<u>62.6</u>	85.2	62.4	83.0	64.1
454.calculix	185	44.6	<u>185</u>	<u>44.7</u>	184	44.9	161	51.4	<u>161</u>	<u>51.4</u>	161	51.3
459.GemsFDTD	<u>47.8</u>	<u>222</u>	48.0	221	47.8	222	43.1	246	43.3	245	<u>43.1</u>	<u>246</u>
465.tonto	276	35.7	<u>275</u>	<u>35.7</u>	274	35.9	199	49.4	<u>199</u>	<u>49.5</u>	199	49.5
470.lbm	16.4	837	<u>16.8</u>	<u>817</u>	17.0	807	16.4	837	<u>16.8</u>	<u>817</u>	17.0	807
481.wrf	<u>107</u>	<u>104</u>	109	102	106	105	<u>107</u>	<u>104</u>	109	102	106	105
482.sphinx3	<u>302</u>	<u>64.4</u>	302	64.5	305	63.8	306	63.8	309	63.1	<u>307</u>	<u>63.6</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

Platform Notes

Default BIOS settings were used
Sysinfo program /speccpu/speccpu_linux/config/sysinfo.rev6818
\$Rev: 6818 \$ \$Date:: 2012-07-17 #\$ e86d102572650a6e4d596a3cee98f191
running on localhost.localdomain Sun Nov 16 12:06:35 2014

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Quanta Computer Inc.

SPECfp2006 = 111

T21P-4U (Intel Xeon E5-2698 v3)

SPECfp_base2006 = 105

CPU2006 license: 9050

Test date: Nov-2014

Test sponsor: Quanta Computer Inc.

Hardware Availability: Nov-2014

Tested by: Quanta Computer Inc.

Software Availability: Nov-2013

Platform Notes (Continued)

```

From /proc/cpuinfo
model name : Intel(R) Xeon(R) CPU E5-2698 v3 @ 2.30GHz
 2 "physical id"s (chips)
 64 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
  cpu cores : 16
  siblings  : 32
  physical 0: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15
  physical 1: cores 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15
cache size : 40960 KB

```

```

From /proc/meminfo
MemTotal:      132046688 kB
HugePages_Total:      1
Hugepagesize:    2048 kB

```

```

/usr/bin/lsb_release -d
Red Hat Enterprise Linux Server release 6.5 (Santiago)

```

```

From /etc/*release* /etc/*version*
redhat-release: Red Hat Enterprise Linux Server release 6.5 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.5 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server

```

```

uname -a:
Linux localhost.localdomain 2.6.32-431.el6.x86_64 #1 SMP Sun Nov 10 22:19:54
EST 2013 x86_64 x86_64 x86_64 GNU/Linux

```

run-level 3 Nov 14 15:45

```

SPEC is set to: /speccpu/speccpu_linux
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sdca2      ext4  197G  13G  175G   7% /

```

```

Additional information from dmidecode:
BIOS American Megatrends Inc. S2P_2A06 10/30/2014
Memory:
 8x NO DIMM NO DIMM
 8x Samsung M393A2G40DB0-CPB 16 GB 2133 MHz 2 rank

```

(End of data from sysinfo program)

General Notes

Environment variables set by runspec before the start of the run:

KMP_AFFINITY = "granularity=fine,compact,1,0"

LD_LIBRARY_PATH = "/speccpu/speccpu_linux/libs/32:/speccpu/speccpu_linux/libs/64:/speccpu/speccpu_linux/sh"

OMP_NUM_THREADS = "32"

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Quanta Computer Inc.

SPECfp2006 = 111

T21P-4U (Intel Xeon E5-2698 v3)

SPECfp_base2006 = 105

CPU2006 license: 9050

Test date: Nov-2014

Test sponsor: Quanta Computer Inc.

Hardware Availability: Nov-2014

Tested by: Quanta Computer Inc.

Software Availability: Nov-2013

General Notes (Continued)

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RedHat EL 6.4
Transparent Huge Pages enabled with:
echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled
runspec command invoked through numactl i.e.:
numactl --interleave=all runspec <etc>

Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch
-ansi-alias

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Quanta Computer Inc.

SPECfp2006 = 111

T21P-4U (Intel Xeon E5-2698 v3)

SPECfp_base2006 = 105

CPU2006 license: 9050

Test date: Nov-2014

Test sponsor: Quanta Computer Inc.

Hardware Availability: Nov-2014

Tested by: Quanta Computer Inc.

Software Availability: Nov-2013

Base Optimization Flags (Continued)

C++ benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias

Fortran benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch
-ansi-alias

Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-auto-ilp32 -ansi-alias

470.lbm: basepeak = yes

482.sphinx3: -xCORE-AVX2 -ipo -O3 -no-prec-div -unroll2 -ansi-alias
-parallel

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Quanta Computer Inc.

SPECfp2006 = 111

T21P-4U (Intel Xeon E5-2698 v3)

SPECfp_base2006 = 105

CPU2006 license: 9050

Test date: Nov-2014

Test sponsor: Quanta Computer Inc.

Hardware Availability: Nov-2014

Tested by: Quanta Computer Inc.

Software Availability: Nov-2013

Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-fno-alias -auto-ilp32

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll4
-ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-inline-calloc -opt-malloc-options=3 -auto -unroll4

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xCORE-AVX2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.html>

<http://www.spec.org/cpu2006/flags/Quanta-Cloud-Technology-Platform-Settings-V1.0.html>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Quanta Computer Inc.	SPECfp2006 =	111
T21P-4U (Intel Xeon E5-2698 v3)	SPECfp_base2006 =	105

CPU2006 license: 9050	Test date: Nov-2014
Test sponsor: Quanta Computer Inc.	Hardware Availability: Nov-2014
Tested by: Quanta Computer Inc.	Software Availability: Nov-2013

You can also download the XML flags sources by saving the following links:

- <http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64.20140128.xml>
- <http://www.spec.org/cpu2006/flags/Quanta-Cloud-Technolog-Platform-Settings-V1.0.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Wed Dec 3 10:30:13 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 2 December 2014.