



SPEC® CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A8 PRO-7600B with
Radeon R7 Graphics)

SPECfp®_rate2006 = 67.6

SPECfp_rate_base2006 = 66.9

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jun-2016

Hardware Availability: Jul-2014

Software Availability: Aug-2015



SPECfp_rate_base2006 = 66.9

SPECfp_rate2006 = 67.6

Hardware

CPU Name: AMD A8 PRO-7600B
 CPU Characteristics: AMD Turbo CORE technology up to 3.80 GHz
 CPU MHz: 3100
 FPU: Integrated
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip
 CPU(s) orderable: 1 chip
 Primary Cache: 192 KB I on chip per chip, 96 KB I shared / 2 cores; 16 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip, 2 MB shared / 2 cores

Software

Operating System: Microsoft Windows 7 Ultimate 6.1.7601 Service Pack 1 Build 7601
 Compiler: C/C++: Version 16.0.0.110 of Intel C++ Studio XE for Windows;
 Fortran: Version 16.0.0.110 of Intel Fortran Studio XE for Windows;
 Libraries: Version 18.00.30723 of Microsoft Visual Studio 2013
 Auto Parallel: No

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A8 PRO-7600B with
Radeon R7 Graphics)

SPECfp_rate2006 = 67.6

SPECfp_rate_base2006 = 66.9

CPU2006 license: 13

Test date: Jun-2016

Test sponsor: Intel Corporation

Hardware Availability: Jul-2014

Tested by: Intel Corporation

Software Availability: Aug-2015

L3 Cache:	None	File System:	NTFS
Other Cache:	None	System State:	Default
Memory:	8 GB (2 x 4 GB 2Rx8 PC3-10600U-11)	Base Pointers:	32/64-bit
Disk Subsystem:	Seagate Barracuda 250 GB SATA, 7200 RPM	Peak Pointers:	32/64-bit
Other Hardware:	None	Other Software:	SmartHeap Library Version 11.0 from http://www.microquill.com/

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	794	68.4	800	68.0	765	71.2	4	794	68.4	800	68.0	765	71.2
416.gamess	4	905	86.4	898	87.2	900	87.2	4	905	86.4	898	87.2	900	87.2
433.milc	4	596	61.6	601	61.2	605	60.8	4	596	61.6	601	61.2	605	60.8
434.zeusmp	4	498	73.2	502	72.4	504	72.4	4	498	73.2	502	72.4	504	72.4
435.gromacs	4	463	61.6	462	62.0	463	61.6	4	463	61.6	462	62.0	463	61.6
436.cactusADM	4	701	68.4	706	67.6	706	67.6	4	701	68.4	706	67.6	706	67.6
437.leslie3d	4	900	41.6	912	41.2	916	41.2	4	900	41.6	912	41.2	916	41.2
444.namd	4	596	53.6	597	53.6	596	53.6	4	591	54.4	594	54.0	591	54.4
447.dealII	4	352	130	370	124	382	120	4	352	130	370	124	382	120
450.soplex	4	824	40.4	815	40.8	815	40.8	4	800	41.6	800	41.6	788	42.4
453.povray	4	221	96.0	222	95.6	224	94.8	4	201	106	202	106	200	106
454.calculix	4	375	88.0	362	91.2	364	90.8	4	375	88.0	362	91.2	364	90.8
459.GemsFDTD	4	1164	36.4	1144	37.2	1131	37.6	4	1164	36.4	1144	37.2	1131	37.6
465.tonto	4	563	70.0	561	70.0	562	70.0	4	543	72.4	547	72.0	548	71.6
470.lbm	4	646	85.2	618	88.8	626	87.6	4	646	85.2	618	88.8	626	87.6
481.wrf	4	616	72.4	581	76.8	593	75.2	4	616	72.4	581	76.8	593	75.2
482.sphinx3	4	1341	58.0	1308	59.6	1320	59.2	4	1341	58.0	1308	59.6	1320	59.2

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

To compile these binaries, the Intel Compiler 16.0 was set up to generate 64-bit binaries with the command:

"psxevars.bat intel64" (shortcut provided in the Intel(r) Parallel Studio XE 2016 program folder)

Platform Notes

Sysinfo program C:\SPEC16.0\Docs\sysinfo
\$Rev: 6775 \$ \$Date::: 2011-08-16 #\\$ \8787f7622badcf24e01c368b1db4377c
running on Clt1C872C5DF572 Thu Jun 2 17:45:04 2016

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A8 PRO-7600B with
Radeon R7 Graphics)

SPECfp_rate2006 = 67.6

SPECfp_rate_base2006 = 66.9

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jun-2016

Hardware Availability: Jul-2014

Software Availability: Aug-2015

Platform Notes (Continued)

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

```
Trying 'systeminfo'
OS Name      : Microsoft Windows 7 Ultimate
OS Version   : 6.1.7601 Service Pack 1 Build 7601
System Manufacturer: System manufacturer
System Model  : System Product Name
Processor(s)  : 1 Processor(s) Installed.
                 [01]: AMD64 Family 21 Model 48 Stepping 1 AuthenticAMD ~3100 Mhz
BIOS Version  : American Megatrends Inc. 2502, 12/11/2015
Total Physical Memory: 7,108 MB
```

```
Trying 'wmic cpu get /value'
DeviceID     : CPU0
L2CacheSize  : 25359
L3CacheSize  : 0
MaxClockSpeed: 3100
Name         : AMD A8 PRO-7600B R7, 10 Compute Cores 4C+6G
NumberOfCores: 2
NumberOfLogicalProcessors: 4
```

(End of data from sysinfo program)

Component Notes

Tested systems can be used with Shin-G ATX case,
PC Power and Cooling 1200W power supply

General Notes

450.soplex (peak): "getline_test" src.alt was used.

447.dealII (base): "max_prototype" src.alt was used.

447.dealII (base): "cxxl1_make_pair" src.alt was used.

450.soplex (base): "getline_test" src.alt was used.

447.dealII (base): "max_prototype" src.alt was used.

447.dealII (base): "cxxl1_make_pair" src.alt was used.

Binaries compiled on a system with 1x Intel Xeon E5-2699 v3 CPU
+ 64GB memory using Windows 8.1 Enterprise 64-bit

Base Compiler Invocation

C benchmarks:

icl -Qvc12 -Qstd=c99

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A8 PRO-7600B with
Radeon R7 Graphics)

SPECfp_rate2006 = 67.6

SPECfp_rate_base2006 = 66.9

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jun-2016

Hardware Availability: Jul-2014

Software Availability: Aug-2015

Base Compiler Invocation (Continued)

C++ benchmarks:

```
icl -Qvc12
```

Fortran benchmarks:

```
ifort
```

Benchmarks using both Fortran and C:

```
icl -Qvc12 -Qstd=c99 ifort
```

Base Portability Flags

```
410.bwaves: -DSPEC_CPU_P64
416.games: -DSPEC_CPU_P64
    433.milc: -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -DSPEC_CPU_P64
436.cactusADM: -DSPEC_CPU_P64 /names:lowercase /assume:underscore
437.leslie3d: -DSPEC_CPU_P64
    444.namd: -DSPEC_CPU_P64 /TP
447.dealII: -DSPEC_CPU_P64 -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
    -DSPEC_CPU_BOOST_CONFIG_MSC_VER -DSPEC_NEED_ALGORITHM
450.soplex: -DSPEC_CPU_P64 -DSPEC_GETLINE_TEST
453.povray: -DSPEC_CPU_P64
454.calculix: -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER /names:lowercase
459.GemsFDTD: -DSPEC_CPU_P64
465.tonto: -DSPEC_CPU_P64
    470.lbm: -DSPEC_CPU_P64
        481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -DSPEC_CPU_P64
```

Base Optimization Flags

C benchmarks:

```
/arch:AVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qauto-ilp32 /F10000000000 -link /FORCE:MULTIPLE
```

C++ benchmarks:

```
/arch:AVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
-Qcxx-features -Qauto-ilp32 /F10000000000 shlw64M.lib
    -link /FORCE:MULTIPLE
```

Fortran benchmarks:

```
/arch:AVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch
/F10000000000 -link /FORCE:MULTIPLE
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc.

(Test Sponsor: Intel Corporation)

ASUS A88X-PRO Motherboard (AMD A8 PRO-7600B with
Radeon R7 Graphics)

SPECfp_rate2006 = 67.6

SPECfp_rate_base2006 = 66.9

CPU2006 license: 13

Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Jun-2016

Hardware Availability: Jul-2014

Software Availability: Aug-2015

Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:

```
/arch:AVX -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch  
-Qauto-ilp32 /F1000000000 -link /FORCE:MULTIPLE
```

Peak Compiler Invocation

C benchmarks:

```
icl -Qvc12 -Qstd=c99
```

C++ benchmarks:

```
icl -Qvc12
```

Fortran benchmarks:

```
ifort
```

Benchmarks using both Fortran and C:

```
icl -Qvc12 -Qstd=c99 ifort
```

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

```
433.milc: basepeak = yes
```

```
470.lbm: basepeak = yes
```

```
482.sphinx3: basepeak = yes
```

C++ benchmarks:

```
444.namd: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)  
-Qipo -O3 -Qprec-div- -Oa -Qauto-ilp32 /F1000000000  
shlw64M.lib -link /FORCE:MULTIPLE
```

```
447.dealII: basepeak = yes
```

```
450.soplex: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)  
-Qipo -O3 -Qauto-ilp32 /F1000000000 shlw64M.lib  
-link /FORCE:MULTIPLE
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ASUSTeK Computer Inc. (Test Sponsor: Intel Corporation) ASUS A88X-PRO Motherboard (AMD A8 PRO-7600B with Radeon R7 Graphics)	SPECfp_rate2006 = 67.6 SPECfp_rate_base2006 = 66.9
CPU2006 license: 13 Test sponsor: Intel Corporation Tested by: Intel Corporation	Test date: Jun-2016 Hardware Availability: Jul-2014 Software Availability: Aug-2015

Peak Optimization Flags (Continued)

```
453.povray: /arch:AVX(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
           -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qauto-ilp32
           /F100000000000 shlw64M.lib           -link /FORCE:MULTIPLE
```

Fortran benchmarks:

```
410.bwaves: basepeak = yes  
416.gamess: basepeak = yes  
434.zeusmp: basepeak = yes  
437.leslie3d: basepeak = yes  
459.GemsFDTD: basepeak = yes  
465.tortoise: basepeak = NVV/noise
```

```
-Qipo -O3 -Qprec-div -Qunroll14 -Qauto /F10000000000  
          -link /FORCE:MULTIPLE
```

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes
436.cactusADM: basepeak = yes
454.calculix: basepeak = yes
481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at [/tmp/repo/flags](#).

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-windows.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.

Report generated on Tue Sep 20 15:06:39 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 20 September 2016.