



SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

Epsylon Sp. z o.o. Sp. Komandytowa
eterio 220 RF0 Type2 (Intel Xeon E5-2620 v4, 2.10 GHz)

SPECrate®2017_fp_base = 55.7
SPECrate®2017_fp_peak = 56.7

CPU2017 License: 9081


Test Date: Oct-2018

Test Sponsor: Epsylon Sp. z o.o. Sp. Komandytowa

Hardware Availability: Sep-2017

Tested by: Epsylon Sp. z o.o. Sp. Komandytowa

Software Availability: Sep-2018



Hardware	
CPU Name:	Intel Xeon E5-2620 v4
Max MHz:	3000
Nominal:	2100
Enabled:	16 cores, 2 chips, 2 threads/core
Orderable:	1,2 chips
Cache L1:	32 KB I + 32 KB D on chip per core
L2:	256 KB I+D on chip per core
L3:	20 MB I+D on chip per chip
Other:	None
Memory:	128 GB (4 x 32 GB 2Rx4 PC4-2666V-R, running at 2133)
Storage:	4 x 2 TB SAS3 configured as RAID5 volume
Other:	None

Software	
OS:	CentOS Linux release 7.5.1804 (Core)
Compiler:	3.10.0-862.14.4.el7.x86_64 C/C++: Version 18.0.0.128 of Intel C/C++ Compiler for Linux; Fortran: Version 18.0.0.128 of Intel Fortran Compiler for Linux
Parallel:	No
Firmware:	Version BIOS 4E4C206G released Oct-2018
File System:	xfs
System State:	Run level 3 (multi-user)
Base Pointers:	64-bit
Peak Pointers:	64-bit
Other:	None
Power Management:	--



SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

Epsylon Sp. z o.o. Sp. Komandytowa
eterio 220 RF0 Type2 (Intel Xeon E5-2620 v4, 2.10 GHz)

SPECrate®2017_fp_base = 55.7
SPECrate®2017_fp_peak = 56.7

CPU2017 License: 9081

Test Date: Oct-2018

Test Sponsor: Epsylon Sp. z o.o. Sp. Komandytowa

Hardware Availability: Sep-2017

Tested by: Epsylon Sp. z o.o. Sp. Komandytowa

Software Availability: Sep-2018

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
503.bwaves_r	32	2307	139	2306	139	2306	139	32	2306	139	2305	139	2305	139
507.cactuBSSN_r	32	813	49.8	808	50.2	809	50.1	32	824	49.1	826	49.0	823	49.2
508.namd_r	32	700	43.4	701	43.3	698	43.5	32	695	43.7	694	43.8	703	43.3
510.parest_r	32	2546	32.9	2540	33.0	2542	32.9	32	2533	33.0	2526	33.1	2533	33.1
511.povray_r	32	1080	69.2	1076	69.5	1074	69.6	32	902	82.8	904	82.7	917	81.5
519.lbm_r	32	1037	32.5	1037	32.5	1036	32.5	32	1023	33.0	1024	32.9	1022	33.0
521.wrf_r	32	1167	61.4	1170	61.2	1171	61.2	32	1167	61.4	1167	61.4	1167	61.4
526.blender_r	32	776	62.8	777	62.7	777	62.7	32	774	63.0	775	62.9	775	62.9
527.cam4_r	32	859	65.1	858	65.2	854	65.5	32	846	66.2	849	65.9	849	65.9
538.imagick_r	32	849	93.8	849	93.8	848	93.8	32	849	93.7	849	93.8	849	93.8
544.nab_r	32	680	79.2	676	79.7	689	78.2	32	660	81.6	662	81.4	660	81.6
549.fotonik3d_r	32	2863	43.6	2867	43.5	2865	43.5	32	2867	43.5	2866	43.5	2864	43.5
554.roms_r	32	1852	27.4	1852	27.5	1853	27.4	32	1850	27.5	1854	27.4	1851	27.5

SPECrate®2017_fp_base = 55.7

SPECrate®2017_fp_peak = 56.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

General Notes

Environment variables set by runcpu before the start of the run:

```
LD_LIBRARY_PATH = "/cpu2017.1.0/lib/ia32:/cpu2017.1.0/lib/intel64:/cpu2017.1.0/je5.0.1-32:/cpu2017.1.0/je5.0.1-64"
```

Binaries compiled on a system with 1x Intel Core i7-4790 CPU + 32 GB RAM memory using Redhat Enterprise Linux 7.4

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1) is mitigated in the system as tested and documented.

Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2) is mitigated in the system as tested and documented.

(Continued on next page)



SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

Epsylon Sp. z o.o. Sp. Komandytowa
eterio 220 RF0 Type2 (Intel Xeon E5-2620 v4, 2.10
GHz)

SPECrate®2017_fp_base = 55.7
SPECrate®2017_fp_peak = 56.7

CPU2017 License: 9081

Test Date: Oct-2018

Test Sponsor: Epsylon Sp. z o.o. Sp. Komandytowa

Hardware Availability: Sep-2017

Tested by: Epsylon Sp. z o.o. Sp. Komandytowa

Software Availability: Sep-2018

General Notes (Continued)

Transparent Huge Pages enabled by default

Prior to runcpu invocation

Filesystem page cache synced and cleared with:

```
sync; echo 3> /proc/sys/vm/drop_caches
runcpu command invoked through numactl i.e.:
numactl --interleave=all runcpu <etc>
```

Platform Notes

BIOS Default + NUMA = Enabled

Sysinfo program /cpu2017.1.0/bin/sysinfo
Rev: r5797 of 2017-06-14 96c45e4568ad54c135fd618bcc091c0f
running on SUT Mon Oct 29 23:48:53 2018

SUT (System Under Test) info as seen by some common utilities.

For more information on this section, see

<https://www.spec.org/cpu2017/Docs/config.html#sysinfo>

From /proc/cpuinfo

```
model name : Intel(R) Xeon(R) CPU E5-2620 v4 @ 2.10GHz
  2 "physical id"s (chips)
  32 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The following
excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
  cpu cores : 8
  siblings   : 16
  physical 0: cores 0 1 2 3 4 5 6 7
  physical 1: cores 0 1 2 3 4 5 6 7
```

From lscpu:

```
Architecture:           x86_64
CPU op-mode(s):        32-bit, 64-bit
Byte Order:            Little Endian
CPU(s):                32
On-line CPU(s) list:  0-31
Thread(s) per core:   2
Core(s) per socket:   8
Socket(s):             2
NUMA node(s):          2
Vendor ID:             GenuineIntel
CPU family:            6
Model:                 79
Model name:            Intel(R) Xeon(R) CPU E5-2620 v4 @ 2.10GHz
Stepping:               1
```

(Continued on next page)



SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

Epsylon Sp. z o.o. Sp. Komandytowa
eterio 220 RF0 Type2 (Intel Xeon E5-2620 v4, 2.10 GHz)

SPECrate®2017_fp_base = 55.7
SPECrate®2017_fp_peak = 56.7

CPU2017 License: 9081

Test Date: Oct-2018

Test Sponsor: Epsylon Sp. z o.o. Sp. Komandytowa

Hardware Availability: Sep-2017

Tested by: Epsylon Sp. z o.o. Sp. Komandytowa

Software Availability: Sep-2018

Platform Notes (Continued)

CPU MHz:	2098.974
CPU max MHz:	2100.0000
CPU min MHz:	1200.0000
BogoMIPS:	4190.18
Virtualization:	VT-x
L1d cache:	32K
L1i cache:	32K
L2 cache:	256K
L3 cache:	20480K
NUMA node0 CPU(s):	0-7,16-23
NUMA node1 CPU(s):	8-15,24-31
Flags:	fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx pdpe1gb rdtscp lm constant_tsc arch_perfmon pebs bts rep_good nopl xtopology nonstop_tsc aperfmpfperf eagerfpu pni pclmulqdq dtes64 ds_cpl vmx smx est tm2 ssse3 sdbg fma cx16 xtpr pdcm pcid dca sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer aes xsave avx f16c rdrand lahf_lm abm 3dnowprefetch epb cat_13 cdp_13 intel_ppin intel_pt ssbd ibrs ibpb stibp tpr_shadow vnmi flexpriority ept vpid fsgsbase tsc_adjust bmi1 hle avx2 smep bmi2 erms invpcid rtm cqm rdt_a rdseed adx smap xsaveopt cqm_llc cqm_occup_llc cqm_mbm_total cqm_mbm_local dtherm arat pln pts spec_ctrl intel_stibp flush_l1d

```
/proc/cpuinfo cache data
cache size : 20480 KB
```

From numactl --hardware WARNING: a numactl 'node' might or might not correspond to a physical chip.

```
available: 2 nodes (0-1)
node 0 cpus: 0 1 2 3 4 5 6 7 16 17 18 19 20 21 22 23
node 0 size: 65429 MB
node 0 free: 52541 MB
node 1 cpus: 8 9 10 11 12 13 14 15 24 25 26 27 28 29 30 31
node 1 size: 65536 MB
node 1 free: 56369 MB
node distances:
node    0    1
  0: 10 21
  1: 21 10
```

```
From /proc/meminfo
MemTotal:      131752272 kB
HugePages_Total:      0
Hugepagesize:     2048 kB
```

```
From /etc/*release* /etc/*version*
centos-release: CentOS Linux release 7.5.1804 (Core)
centos-release-upstream: Derived from Red Hat Enterprise Linux 7.5 (Source)
os-release:
```

(Continued on next page)



SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

Epsylon Sp. z o.o. Sp. Komandytowa
eterio 220 RF0 Type2 (Intel Xeon E5-2620 v4, 2.10
GHz)

SPECrate®2017_fp_base = 55.7
SPECrate®2017_fp_peak = 56.7

CPU2017 License: 9081

Test Date: Oct-2018

Test Sponsor: Epsylon Sp. z o.o. Sp. Komandytowa

Hardware Availability: Sep-2017

Tested by: Epsylon Sp. z o.o. Sp. Komandytowa

Software Availability: Sep-2018

Platform Notes (Continued)

```
NAME="CentOS Linux"
VERSION="7 (Core)"
ID="centos"
ID_LIKE="rhel fedora"
VERSION_ID="7"
PRETTY_NAME="CentOS Linux 7 (Core)"
ANSI_COLOR="0;31"
CPE_NAME="cpe:/o:centos:centos:7"
redhat-release: CentOS Linux release 7.5.1804 (Core)
system-release: CentOS Linux release 7.5.1804 (Core)
system-release-cpe: cpe:/o:centos:centos:7

uname -a:
Linux SUT 3.10.0-862.14.4.el7.x86_64 #1 SMP Wed Sep 26 15:12:11 UTC 2018 x86_64 x86_64
x86_64 GNU/Linux

run-level 3 Oct 29 10:12

SPEC is set to: /cpu2017.1.0
Filesystem           Type  Size  Used Avail Use% Mounted on
/dev/mapper/centos-root xfs   5.5T   29G   5.5T   1%  /


Additional information from dmidecode follows. WARNING: Use caution when you interpret
this section. The 'dmidecode' program reads system data which is "intended to allow
hardware to be accurately determined", but the intent may not be met, as there are
frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

BIOS American Megatrends Inc. 4E4C206G 10/15/2018
Memory:
 12x NO DIMM NO DIMM
 4x Samsung M393A4K40CB2-CTD 32 GB 2 rank 2667, configured at 2133

(End of data from sysinfo program)
```

Compiler Version Notes

```
=====
C          | 519.lbm_r(base, peak) 538.imagick_r(base, peak)
          | 544.nab_r(base, peak)
-----
icc (ICC) 18.0.0 20170811
Copyright (C) 1985-2017 Intel Corporation. All rights reserved.
-----

=====
C++         | 508.namd_r(base, peak) 510.parest_r(base, peak)
-----
```

(Continued on next page)



SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

Epsylon Sp. z o.o. Sp. Komandytowa
eterio 220 RF0 Type2 (Intel Xeon E5-2620 v4, 2.10
GHz)

SPECCrate®2017_fp_base = 55.7
SPECCrate®2017_fp_peak = 56.7

CPU2017 License: 9081

Test Date: Oct-2018

Test Sponsor: Epsylon Sp. z o.o. Sp. Komandytowa

Hardware Availability: Sep-2017

Tested by: Epsylon Sp. z o.o. Sp. Komandytowa

Software Availability: Sep-2018

Compiler Version Notes (Continued)

icpc (ICC) 18.0.0 20170811

Copyright (C) 1985-2017 Intel Corporation. All rights reserved.

=====

C++, C | 511.povray_r(base, peak) 526.blender_r(base, peak)

icpc (ICC) 18.0.0 20170811

Copyright (C) 1985-2017 Intel Corporation. All rights reserved.

icc (ICC) 18.0.0 20170811

Copyright (C) 1985-2017 Intel Corporation. All rights reserved.

=====

C++, C, Fortran | 507.cactuBSSN_r(base, peak)

icpc (ICC) 18.0.0 20170811

Copyright (C) 1985-2017 Intel Corporation. All rights reserved.

icc (ICC) 18.0.0 20170811

Copyright (C) 1985-2017 Intel Corporation. All rights reserved.

ifort (IFORT) 18.0.0 20170811

Copyright (C) 1985-2017 Intel Corporation. All rights reserved.

=====

Fortran | 503.bwaves_r(base, peak) 549.fotonik3d_r(base, peak)

| 554.roms_r(base, peak)

ifort (IFORT) 18.0.0 20170811

Copyright (C) 1985-2017 Intel Corporation. All rights reserved.

=====

Fortran, C | 521.wrf_r(base, peak) 527.cam4_r(base, peak)

ifort (IFORT) 18.0.0 20170811

Copyright (C) 1985-2017 Intel Corporation. All rights reserved.

icc (ICC) 18.0.0 20170811

Copyright (C) 1985-2017 Intel Corporation. All rights reserved.

Base Compiler Invocation

C benchmarks:

icc

(Continued on next page)



SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

Epsylon Sp. z o.o. Sp. Komandytowa
eterio 220 RF0 Type2 (Intel Xeon E5-2620 v4, 2.10
GHz)

SPECrate®2017_fp_base = 55.7
SPECrate®2017_fp_peak = 56.7

CPU2017 License: 9081

Test Date: Oct-2018

Test Sponsor: Epsylon Sp. z o.o. Sp. Komandytowa

Hardware Availability: Sep-2017

Tested by: Epsylon Sp. z o.o. Sp. Komandytowa

Software Availability: Sep-2018

Base Compiler Invocation (Continued)

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

ifort icc

Benchmarks using both C and C++:

icpcicc

Benchmarks using Fortran, C, and C++:

icpciccifort

Base Portability Flags

503.bwaves_r: -DSPEC_LP64
507.cactuBSSN_r: -DSPEC_LP64
508.namd_r: -DSPEC_LP64
510.parest_r: -DSPEC_LP64
511.povray_r: -DSPEC_LP64
519.lbm_r: -DSPEC_LP64
521.wrf_r: -DSPEC_LP64 -DSPEC_CASE_FLAG -convert big_endian
526.blender_r: -DSPEC_LP64 -DSPEC_LINUX -funsigned-char
527.cam4_r: -DSPEC_LP64 -DSPEC_CASE_FLAG
538.imagick_r: -DSPEC_LP64
544.nab_r: -DSPEC_LP64
549.fotonik3d_r: -DSPEC_LP64
554.roms_r: -DSPEC_LP64

Base Optimization Flags

C benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch -ffinite-math-only
-qopt-mem-layout-trans=3

C++ benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch -ffinite-math-only
-qopt-mem-layout-trans=3

(Continued on next page)



SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

Epsylon Sp. z o.o. Sp. Komandytowa
eterio 220 RF0 Type2 (Intel Xeon E5-2620 v4, 2.10
GHz)

SPECrate®2017_fp_base = 55.7
SPECrate®2017_fp_peak = 56.7

CPU2017 License: 9081

Test Date: Oct-2018

Test Sponsor: Epsylon Sp. z o.o. Sp. Komandytowa

Hardware Availability: Sep-2017

Tested by: Epsylon Sp. z o.o. Sp. Komandytowa

Software Availability: Sep-2018

Base Optimization Flags (Continued)

Fortran benchmarks:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch -ffinite-math-only  
-qopt-mem-layout-trans=3 -nostandard-realloc-lhs -align array32byte
```

Benchmarks using both Fortran and C:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch -ffinite-math-only  
-qopt-mem-layout-trans=3 -nostandard-realloc-lhs -align array32byte
```

Benchmarks using both C and C++:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch -ffinite-math-only  
-qopt-mem-layout-trans=3
```

Benchmarks using Fortran, C, and C++:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch -ffinite-math-only  
-qopt-mem-layout-trans=3 -nostandard-realloc-lhs -align array32byte
```

Base Other Flags

C benchmarks:

```
-m64 -std=c11
```

C++ benchmarks:

```
-m64
```

Fortran benchmarks:

```
-m64
```

Benchmarks using both Fortran and C:

```
-m64 -std=c11
```

Benchmarks using both C and C++:

```
-m64 -std=c11
```

Benchmarks using Fortran, C, and C++:

```
-m64 -std=c11
```

Peak Compiler Invocation

C benchmarks:

```
icc
```

(Continued on next page)



SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

Epsylon Sp. z o.o. Sp. Komandytowa
eterio 220 RF0 Type2 (Intel Xeon E5-2620 v4, 2.10
GHz)

SPECrate®2017_fp_base = 55.7
SPECrate®2017_fp_peak = 56.7

CPU2017 License: 9081

Test Date: Oct-2018

Test Sponsor: Epsylon Sp. z o.o. Sp. Komandytowa

Hardware Availability: Sep-2017

Tested by: Epsylon Sp. z o.o. Sp. Komandytowa

Software Availability: Sep-2018

Peak Compiler Invocation (Continued)

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

ifort icc

Benchmarks using both C and C++:

icpcicc

Benchmarks using Fortran, C, and C++:

icpciccifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

519.lbm_r: -prof-gen(pass 1) -prof-use(pass 2) -ipo -xCORE-AVX2 -O3
-no-prec-div -qopt-prefetch -ffinite-math-only
-qopt-mem-layout-trans=3

538.imagick_r: -xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch
-ffinite-math-only -qopt-mem-layout-trans=3

544.nab_r: Same as 519.lbm_r

C++ benchmarks:

-prof-gen(pass 1) -prof-use(pass 2) -ipo -xCORE-AVX2 -O3
-no-prec-div -qopt-prefetch -ffinite-math-only
-qopt-mem-layout-trans=3

Fortran benchmarks:

503.bwaves_r: -xCORE-AVX2 -ipo -O3 -no-prec-div -qopt-prefetch
-ffinite-math-only -qopt-mem-layout-trans=3
-nostandard-realloc-lhs -align array32byte

(Continued on next page)



SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

Epsylon Sp. z o.o. Sp. Komandytowa
eterio 220 RF0 Type2 (Intel Xeon E5-2620 v4, 2.10
GHz)

SPECrate®2017_fp_base = 55.7
SPECrate®2017_fp_peak = 56.7

CPU2017 License: 9081

Test Date: Oct-2018

Test Sponsor: Epsylon Sp. z o.o. Sp. Komandytowa

Hardware Availability: Sep-2017

Tested by: Epsylon Sp. z o.o. Sp. Komandytowa

Software Availability: Sep-2018

Peak Optimization Flags (Continued)

549.fotonik3d_r: Same as 503.bwaves_r

554.roms_r: -prof-gen(pass 1) -prof-use(pass 2) -ipo -xCORE-AVX2 -O3
-no-prec-div -qopt-prefetch -ffinite-math-only
-qopt-mem-layout-trans=3 -nostandard-realloc-lhs
-align array32byte

Benchmarks using both Fortran and C:

-prof-gen(pass 1) -prof-use(pass 2) -ipo -xCORE-AVX2 -O3
-no-prec-div -qopt-prefetch -ffinite-math-only
-qopt-mem-layout-trans=3 -nostandard-realloc-lhs -align array32byte

Benchmarks using both C and C++:

-prof-gen(pass 1) -prof-use(pass 2) -ipo -xCORE-AVX2 -O3
-no-prec-div -qopt-prefetch -ffinite-math-only
-qopt-mem-layout-trans=3

Benchmarks using Fortran, C, and C++:

-prof-gen(pass 1) -prof-use(pass 2) -ipo -xCORE-AVX2 -O3
-no-prec-div -qopt-prefetch -ffinite-math-only
-qopt-mem-layout-trans=3 -nostandard-realloc-lhs -align array32byte

Peak Other Flags

C benchmarks:

-m64 -std=c11

C++ benchmarks:

-m64

Fortran benchmarks:

-m64

Benchmarks using both Fortran and C:

-m64 -std=c11

Benchmarks using both C and C++:

-m64 -std=c11

Benchmarks using Fortran, C, and C++:

-m64 -std=c11



SPEC CPU®2017 Floating Point Rate Result

Copyright 2017-2021 Standard Performance Evaluation Corporation

Epsylon Sp. z o.o. Sp. Komandytowa
eterio 220 RF0 Type2 (Intel Xeon E5-2620 v4, 2.10
GHz)

SPECrate®2017_fp_base = 55.7

SPECrate®2017_fp_peak = 56.7

CPU2017 License: 9081

Test Date: Oct-2018

Test Sponsor: Epsylon Sp. z o.o. Sp. Komandytowa

Hardware Availability: Sep-2017

Tested by: Epsylon Sp. z o.o. Sp. Komandytowa

Software Availability: Sep-2018

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/Intel-ic18.0-official-linux64.2017-10-19.html>

<http://www.spec.org/cpu2017/flags/Epsylon-Platform-Flags-RevA-Mar-2018-For-Supermicro-Platform.2018-11-20.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2017/flags/Intel-ic18.0-official-linux64.2017-10-19.xml>

<http://www.spec.org/cpu2017/flags/Epsylon-Platform-Flags-RevA-Mar-2018-For-Supermicro-Platform.2018-11-20.xml>

SPEC CPU and SPECrate are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU®2017 v1.0.2 on 2018-10-29 23:48:52-0400.

Report generated on 2021-03-29 17:36:00 by CPU2017 PDF formatter v6442.

Originally published on 2018-11-27.