



# SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

## Hewlett Packard Enterprise

(Test Sponsor: HPE)

### HPE Compute Scale-up Server 3250

(2.00 GHz, Intel Xeon 6788P)

SPECspeed®2017\_fp\_base = 445

SPECspeed®2017\_fp\_peak = 445

CPU2017 License: 3


Test Sponsor: HPE

Tested by: HPE

Test Date: Mar-2026

Hardware Availability: Apr-2026

Software Availability: Feb-2026



### Hardware

CPU Name: Intel Xeon 6788P  
 Max MHz: 3800  
 Nominal: 2000  
 Enabled: 1032 cores, 12 chips  
 Orderable: 4, 8, 12, 16 chip(s)  
 Cache L1: 64 KB I + 48 KB D on chip per core  
 L2: 2 MB I+D on chip per core  
 L3: 336 MB I+D on chip per chip  
 Other: None  
 Memory: 6 TB (96 x 64 GB 2Rx4 PC5-6400B-R)  
 Storage: 1 x 1.5 TB NVMe SSD  
 Other: CPU Cooling: Air

### Software

OS: SUSE Linux Enterprise Server 15 SP7  
 Kernel 6.4.0-150700.53.31-default  
 Compiler: C/C++: Version 2025.2 of Intel oneAPI DPC++/C++ Compiler for Linux;  
 Fortran: Version 2025.2 of Intel Fortran Compiler for Linux;  
 Parallel: Yes  
 Firmware: HPE Firmware Bundle Version 1.0.308 01/21/2026 released Jan-2026  
 File System: xfs  
 System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit  
 Peak Pointers: 64-bit  
 Other: jemalloc memory allocator V5.0.1  
 Power Management: BIOS and OS set to prefer performance at the cost of additional power usage



# SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Hewlett Packard Enterprise**

(Test Sponsor: HPE)

**HPE Compute Scale-up Server 3250**

(2.00 GHz, Intel Xeon 6788P)

**SPECSpeed®2017\_fp\_base = 445**

**SPECSpeed®2017\_fp\_peak = 445**

**CPU2017 License:** 3  
**Test Sponsor:** HPE  
**Tested by:** HPE

**Test Date:** Mar-2026  
**Hardware Availability:** Apr-2026  
**Software Availability:** Feb-2026

## Results Table

Benchmark	Base						Peak							
	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Threads	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
603.bwaves_s	256	19.5	3020	19.4	3040	<b><u>19.4</u></b>	<b><u>3030</u></b>	256	<b><u>19.4</u></b>	<b><u>3040</u></b>	19.4	3040	19.5	3030
607.cactuBSSN_s	256	30.3	551	30.1	555	<b><u>30.1</u></b>	<b><u>554</u></b>	256	30.3	551	30.1	555	<b><u>30.1</u></b>	<b><u>554</u></b>
619.lbm_s	256	12.5	418	<b><u>12.5</u></b>	<b><u>419</u></b>	12.2	428	256	12.5	418	<b><u>12.5</u></b>	<b><u>419</u></b>	12.2	428
621.wrf_s	256	108	123	110	120	<b><u>110</u></b>	<b><u>120</u></b>	256	108	123	110	120	<b><u>110</u></b>	<b><u>120</u></b>
627.cam4_s	256	59.0	150	<b><u>60.1</u></b>	<b><u>148</u></b>	60.3	147	256	59.0	150	<b><u>60.1</u></b>	<b><u>148</u></b>	60.3	147
628.pop2_s	256	132	90.0	<b><u>132</u></b>	<b><u>90.1</u></b>	131	90.4	256	132	90.0	<b><u>132</u></b>	<b><u>90.1</u></b>	131	90.4
638.imagick_s	256	19.4	744	18.9	765	<b><u>18.9</u></b>	<b><u>764</u></b>	256	19.4	744	18.9	765	<b><u>18.9</u></b>	<b><u>764</u></b>
644.nab_s	256	<b><u>13.3</u></b>	<b><u>1310</u></b>	13.2	1330	13.4	1300	256	<b><u>13.3</u></b>	<b><u>1310</u></b>	13.2	1330	13.4	1300
649.fotonik3d_s	256	<b><u>40.3</u></b>	<b><u>226</u></b>	42.2	216	40.1	227	256	<b><u>40.3</u></b>	<b><u>226</u></b>	42.2	216	40.1	227
654.roms_s	256	13.4	1170	<b><u>13.1</u></b>	<b><u>1200</u></b>	13.1	1210	256	13.4	1170	<b><u>13.1</u></b>	<b><u>1200</u></b>	13.1	1210

**SPECSpeed®2017\_fp\_base = 445**

**SPECSpeed®2017\_fp\_peak = 445**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"  
Transparent Huge Pages enabled by default  
Prior to runcpu invocation  
Filesystem page cache synced and cleared with:  
sync; echo 3> /proc/sys/vm/drop\_caches

## Environment Variables Notes

Environment variables set by runcpu before the start of the run:  
KMP\_AFFINITY = "granularity=fine,compact"  
LD\_LIBRARY\_PATH = "/home/cpu2017/lib/intel64:/home/cpu2017/je5.0.1-64"  
MALLOC\_CONF = "retain:true"  
OMP\_STACKSIZE = "192M"

## General Notes

Binaries compiled on a system with 2x Intel Xeon Platinum 8280M CPU + 384GB RAM  
memory using Redhat Enterprise Linux 8.0  
NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown)  
is mitigated in the system as tested and documented.  
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1)  
is mitigated in the system as tested and documented.  
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2)  
is mitigated in the system as tested and documented.  
jemalloc, a general purpose malloc implementation  
built with the RedHat Enterprise 7.5, and the system compiler gcc 4.8.5  
sources available from jemalloc.net or <https://github.com/jemalloc/jemalloc/releases>

## Platform Notes

BIOS Configuration:  
Workload Profile set to HPC  
Workload Profile set to Custom

(Continued on next page)



# SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Hewlett Packard Enterprise**

(Test Sponsor: HPE)

**HPE Compute Scale-up Server 3250**

(2.00 GHz, Intel Xeon 6788P)

**SPECspeed®2017\_fp\_base = 445**

**SPECspeed®2017\_fp\_peak = 445**

**CPU2017 License:** 3

**Test Sponsor:** HPE

**Tested by:** HPE

**Test Date:** Mar-2026

**Hardware Availability:** Apr-2026

**Software Availability:** Feb-2026

## Platform Notes (Continued)

Power Regulator set to OS Control  
 Energy Efficient Turbo set to Disabled  
 Energy/Performance Bias set to Maximum Performance  
 Intel Hyper-Threading set to Disabled  
 Adjacent Sector Prefetch set to Disabled  
 LLC Prefetch set to Enabled  
 Last Level Cache (LLC) Dead Line Allocation set to Disabled  
 Enhanced Processor Performance Profile set to Aggressive  
 Memory Patrol Scrubbing set to Disabled  
 Advanced Memory Protection set to Advanced ECC Support  
 SR-IOV set to Disabled  
 Intel Virtualization Technology (Intel VT, VT-x) set to Disabled  
 Dynamic Prefetch Throttling set to Disabled  
 Enabled Cores per Processor set to 64  
 Page Policy set to Open Adaptive  
 Sub-NUMA Clustering set to Auto

Sysinfo program /home/cpu2017/bin/sysinfo  
 Rev: r6732 of 2022-11-07 fe91c89b7ed5c36ae2c92cc097bec197  
 running on gnh-108 Sun Mar 1 17:13:06 2026

SUT (System Under Test) info as seen by some common utilities.

-----  
Table of contents  
-----

1. uname -a
2. w
3. Username
4. ulimit -a
5. sysinfo process ancestry
6. /proc/cpuinfo
7. lscpu
8. numactl --hardware
9. /proc/meminfo
10. who -r
11. Systemd service manager version: systemd 254 (254.27+suse.179.g75eab961ea)
12. Services, from systemctl list-unit-files
13. Linux kernel boot-time arguments, from /proc/cmdline
14. cpupower frequency-info
15. tuned-adm active
16. sysctl
17. /sys/kernel/mm/transparent\_hugepage
18. /sys/kernel/mm/transparent\_hugepage/khugepaged
19. OS release
20. Disk information
21. /sys/devices/virtual/dmi/id
22. dmidecode
23. BIOS

-----  
 1. uname -a  
 Linux gnh-108 6.4.0-150700.53.31-default #1 SMP PREEMPT\_DYNAMIC Tue Feb 3 14:18:17 UTC 2026 (73f3a11)  
 x86\_64 x86\_64 x86\_64 GNU/Linux  
 -----

-----  
 2. w  
 17:13:06 up 3:28, 2 users, load average: 150.59, 204.83, 218.79  
 USER TTY FROM LOGIN@ IDLE JCPU PCPU WHAT  
 -----

(Continued on next page)



# SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Hewlett Packard Enterprise**

(Test Sponsor: HPE)

**HPE Compute Scale-up Server 3250**

(2.00 GHz, Intel Xeon 6788P)

**SPECspeed®2017\_fp\_base = 445**

**SPECspeed®2017\_fp\_peak = 445**

**CPU2017 License:** 3  
**Test Sponsor:** HPE  
**Tested by:** HPE

**Test Date:** Mar-2026  
**Hardware Availability:** Apr-2026  
**Software Availability:** Feb-2026

## Platform Notes (Continued)

```
test      ttyS0    -           13:48    3:16m 0.18s 0.02s login -- test
test      pts/0    -           13:48    3:16m 1.01s 0.16s sudo su
```

### 3. Username

```
From environment variable $USER:  root
From the command 'logname':      test
```

### 4. ulimit -a

```
core file size          (blocks, -c) 0
data seg size           (kbytes, -d) unlimited
scheduling priority     (-e) 0
file size               (blocks, -f) unlimited
pending signals         (-i) 24378831
max locked memory       (kbytes, -l) 8192
max memory size         (kbytes, -m) unlimited
open files              (-n) 40000
pipe size               (512 bytes, -p) 8
POSIX message queues    (bytes, -q) 819200
real-time priority      (-r) 0
stack size              (kbytes, -s) unlimited
cpu time                (seconds, -t) unlimited
max user processes      (-u) 24378831
virtual memory          (kbytes, -v) unlimited
file locks              (-x) unlimited
```

### 5. sysinfo process ancestry

```
/usr/lib/systemd/systemd --switched-root --system --deserialize=39
login -- test
-bash
sudo su
sudo su
su
bash
bash
runcpu --nobuild --action validate --define default-platform-flags -c
ic2025.2-linux64-core-avx2-speed-20250605.cfg --define cores=256 --tune base,peak -o all --define
drop_caches fpspeed
runcpu --nobuild --action validate --define default-platform-flags --configfile
ic2025.2-linux64-core-avx2-speed-20250605.cfg --define cores=256 --tune base,peak --output_format all
--define drop_caches --nopower --runmode speed --tune base:peak --size refspeed fpspeed --nopreenv
--note-preenv --logfile $SPEC/tmp/CPU2017.016/templogs/preenv.fpspeed.016.0.log --lognum 016.0
--from_runcpu 2
specperl $SPEC/bin/sysinfo
$SPEC = /home/cpu2017
```

### 6. /proc/cpuinfo

```
model name      : Intel(R) Xeon(R) 6788P
vendor_id      : GenuineIntel
cpu family     : 6
model          : 173
stepping      : 1
microcode     : 0x1000405
bugs          : spectre_v1 spectre_v2 spec_store_bypass swapgs bhi vmscape
cpu cores     : 64
siblings      : 64
12 physical ids (chips)
```

(Continued on next page)



# SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Hewlett Packard Enterprise**

(Test Sponsor: HPE)

**HPE Compute Scale-up Server 3250**  
(2.00 GHz, Intel Xeon 6788P)

**SPECspeed®2017\_fp\_base = 445**

**SPECspeed®2017\_fp\_peak = 445**

**CPU2017 License:** 3  
**Test Sponsor:** HPE  
**Tested by:** HPE

**Test Date:** Mar-2026  
**Hardware Availability:** Apr-2026  
**Software Availability:** Feb-2026

## Platform Notes (Continued)

```

768 processors (hardware threads)
physical id 0: core ids 0-31,64-95
physical id 1: core ids 0-31,64-95
physical id 2: core ids 0-31,64-95
physical id 3: core ids 0-31,64-95
physical id 4: core ids 0-31,64-95
physical id 5: core ids 0-31,64-95
physical id 6: core ids 0-31,64-95
physical id 7: core ids 0-31,64-95
physical id 8: core ids 0-31,64-95
physical id 9: core ids 0-31,64-95
physical id 10: core ids 0-31,64-95
physical id 11: core ids 0-31,64-95
physical id 0: apicids
0,2,4,6,8,10,12,14,16,18,20,22,24,26,28,30,32,34,36,38,40,42,44,46,48,50,52,54,56,58,60,62,128,130,132,134,136,138,140,142,144,146,148,150,152,154,156,158,160,162,164,166,168,170,172,174,176,178,180,182,184,186,188,190
physical id 1: apicids
256,258,260,262,264,266,268,270,272,274,276,278,280,282,284,286,288,290,292,294,296,298,300,302,304,306,308,310,312,314,316,318,384,386,388,390,392,394,396,398,400,402,404,406,408,410,412,414,416,418,420,422,424,426,428,430,432,434,436,438,440,442,444,446
physical id 2: apicids
512,514,516,518,520,522,524,526,528,530,532,534,536,538,540,542,544,546,548,550,552,554,556,558,560,562,564,566,568,570,572,574,640,642,644,646,648,650,652,654,656,658,660,662,664,666,668,670,672,674,676,678,680,682,684,686,688,690,692,694,696,698,700,702
physical id 3: apicids
768,770,772,774,776,778,780,782,784,786,788,790,792,794,796,798,800,802,804,806,808,810,812,814,816,818,820,822,824,826,828,830,896,898,900,902,904,906,908,910,912,914,916,918,920,922,924,926,928,930,932,934,936,938,940,942,944,946,948,950,952,954,956,958
physical id 4: apicids
1024,1026,1028,1030,1032,1034,1036,1038,1040,1042,1044,1046,1048,1050,1052,1054,1056,1058,1060,1062,1064,1066,1068,1070,1072,1074,1076,1078,1080,1082,1084,1086,1152,1154,1156,1158,1160,1162,1164,1166,1168,1170,1172,1174,1176,1178,1180,1182,1184,1186,1188,1190,1192,1194,1196,1198,1200,1202,1204,1206,1208,1210,1212,1214
physical id 5: apicids
1280,1282,1284,1286,1288,1290,1292,1294,1296,1298,1300,1302,1304,1306,1308,1310,1312,1314,1316,1318,1320,1322,1324,1326,1328,1330,1332,1334,1336,1338,1340,1342,1408,1410,1412,1414,1416,1418,1420,1422,1424,1426,1428,1430,1432,1434,1436,1438,1440,1442,1444,1446,1448,1450,1452,1454,1456,1458,1460,1462,1464,1466,1468,1470
physical id 6: apicids
1536,1538,1540,1542,1544,1546,1548,1550,1552,1554,1556,1558,1560,1562,1564,1566,1568,1570,1572,1574,1576,1578,1580,1582,1584,1586,1588,1590,1592,1594,1596,1598,1664,1666,1668,1670,1672,1674,1676,1678,1680,1682,1684,1686,1688,1690,1692,1694,1696,1698,1700,1702,1704,1706,1708,1710,1712,1714,1716,1718,1720,1722,1724,1726
physical id 7: apicids
1792,1794,1796,1798,1800,1802,1804,1806,1808,1810,1812,1814,1816,1818,1820,1822,1824,1826,1828,1830,1832,1834,1836,1838,1840,1842,1844,1846,1848,1850,1852,1854,1920,1922,1924,1926,1928,1930,1932,1934,1936,1938,1940,1942,1944,1946,1948,1950,1952,1954,1956,1958,1960,1962,1964,1966,1968,1970,1972,1974,1976,1978,1980,1982
physical id 8: apicids
2048,2050,2052,2054,2056,2058,2060,2062,2064,2066,2068,2070,2072,2074,2076,2078,2080,2082,2084,2086,2088,2090,2092,2094,2096,2098,2100,2102,2104,2106,2108,2110,2176,2178,2180,2182,2184,2186,2188,2190,2192,2194,2196,2198,2200,2202,2204,2206,2208,2210,2212,2214,2216,2218,2220,2222,2224,2226,2228,2230,2232,2234,2236,2238
physical id 9: apicids
2304,2306,2308,2310,2312,2314,2316,2318,2320,2322,2324,2326,2328,2330,2332,2334,2336,2338,2340,2342,2344,2346,2348,2350,2352,2354,2356,2358,2360,2362,2364,2366,2432,2434,2436,2438,2440,2442,2444,2446,2448,2450,2452,2454,2456,2458,2460,2462,2464,2466,2468,2470,2472,2474,2476,2478,2480,2482,2484,2486,2488,2490,2492,2494
physical id 10: apicids

```

(Continued on next page)



# SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Hewlett Packard Enterprise**

(Test Sponsor: HPE)

**HPE Compute Scale-up Server 3250**

(2.00 GHz, Intel Xeon 6788P)

**SPECspeed®2017\_fp\_base = 445**

**SPECspeed®2017\_fp\_peak = 445**

**CPU2017 License:** 3  
**Test Sponsor:** HPE  
**Tested by:** HPE

**Test Date:** Mar-2026  
**Hardware Availability:** Apr-2026  
**Software Availability:** Feb-2026

## Platform Notes (Continued)

2560, 2562, 2564, 2566, 2568, 2570, 2572, 2574, 2576, 2578, 2580, 2582, 2584, 2586, 2588, 2590, 2592, 2594, 2596, 2598, 2600, 2602, 2604, 2606, 2608, 2610, 2612, 2614, 2616, 2618, 2620, 2622, 2688, 2690, 2692, 2694, 2696, 2698, 2700, 2702, 2704, 2706, 2708, 2710, 2712, 2714, 2716, 2718, 2720, 2722, 2724, 2726, 2728, 2730, 2732, 2734, 2736, 2738, 2740, 2742, 2744, 2746, 2748, 2750

physical id 11: apicids

2816, 2818, 2820, 2822, 2824, 2826, 2828, 2830, 2832, 2834, 2836, 2838, 2840, 2842, 2844, 2846, 2848, 2850, 2852, 2854, 2856, 2858, 2860, 2862, 2864, 2866, 2868, 2870, 2872, 2874, 2876, 2878, 2944, 2946, 2948, 2950, 2952, 2954, 2956, 2958, 2960, 2962, 2964, 2966, 2968, 2970, 2972, 2974, 2976, 2978, 2980, 2982, 2984, 2986, 2988, 2990, 2992, 2994, 2996, 2998, 3000, 3002, 3004, 3006

Caution: /proc/cpuinfo data regarding chips, cores, and threads is not necessarily reliable, especially for virtualized systems. Use the above data carefully.

### 7. lscpu

From lscpu from util-linux 2.40.4:

```

Architecture:          x86_64
CPU op-mode(s):        32-bit, 64-bit
Address sizes:          52 bits physical, 57 bits virtual
Byte Order:             Little Endian
CPU(s):                 768
On-line CPU(s) list:   0-767
Vendor ID:              GenuineIntel
Model name:             Intel(R) Xeon(R) 6788P
CPU family:             6
Model:                  173
Thread(s) per core:    1
Core(s) per socket:    64
Socket(s):              12
Stepping:               1
CPU(s) scaling MHz:    21%
CPU max MHz:           3800.0000
CPU min MHz:           800.0000
BogoMIPS:               3999.53
Flags:                  fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat
pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx
pdpe1gb rdtscp lm constant_tsc arch_perfmon pebs bts rep_good nopl
xtopology nonstop_tsc cpuid aperfmperf pni pclmulqdq dtes64
monitor ds_cpl smx est tm2 ssse3 sdbg fma cx16 xtpr pdcm pcid dca
sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer aes xsave avx
f16c rdrand lahf_lm abm 3dnowprefetch cpuid_fault epb cat_l3
cat_l2 cdp_l3 intel_ppin cdp_l2 ssbd mba ibrs ibpb stibp
ibrs_enhanced fsgsbase tsc_adjust bmil hle avx2 smep bmi2 erms
invpcid rtm cqm rdt_a avx512f avx512dq rdseed adx smap avx512ifma
clflushopt clwb intel_pt avx512cd sha_ni avx512bw avx512vl
xsavesopt xsavec xgetbv1 xsaves cqm_llc cqm_occup_llc cqm_mbm_total
cqm_mbm_local split_lock_detect user_shstk avx_vnni avx512_bf16
wbnoinvd dtherm ida arat pln pts hwp hwp_act_window hwp_epp
hwp_pkg_req avx512vbmi umip pku ospke waitpkg avx512_vbmi2 gfni
vaes vpclmulqdq avx512_vnni avx512_bitalg tme avx512_vpoptdq
la57 rdpid bus_lock_detect cldemote movdiri movdir64b enqcmd fsrm
md_clear serialize tsxldtrk pconfig arch_lbr ibt amx_bf16
avx512_fp16 amx_tile amx_int8 flush_lld arch_capabilities
ibpb_exit_to_user
L1d cache:             36 MiB (768 instances)
L1i cache:             48 MiB (768 instances)
L2 cache:              1.5 GiB (768 instances)
L3 cache:              3.9 GiB (12 instances)
NUMA node(s):         24
NUMA node0 CPU(s):   0-31

```

(Continued on next page)



# SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Hewlett Packard Enterprise**

(Test Sponsor: HPE)

**HPE Compute Scale-up Server 3250**

(2.00 GHz, Intel Xeon 6788P)

**SPECspeed®2017\_fp\_base = 445**

**SPECspeed®2017\_fp\_peak = 445**

**CPU2017 License:** 3  
**Test Sponsor:** HPE  
**Tested by:** HPE

**Test Date:** Mar-2026  
**Hardware Availability:** Apr-2026  
**Software Availability:** Feb-2026

## Platform Notes (Continued)

```

NUMA node1 CPU(s):      32-63
NUMA node2 CPU(s):      64-95
NUMA node3 CPU(s):      96-127
NUMA node4 CPU(s):      128-159
NUMA node5 CPU(s):      160-191
NUMA node6 CPU(s):      192-223
NUMA node7 CPU(s):      224-255
NUMA node8 CPU(s):      256-287
NUMA node9 CPU(s):      288-319
NUMA node10 CPU(s):     320-351
NUMA node11 CPU(s):     352-383
NUMA node12 CPU(s):     384-415
NUMA node13 CPU(s):     416-447
NUMA node14 CPU(s):     448-479
NUMA node15 CPU(s):     480-511
NUMA node16 CPU(s):     512-543
NUMA node17 CPU(s):     544-575
NUMA node18 CPU(s):     576-607
NUMA node19 CPU(s):     608-639
NUMA node20 CPU(s):     640-671
NUMA node21 CPU(s):     672-703
NUMA node22 CPU(s):     704-735
NUMA node23 CPU(s):     736-767
Vulnerability Gather data sampling: Not affected
Vulnerability Indirect target selection: Not affected
Vulnerability Itlb multihit: Not affected
Vulnerability L1tf: Not affected
Vulnerability Mds: Not affected
Vulnerability Meltdown: Not affected
Vulnerability Mmio stale data: Not affected
Vulnerability Reg file data sampling: Not affected
Vulnerability Retbleed: Not affected
Vulnerability Spec rstack overflow: Not affected
Vulnerability Spec store bypass: Mitigation; Speculative Store Bypass disabled via prctl
Vulnerability Spectre v1: Mitigation; usercopy/swaps barriers and __user pointer sanitization
Vulnerability Spectre v2: Mitigation; Enhanced / Automatic IBRS; IBPB conditional; PBRSE-eIBRS Not affected; BHI BHI_DIS_S
Vulnerability Srbds: Not affected
Vulnerability Tsa: Not affected
Vulnerability Tsx async abort: Not affected
Vulnerability Vmscape: Mitigation; IBPB before exit to userspace

```

From lscpu --cache:

NAME	ONE-SIZE	ALL-SIZE	WAYS	TYPE	LEVEL	SETS	PHY-LINE	COHERENCY-SIZE
L1d	48K	36M	12	Data	1	64	1	64
L1i	64K	48M	16	Instruction	1	64	1	64
L2	2M	1.5G	16	Unified	2	2048	1	64
L3	336M	3.9G	16	Unified	3	344064	1	64

8. numactl --hardware

NOTE: a numactl 'node' might or might not correspond to a physical chip.

available: 24 nodes (0-23)

```

node 0 cpus: 0-31
node 0 size: 256990 MB
node 0 free: 251236 MB
node 1 cpus: 32-63
node 1 size: 250021 MB
node 1 free: 248618 MB

```

(Continued on next page)



# SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Hewlett Packard Enterprise**

(Test Sponsor: HPE)

**HPE Compute Scale-up Server 3250**

(2.00 GHz, Intel Xeon 6788P)

**SPECspeed®2017\_fp\_base = 445**

**SPECspeed®2017\_fp\_peak = 445**

**CPU2017 License:** 3

**Test Sponsor:** HPE

**Tested by:** HPE

**Test Date:** Mar-2026

**Hardware Availability:** Apr-2026

**Software Availability:** Feb-2026

## Platform Notes (Continued)

```

node 2 cpus: 64-95
node 2 size: 258039 MB
node 2 free: 254869 MB
node 3 cpus: 96-127
node 3 size: 250037 MB
node 3 free: 248898 MB
node 4 cpus: 128-159
node 4 size: 258039 MB
node 4 free: 255815 MB
node 5 cpus: 160-191
node 5 size: 250037 MB
node 5 free: 243130 MB
node 6 cpus: 192-223
node 6 size: 258039 MB
node 6 free: 250093 MB
node 7 cpus: 224-255
node 7 size: 250037 MB
node 7 free: 244836 MB
node 8 cpus: 256-287
node 8 size: 258000 MB
node 8 free: 257704 MB
node 9 cpus: 288-319
node 9 size: 250037 MB
node 9 free: 249812 MB
node 10 cpus: 320-351
node 10 size: 258039 MB
node 10 free: 257742 MB
node 11 cpus: 352-383
node 11 size: 250037 MB
node 11 free: 249785 MB
node 12 cpus: 384-415
node 12 size: 258039 MB
node 12 free: 257843 MB
node 13 cpus: 416-447
node 13 size: 250037 MB
node 13 free: 249771 MB
node 14 cpus: 448-479
node 14 size: 258039 MB
node 14 free: 257817 MB
node 15 cpus: 480-511
node 15 size: 250037 MB
node 15 free: 249818 MB
node 16 cpus: 512-543
node 16 size: 258039 MB
node 16 free: 257663 MB
node 17 cpus: 544-575
node 17 size: 250037 MB
node 17 free: 249691 MB
node 18 cpus: 576-607
node 18 size: 258039 MB
node 18 free: 257741 MB
node 19 cpus: 608-639
node 19 size: 250037 MB
node 19 free: 249676 MB
node 20 cpus: 640-671
node 20 size: 258039 MB
node 20 free: 257733 MB
node 21 cpus: 672-703
node 21 size: 250037 MB
node 21 free: 249651 MB

```

(Continued on next page)



# SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Hewlett Packard Enterprise**

(Test Sponsor: HPE)

**HPE Compute Scale-up Server 3250**

(2.00 GHz, Intel Xeon 6788P)

**SPECspeed®2017\_fp\_base = 445**

**SPECspeed®2017\_fp\_peak = 445**

**CPU2017 License:** 3  
**Test Sponsor:** HPE  
**Tested by:** HPE

**Test Date:** Mar-2026  
**Hardware Availability:** Apr-2026  
**Software Availability:** Feb-2026

## Platform Notes (Continued)

```

node 22 cpus: 704-735
node 22 size: 258039 MB
node 22 free: 257677 MB
node 23 cpus: 736-767
node 23 size: 248967 MB
node 23 free: 248635 MB
node distances:
node  0  1  2  3  4  5  6  7  8  9 10 11 12 13 14 15 16 17 18 19 20 21 22 23
0: 10 12 16 16 16 16 18 18 40 40 40 40 40 40 40 40 40 40 40 40 40 40 40
1: 12 10 16 16 16 16 18 18 40 40 40 40 40 40 40 40 40 40 40 40 40 40 40
2: 16 16 10 12 18 18 16 16 40 40 40 40 40 40 40 40 40 40 40 40 40 40 40
3: 16 16 12 10 18 18 16 16 40 40 40 40 40 40 40 40 40 40 40 40 40 40 40
4: 16 16 18 18 10 12 16 16 40 40 40 40 40 40 40 40 40 40 40 40 40 40 40
5: 16 16 18 18 12 10 16 16 40 40 40 40 40 40 40 40 40 40 40 40 40 40 40
6: 18 18 16 16 16 16 10 12 40 40 40 40 40 40 40 40 40 40 40 40 40 40 40
7: 18 18 16 16 16 16 12 10 40 40 40 40 40 40 40 40 40 40 40 40 40 40 40
8: 40 40 40 40 40 40 40 40 10 12 16 16 16 16 18 18 40 40 40 40 40 40 40
9: 40 40 40 40 40 40 40 40 12 10 16 16 16 16 18 18 40 40 40 40 40 40 40
10: 40 40 40 40 40 40 40 40 16 16 10 12 18 18 16 16 40 40 40 40 40 40 40
11: 40 40 40 40 40 40 40 40 16 16 12 10 18 18 16 16 40 40 40 40 40 40 40
12: 40 40 40 40 40 40 40 40 16 16 18 18 10 12 16 16 40 40 40 40 40 40 40
13: 40 40 40 40 40 40 40 40 16 16 18 18 12 10 16 16 40 40 40 40 40 40 40
14: 40 40 40 40 40 40 40 40 18 18 16 16 16 16 10 12 40 40 40 40 40 40 40
15: 40 40 40 40 40 40 40 40 18 18 16 16 16 16 12 10 40 40 40 40 40 40 40
16: 40 40 40 40 40 40 40 40 40 40 40 40 40 40 10 12 16 16 16 16 18 18
17: 40 40 40 40 40 40 40 40 40 40 40 40 40 40 40 12 10 16 16 16 16 18 18
18: 40 40 40 40 40 40 40 40 40 40 40 40 40 40 40 16 16 10 12 18 18 16 16
19: 40 40 40 40 40 40 40 40 40 40 40 40 40 40 40 16 16 12 10 18 18 16 16
20: 40 40 40 40 40 40 40 40 40 40 40 40 40 40 40 16 16 18 18 10 12 16 16
21: 40 40 40 40 40 40 40 40 40 40 40 40 40 40 40 16 16 18 18 12 10 16 16
22: 40 40 40 40 40 40 40 40 40 40 40 40 40 40 40 18 18 16 16 16 16 10 12
23: 40 40 40 40 40 40 40 40 40 40 40 40 40 40 40 18 18 16 16 16 16 12 10

```

```

-----
9. /proc/meminfo
MemTotal:      6241018480 kB

```

```

-----
10. who -r
run-level 3 Mar 1 13:48

```

```

-----
11. Systemd service manager version: systemd 254 (254.27+suse.179.g75eab961ea)
Default Target Status
multi-user      running

```

```

-----
12. Services, from systemctl list-unit-files
STATE UNIT FILES
enabled YaST2-Firstboot YaST2-Second-Stage apparmor appstream-sync-cache auditd bluetooth chronyd
cpuset_cpunodemap cpuset_memory_spread cron dcd dcdchkgracefulshutdown dcdshutdown
display-manager getty@ hpe-auto-config hpe_irqbalance iscsi issue-generator kbdsettings
kdump kdump-early kdump-notify klog lvm2-monitor nscd postfix purge-kernels rollback
rsyslog smartd sshd systemd-pstore vgauthd vmblock-fuse vmtoolsd vsftpd wicked
wickedd-auto4 wickedd-dhcp4 wickedd-dhcp6 wickedd-nanny
enabled-runtime systemd-fsck-root systemd-remount-fs
disabled accounts-daemon amavis apache2 apache2@ autofs autoyast-initscripts blk-availability
bluetooth-mesh boot-sysctl ca-certificates certmonger chrony-wait clamd clamonacc
console-getty cups cups-browsed cxl-monitor debug-shell ebttables exchange-bmc-os-info
firewalld fsidd gpm grub2-once haveged ipmi ipmiev d irqbalance iscsi-init iscsid

```

(Continued on next page)



# SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Hewlett Packard Enterprise**

(Test Sponsor: HPE)

**HPE Compute Scale-up Server 3250**

(2.00 GHz, Intel Xeon 6788P)

**SPECspeed®2017\_fp\_base = 445**

**SPECspeed®2017\_fp\_peak = 445**

**CPU2017 License:** 3  
**Test Sponsor:** HPE  
**Tested by:** HPE

**Test Date:** Mar-2026  
**Hardware Availability:** Apr-2026  
**Software Availability:** Feb-2026

## Platform Notes (Continued)

```

indirect
issue-add-ssh-keys kexec-load lunmask man-db-create mariadb mariadb@ multipathd named
ndctl-monitor nfs nfs-blkmap nfs-server nfsserver nmb ostree-remount ostree-state-overlay@
rpcbind rpmconfigcheck rsyncd rtkit-daemon samba-bgqd smartd_generate_opts smb snmpd
snmptrapd spamd spampd speech-dispatcherd srp_daemon srp_daemon_port@ sysstat
sysstat_collect sysstat_summary systemd-boot-check-no-failures systemd-confext
systemd-network-generator systemd-sysexit systemd-time-wait-sync systemd-timesyncd tuned
udisks2 update-system-flatpaks upower vncserver@ winbind wsdd ypbind
serial-getty@ systemd-userdbd tftpd wickedd

```

### 13. Linux kernel boot-time arguments, from /proc/cmdline

```

BOOT_IMAGE=/boot/vmlinuz-6.4.0-150700.53.31-default
root=UUID=8f7dbb2d-77d8-40d9-b606-6b60ffd4e6ad
rd.auto=1
console=ttyS0,115200n8
selinux=0
security=
splash=silent
mitigations=auto
console=ttyS0,115200
udev.children-max=512
nmi_watchdog=0
uv_nmi.action=kdump
add_efi_memmap
tsc=nowatchdog
earlyprintk=ttyS0,115200
log_buf_len=8M
numa_balancing=disable
crashkernel=1G,high
watchdog_thresh=60
workqueue.watchdog_thresh=120

```

### 14. cpupower frequency-info

```

analyzing CPU 170:
  current policy: frequency should be within 800 MHz and 3.80 GHz.
                   The governor "performance" may decide which speed to use
                   within this range.

boost state support:
  Supported: yes
  Active: yes

```

### 15. tuned-adm active

No current active profile.

### 16. sysctl

```

kernel.numa_balancing          0
kernel.randomize_va_space      2
vm.compaction_proactiveness    20
vm.dirty_background_bytes      0
vm.dirty_background_ratio     10
vm.dirty_bytes                 0
vm.dirty_expire_centisecs     3000
vm.dirty_ratio                 20
vm.dirty_writeback_centisecs   500
vm.dirtytime_expire_seconds   43200
vm.extfrag_threshold          500
vm.min_unmapped_ratio         1

```

(Continued on next page)



# SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

## Hewlett Packard Enterprise

(Test Sponsor: HPE)

HPE Compute Scale-up Server 3250  
(2.00 GHz, Intel Xeon 6788P)

SPECspeed®2017\_fp\_base = 445

SPECspeed®2017\_fp\_peak = 445

**CPU2017 License:** 3  
**Test Sponsor:** HPE  
**Tested by:** HPE

**Test Date:** Mar-2026  
**Hardware Availability:** Apr-2026  
**Software Availability:** Feb-2026

### Platform Notes (Continued)

```

vm.nr_hugepages          0
vm.nr_hugepages_mempolicy 0
vm.nr_overcommit_hugepages 0
vm.swappiness            60
vm.watermark_boost_factor 15000
vm.watermark_scale_factor 10
vm.zone_reclaim_mode     0

```

```

-----
17. /sys/kernel/mm/transparent_hugepage
defrag          always defer+madvice [madvice] never
enabled         [always] madvice never
hpage_pmd_size 2097152
shmem_enabled   always within_size advise [never] deny force

```

```

-----
18. /sys/kernel/mm/transparent_hugepage/khugepaged
alloc_sleep_millisecs 60000
defrag                 1
max_ptes_none         511
max_ptes_shared       256
max_ptes_swap         64
pages_to_scan         4096
scan_sleep_millisecs 10000

```

```

-----
19. OS release
From /etc/*-release /etc/*-version
os-release          SUSE Linux Enterprise Server 15 SP7
hpe-foundation-release HPE Foundation Software 2.5.9, Build 757.1570.260209T0200.a.sles15sp7hpe-260209T0200

```

```

-----
20. Disk information
SPEC is set to: /home/cpu2017
Filesystem  Type  Size  Used Avail Use% Mounted on
/dev/nvme1n1p2 xfs  1.5T  64G  1.4T   5% /

```

```

-----
21. /sys/devices/virtual/dmi/id
Vendor:          HPE
Product:         Compute Scale-up Server 3250
Product Family: 1590PID03030202
Serial:          5UFD3H1626-000

```

```

-----
22. dmidecode
Additional information from dmidecode 3.6 follows.  WARNING: Use caution when you interpret this section.
The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately
determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the
"DMTF SMBIOS" standard.
Memory:
  46x Samsung M321R8GA0EB2-CCPKC 64 GB 2 rank 6400
  50x Samsung M321R8GA0EB2-CCPWC 64 GB 2 rank 6400

```

```

-----
23. BIOS
(This section combines info from /sys/devices and dmidecode.)
BIOS Vendor:      HPE
BIOS Version:     Bundle:1.0.308-20260123_101935 SFW:010.001.004.000.2601210240

```

(Continued on next page)



# SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Hewlett Packard Enterprise**

(Test Sponsor: HPE)

**HPE Compute Scale-up Server 3250**

(2.00 GHz, Intel Xeon 6788P)

SPECspeed®2017\_fp\_base = 445

SPECspeed®2017\_fp\_peak = 445

**CPU2017 License:** 3  
**Test Sponsor:** HPE  
**Tested by:** HPE

**Test Date:** Mar-2026  
**Hardware Availability:** Apr-2026  
**Software Availability:** Feb-2026

## Platform Notes (Continued)

BIOS Date: 01/21/2026

## Compiler Version Notes

=====  
C | 619.lbm\_s(base, peak) 638.imagick\_s(base, peak) 644.nab\_s(base, peak)  
=====

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2025.2.0 Build 20250605  
Copyright (C) 1985-2025 Intel Corporation. All rights reserved.  
=====

=====  
C++, C, Fortran | 607.cactuBSSN\_s(base, peak)  
=====

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2025.2.0 Build 20250605  
Copyright (C) 1985-2025 Intel Corporation. All rights reserved.

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2025.2.0 Build 20250605  
Copyright (C) 1985-2025 Intel Corporation. All rights reserved.

Intel(R) Fortran Compiler for applications running on Intel(R) 64, Version 2025.2.0 Build 20250605  
Copyright (C) 1985-2025 Intel Corporation. All rights reserved.  
=====

=====  
Fortran | 603.bwaves\_s(base, peak) 649.fotonik3d\_s(base, peak) 654.roms\_s(base, peak)  
=====

Intel(R) Fortran Compiler for applications running on Intel(R) 64, Version 2025.2.0 Build 20250605  
Copyright (C) 1985-2025 Intel Corporation. All rights reserved.  
=====

=====  
Fortran, C | 621.wrf\_s(base, peak) 627.cam4\_s(base, peak) 628.pop2\_s(base, peak)  
=====

Intel(R) Fortran Compiler for applications running on Intel(R) 64, Version 2025.2.0 Build 20250605  
Copyright (C) 1985-2025 Intel Corporation. All rights reserved.

Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2025.2.0 Build 20250605  
Copyright (C) 1985-2025 Intel Corporation. All rights reserved.  
=====

## Base Compiler Invocation

C benchmarks:

icx

Fortran benchmarks:

ifx

Benchmarks using both Fortran and C:

ifx icx

Benchmarks using Fortran, C, and C++:

icpx icx ifx



# SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Hewlett Packard Enterprise**

(Test Sponsor: HPE)

**HPE Compute Scale-up Server 3250**

(2.00 GHz, Intel Xeon 6788P)

**SPECspeed®2017\_fp\_base = 445**

**SPECspeed®2017\_fp\_peak = 445**

**CPU2017 License:** 3

**Test Sponsor:** HPE

**Tested by:** HPE

**Test Date:** Mar-2026

**Hardware Availability:** Apr-2026

**Software Availability:** Feb-2026

## Base Portability Flags

```

603.bwaves_s: -DSPEC_LP64
607.cactuBSSN_s: -DSPEC_LP64
619.lbm_s: -DSPEC_LP64
621.wrf_s: -DSPEC_LP64 -DSPEC_CASE_FLAG -convert big_endian
627.cam4_s: -DSPEC_LP64 -DSPEC_CASE_FLAG
628.pop2_s: -DSPEC_LP64 -DSPEC_CASE_FLAG -convert big_endian
-assume byterecl
638.imagick_s: -DSPEC_LP64
644.nab_s: -DSPEC_LP64
649.fotonik3d_s: -DSPEC_LP64
654.roms_s: -DSPEC_LP64

```

## Base Optimization Flags

### C benchmarks:

```

-w -std=c11 -m64 -Wl,-z,muldefs -xCORE-AVX2 -Ofast -ffast-math
-flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4 -fiopenmp
-DSPEC_OPENMP -Wno-implicit-int -L/usr/local/jemalloc64-5.0.1/lib
-ljemalloc

```

### Fortran benchmarks:

```

-w -m64 -Wl,-z,muldefs -DSPEC_OPENMP -xCORE-AVX2 -Ofast -ffast-math
-flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4 -fiopenmp
-nostandard-realloc-lhs -align array32byte -auto
-L/usr/local/jemalloc64-5.0.1/lib -ljemalloc

```

### Benchmarks using both Fortran and C:

```

-w -m64 -std=c11 -Wl,-z,muldefs -xCORE-AVX2 -Ofast -ffast-math
-flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4 -fiopenmp
-DSPEC_OPENMP -Wno-implicit-int -nostandard-realloc-lhs
-align array32byte -auto -L/usr/local/jemalloc64-5.0.1/lib -ljemalloc

```

### Benchmarks using Fortran, C, and C++:

```

-w -std=c++14 -m64 -std=c11 -Wl,-z,muldefs -xCORE-AVX2 -Ofast
-ffast-math -flto -mfpmath=sse -funroll-loops
-qopt-mem-layout-trans=4 -fiopenmp -DSPEC_OPENMP -Wno-implicit-int
-nostandard-realloc-lhs -align array32byte -auto
-L/usr/local/jemalloc64-5.0.1/lib -ljemalloc

```



# SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Hewlett Packard Enterprise**

(Test Sponsor: HPE)

**HPE Compute Scale-up Server 3250**

(2.00 GHz, Intel Xeon 6788P)

**SPECspeed®2017\_fp\_base = 445**

**SPECspeed®2017\_fp\_peak = 445**

**CPU2017 License:** 3  
**Test Sponsor:** HPE  
**Tested by:** HPE

**Test Date:** Mar-2026  
**Hardware Availability:** Apr-2026  
**Software Availability:** Feb-2026

## Peak Compiler Invocation

C benchmarks:

icx

Fortran benchmarks:

ifx

Benchmarks using both Fortran and C:

ifx icx

Benchmarks using Fortran, C, and C++:

icpx icx ifx

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

619.lbm\_s: basepeak = yes

638.imagick\_s: basepeak = yes

644.nab\_s: basepeak = yes

Fortran benchmarks:

603.bwaves\_s: -w -m64 -Wl,-z,muldefs -DSPEC\_OPENMP -xCORE-AVX2 -Ofast  
-ffast-math -flto -mfpmath=sse -funroll-loops  
-gopt-mem-layout-trans=4 -fiopenmp -nostandard-realloc-lhs  
-align array32byte -auto -L/usr/local/jemalloc64-5.0.1/lib  
-ljemalloc

649.fotonik3d\_s: basepeak = yes

654.roms\_s: basepeak = yes

Benchmarks using both Fortran and C:

621.wrf\_s: basepeak = yes

(Continued on next page)



# SPEC CPU®2017 Floating Point Speed Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

**Hewlett Packard Enterprise**

(Test Sponsor: HPE)

**HPE Compute Scale-up Server 3250**

(2.00 GHz, Intel Xeon 6788P)

**SPECspeed®2017\_fp\_base = 445**

**SPECspeed®2017\_fp\_peak = 445**

**CPU2017 License:** 3

**Test Sponsor:** HPE

**Tested by:** HPE

**Test Date:** Mar-2026

**Hardware Availability:** Apr-2026

**Software Availability:** Feb-2026

## Peak Optimization Flags (Continued)

627.cam4\_s: basepeak = yes

628.pop2\_s: basepeak = yes

Benchmarks using Fortran, C, and C++:

607.cactuBSSN\_s: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2017/flags/HPE-Platform-Flags-Intel-CSS-GNR-rev1.3.html>

<http://www.spec.org/cpu2017/flags/Intel-ic2025-official-linux64.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2017/flags/HPE-Platform-Flags-Intel-CSS-GNR-rev1.3.xml>

<http://www.spec.org/cpu2017/flags/Intel-ic2025-official-linux64.xml>

SPEC CPU and SPECspeed are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact [info@spec.org](mailto:info@spec.org).

Tested with SPEC CPU®2017 v1.1.9 on 2026-03-01 18:13:06-0500.

Report generated on 2026-05-26 11:59:57 by CPU2017 PDF formatter v6716.

Originally published on 2026-04-21.