SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise

(Test Sponsor: HPE)

Compute Scale-up Server 3250
(2.00 GHz, Intel Xeon 6788P)

SPECrate®2017_int_base = 6110

SPECrate®2017_int_peak = 6200

CPU2017 License: 3
Test Sponsor: HPE
Tested by: HPE

Test Date: Feb-2026
Hardware Availability: Apr-2026
Software Availability: Feb-2026



Hardware

CPU Name:	Intel Xeon 6788P
Max MHz:	3800
Nominal:	2000
Enabled:	688 cores, 8 chips, 2 threads/core
Orderable:	4, 8, 12, 16 chip(s)
Cache L1:	64 KB I + 48 KB D on chip per core
L2:	2 MB I+D on chip per core
L3:	336 MB I+D on chip per chip
Other:	None
Memory:	4 TB (64 x 64 GB 2Rx4 PC5-6400B-R)
Storage:	1 x 1.5 TB NVMe SSD
Other:	CPU Cooling: Air

Software

OS:	SUSE Linux Enterprise Server 15 SP7 Kernel 6.4.0-150700.53.31-default
Compiler:	C/C++: Version 2025.2 of Intel oneAPI DPC++/C++ Compiler for Linux; Fortran: Version 2025.2 of Intel Fortran Compiler for Linux;
Parallel:	No
Firmware:	HPE Firmware Bundle Version 1.0.306 01/10/2026 released Jan-2026
File System:	xfs
System State:	Run level 3 (multi-user)
Base Pointers:	64-bit
Peak Pointers:	64-bit
Other:	None
Power Management:	BIOS and OS set to prefer performance at the cost of additional power usage

SPEC CPU®2017 Integer Rate Result

Copyright 2017-2026 Standard Performance Evaluation Corporation

Hewlett Packard Enterprise
(Test Sponsor: HPE)
Compute Scale-up Server 3250
(2.00 GHz, Intel Xeon 6788P)

SPECrate®2017_int_base = 6110

SPECrate®2017_int_peak = 6200

CPU2017 License: 3
Test Sponsor: HPE
Tested by: HPE

Test Date: Feb-2026
Hardware Availability: Apr-2026
Software Availability: Feb-2026

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
500.perlbench_r	1376	441	4970	**445**	**4920**	445	4920	1376	401	5470	408	5360	**401**	**5460**
502.gcc_r	1376	450	4330	450	4330	**450**	**4330**	1376	450	4330	450	4330	**450**	**4330**
505.mcf_r	1376	266	8350	**266**	**8360**	266	8360	1376	266	8350	**266**	**8360**	266	8360
520.omnetpp_r	1376	**567**	**3180**	566	3190	567	3180	1376	**567**	**3180**	566	3190	567	3180
523.xalancbmk_r	1376	**168**	**8630**	171	8520	168	8640	1376	**168**	**8630**	171	8520	168	8640
525.x264_r	1376	172	14000	168	14300	**170**	**14200**	1376	164	14600	166	14500	**165**	**14600**
531.deepsjeng_r	1376	**313**	**5030**	305	5160	314	5020	1376	**313**	**5030**	305	5160	314	5020
541.leela_r	1376	**461**	**4940**	460	4950	464	4910	1376	**461**	**4940**	460	4950	464	4910
548.exchange2_r	1376	**241**	**15000**	238	15200	245	14700	1376	**241**	**15000**	238	15200	245	14700
557.xz_r	1376	526	2830	526	2820	**526**	**2820**	1376	526	2830	526	2820	**526**	**2820**

SPECrate®2017_int_base = 6110

SPECrate®2017_int_peak = 6200

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The numactl mechanism was used to bind copies to processors. The config file option 'submit'
was used to generate numactl commands to bind each copy to a specific processor.
For details, please see the config file.
```

Operating System Notes

```
Stack size set to unlimited using "ulimit -s unlimited"
```

Environment Variables Notes

```
Environment variables set by runcpu before the start of the run:
LD_LIBRARY_PATH = "/home/cpu2017_new/lib/intel64:/home/cpu2017_new/lib/ia32:/home/cpu2017_new/je5.0.1-32"
MALLOC_CONF = "retain:true"
```

General Notes

```
Binaries compiled on a system with 2x Intel Xeon Platinum 8280M CPU + 384GB RAM
memory using Red Hat Enterprise Linux 8.4
NA: The test sponsor attests, as of date of publication, that CVE-2017-5754 (Meltdown)
is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5753 (Spectre variant 1)
is mitigated in the system as tested and documented.
Yes: The test sponsor attests, as of date of publication, that CVE-2017-5715 (Spectre variant 2)
is mitigated in the system as tested and documented.
```

Platform Notes

```
Workload Profile set to Custom
Energy/Performance Bias set to Maximum Performance
Energy Efficient Turbo set to Disabled
```

(Continued on next page)

Platform Notes (Continued)

```
Advanced Memory Protection set to Advanced ECC Support
SR-IOV set to Disabled
Intel Virtualization Technology (Intel VT, VT-x) set to Disabled
Dynamic Prefetch Throttling set to Conservative
DCU Stream Prefetcher set to Disabled
Last Level Cache (LLC) Dead Line Allocation set to Disabled
Enhanced Processor Performance Profile set to Aggressive
Memory Patrol Scrubbing set to Disabled
Page Policy set to Open Adaptive

Sysinfo program /home/cpu2017_new/bin/sysinfo
Rev: r6732 of 2022-11-07 fe91c89b7ed5c36ae2c92cc097bec197
running on gnh-159 Wed Feb 18 22:38:17 2026

SUT (System Under Test) info as seen by some common utilities.

------------------------------------------------------------
Table of contents
------------------------------------------------------------
 1. uname -a
 2. w
 3. Username
 4. ulimit -a
 5. sysinfo process ancestry
 6. /proc/cpuinfo
 7. lscpu
 8. numactl --hardware
 9. /proc/meminfo
10. who -r
11. Systemd service manager version: systemd 254 (254.27+suse.179.g75eab961ea)
12. Services, from systemctl list-unit-files
13. Linux kernel boot-time arguments, from /proc/cmdline
14. cpupower frequency-info
15. tuned-adm active
16. sysctl
17. /sys/kernel/mm/transparent_hugepage
18. /sys/kernel/mm/transparent_hugepage/khugepaged
19. OS release
20. Disk information
21. /sys/devices/virtual/dmi/id
22. dmidecode
23. BIOS
------------------------------------------------------------

------------------------------------------------------------
1. uname -a
  Linux gnh-159 6.4.0-150700.53.31-default #1 SMP PREEMPT_DYNAMIC Tue Feb  3 14:18:17 UTC 2026 (73f3a11)
  x86_64 x86_64 x86_64 GNU/Linux

------------------------------------------------------------
2. w
   22:38:18 up  6:48,  1 user,  load average: 0.09, 0.20, 1.00
  USER     TTY      FROM             LOGIN@   IDLE   JCPU   PCPU WHAT
  test     ttyS0    -                15:54   10.00s  0.45s  0.06s login -- test
  test     pts/0    -                15:54   10.00s  1.86s  0.35s sudo su

------------------------------------------------------------
3. Username
  From environment variable $USER:  root
  From the command 'logname':       test
```

(Continued on next page)

Platform Notes (Continued)

```
------------------------------------------------------------
4. ulimit -a
  core file size          (blocks, -c) 0
  data seg size           (kbytes, -d) unlimited
  scheduling priority             (-e) 0
  file size               (blocks, -f) unlimited
  pending signals                 (-i) 16247671
  max locked memory       (kbytes, -l) 8192
  max memory size         (kbytes, -m) unlimited
  open files                      (-n) 40000
  pipe size            (512 bytes, -p) 8
  POSIX message queues     (bytes, -q) 819200
  real-time priority              (-r) 0
  stack size              (kbytes, -s) unlimited
  cpu time               (seconds, -t) unlimited
  max user processes              (-u) 16247671
  virtual memory          (kbytes, -v) unlimited
  file locks                      (-x) unlimited

------------------------------------------------------------
5. sysinfo process ancestry
 /usr/lib/systemd/systemd --switched-root --system --deserialize=39
 login -- test
 -bash
 sudo su
 sudo su
 su
 bash
 bash
 runcpu --nobuild --action validate --define default-platform-flags --define numcopies=1376 -c
   ic2025.2-linux64-graniterapids-rate-20250605.cfg --define smt-on --define cores=688 --define physicalfirst
   --define invoke_with_interleave --define drop_caches --tune base,peak -o all intrate
 runcpu --nobuild --action validate --define default-platform-flags --define numcopies=1376 --configfile
   ic2025.2-linux64-graniterapids-rate-20250605.cfg --define smt-on --define cores=688 --define physicalfirst
   --define invoke_with_interleave --define drop_caches --tune base,peak --output_format all --nopower
   --runmode rate --tune base:peak --size refrate intrate --nopreenv --note-preenv --logfile
   $SPEC/tmp/CPU2017.001/templogs/preenv.intrate.001.0.log --lognum 001.0 --from_runcpu 2
 specperl $SPEC/bin/sysinfo
$SPEC = /home/cpu2017_new

------------------------------------------------------------
6. /proc/cpuinfo
    model name      : Intel(R) Xeon(R) 6788P
    vendor_id       : GenuineIntel
    cpu family      : 6
    model           : 173
    stepping        : 1
    microcode       : 0x1000405
    bugs            : spectre_v1 spectre_v2 spec_store_bypass swapgs bhi vmscape
    cpu cores       : 86
    siblings        : 172
    8 physical ids (chips)
    1376 processors (hardware threads)
    physical id 0: core ids 0-42,64-106
    physical id 1: core ids 0-42,64-106
    physical id 2: core ids 0-42,64-106
    physical id 3: core ids 0-42,64-106
    physical id 4: core ids 0-42,64-106
    physical id 5: core ids 0-42,64-106
```

(Continued on next page)

Platform Notes (Continued)

```
     physical id 6: core ids 0-42,64-106
     physical id 7: core ids 0-42,64-106
     physical id 0: apicids 0-85,128-213
     physical id 1: apicids 256-341,384-469
     physical id 2: apicids 512-597,640-725
     physical id 3: apicids 768-853,896-981
     physical id 4: apicids 1024-1109,1152-1237
     physical id 5: apicids 1280-1365,1408-1493
     physical id 6: apicids 1536-1621,1664-1749
     physical id 7: apicids 1792-1877,1920-2005
   Caution: /proc/cpuinfo data regarding chips, cores, and threads is not necessarily reliable, especially for
   virtualized systems.  Use the above data carefully.

 ------------------------------------------------------------
 7. lscpu

 From lscpu from util-linux 2.40.4:
   Architecture:                            x86_64
   CPU op-mode(s):                          32-bit, 64-bit
   Address sizes:                           52 bits physical, 57 bits virtual
   Byte Order:                              Little Endian
   CPU(s):                                  1376
   On-line CPU(s) list:                     0-1375
   Vendor ID:                               GenuineIntel
   Model name:                              Intel(R) Xeon(R) 6788P
   CPU family:                              6
   Model:                                   173
   Thread(s) per core:                      2
   Core(s) per socket:                      86
   Socket(s):                               8
   Stepping:                                1
   CPU(s) scaling MHz:                      21%
   CPU max MHz:                             3800.0000
   CPU min MHz:                             800.0000
   BogoMIPS:                                3999.46
   Flags:                                   fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat
                                            pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx
                                            pdpe1gb rdtscp lm constant_tsc arch_perfmon pebs bts rep_good nopl
                                            xtopology nonstop_tsc cpuid aperfmperf pni pclmulqdq dtes64
                                            monitor ds_cpl smx est tm2 ssse3 sdbg fma cx16 xtpr pdcm pcid dca
                                            sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer aes xsave avx
                                            f16c rdrand lahf_lm abm 3dnowprefetch cpuid_fault epb cat_l3
                                            cat_l2 cdp_l3 intel_ppin cdp_l2 ssbd mba ibrs ibpb stibp
                                            ibrs_enhanced fsgsbase tsc_adjust bmi1 hle avx2 smep bmi2 erms
                                            invpcid rtm cqm rdt_a avx512f avx512dq rdseed adx smap avx512ifma
                                            clflushopt clwb intel_pt avx512cd sha_ni avx512bw avx512vl
                                            xsaveopt xsavec xgetbv1 xsaves cqm_llc cqm_occup_llc cqm_mbm_total
                                            cqm_mbm_local split_lock_detect user_shstk avx_vnni avx512_bf16
                                            wbnoinvd dtherm ida arat pln pts hwp hwp_act_window hwp_epp
                                            hwp_pkg_req avx512vbmi umip pku ospke waitpkg avx512_vbmi2 gfni
                                            vaes vpclmulqdq avx512_vnni avx512_bitalg tme avx512_vpopcntdq
                                            la57 rdpid bus_lock_detect cldemote movdiri movdir64b enqcmd fsrm
                                            md_clear serialize tsxldtrk pconfig arch_lbr ibt amx_bf16
                                            avx512_fp16 amx_tile amx_int8 flush_l1d arch_capabilities
                                            ibpb_exit_to_user
   L1d cache:                               32.3 MiB (688 instances)
   L1i cache:                               43 MiB (688 instances)
   L2 cache:                                1.3 GiB (688 instances)
   L3 cache:                                2.6 GiB (8 instances)
   NUMA node(s):                            16
```

(Continued on next page)

Platform Notes (Continued)

```
   NUMA node0 CPU(s):                    0-42,688-730
   NUMA node1 CPU(s):                    43-85,731-773
   NUMA node2 CPU(s):                    86-128,774-816
   NUMA node3 CPU(s):                    129-171,817-859
   NUMA node4 CPU(s):                    172-214,860-902
   NUMA node5 CPU(s):                    215-257,903-945
   NUMA node6 CPU(s):                    258-300,946-988
   NUMA node7 CPU(s):                    301-343,989-1031
   NUMA node8 CPU(s):                    344-386,1032-1074
   NUMA node9 CPU(s):                    387-429,1075-1117
   NUMA node10 CPU(s):                   430-472,1118-1160
   NUMA node11 CPU(s):                   473-515,1161-1203
   NUMA node12 CPU(s):                   516-558,1204-1246
   NUMA node13 CPU(s):                   559-601,1247-1289
   NUMA node14 CPU(s):                   602-644,1290-1332
   NUMA node15 CPU(s):                   645-687,1333-1375
   Vulnerability Gather data sampling:   Not affected
   Vulnerability Indirect target selection: Not affected
   Vulnerability Itlb multihit:          Not affected
   Vulnerability L1tf:                   Not affected
   Vulnerability Mds:                    Not affected
   Vulnerability Meltdown:               Not affected
   Vulnerability Mmio stale data:        Not affected
   Vulnerability Reg file data sampling: Not affected
   Vulnerability Retbleed:               Not affected
   Vulnerability Spec rstack overflow:   Not affected
   Vulnerability Spec store bypass:      Mitigation; Speculative Store Bypass disabled via prctl
   Vulnerability Spectre v1:             Mitigation; usercopy/swapgs barriers and __user pointer
                                         sanitization
   Vulnerability Spectre v2:             Mitigation; Enhanced / Automatic IBRS; IBPB conditional;
                                         PBRSB-eIBRS Not affected; BHI BHI_DIS_S
   Vulnerability Srbds:                  Not affected
   Vulnerability Tsa:                    Not affected
   Vulnerability Tsx async abort:        Not affected
   Vulnerability Vmscape:                Mitigation; IBPB before exit to userspace

 From lscpu --cache:
      NAME ONE-SIZE ALL-SIZE WAYS TYPE        LEVEL   SETS PHY-LINE COHERENCY-SIZE
      L1d       48K    32.3M   12 Data            1     64        1             64
      L1i       64K      43M   16 Instruction     1     64        1             64
      L2         2M     1.3G   16 Unified         2   2048        1             64
      L3       336M     2.6G   16 Unified         3 344064        1             64

 ------------------------------------------------------------
 8. numactl --hardware
 NOTE: a numactl 'node' might or might not correspond to a physical chip.
   available: 16 nodes (0-15)
   node 0 cpus: 0-42,688-730
   node 0 size: 256724 MB
   node 0 free: 242269 MB
   node 1 cpus: 43-85,731-773
   node 1 size: 249968 MB
   node 1 free: 242689 MB
   node 2 cpus: 86-128,774-816
   node 2 size: 258025 MB
   node 2 free: 257251 MB
   node 3 cpus: 129-171,817-859
   node 3 size: 250023 MB
   node 3 free: 244097 MB
   node 4 cpus: 172-214,860-902
```

(Continued on next page)

Platform Notes (Continued)

```
   node 4 size: 258025 MB
   node 4 free: 257141 MB
   node 5 cpus: 215-257,903-945
   node 5 size: 250023 MB
   node 5 free: 248928 MB
   node 6 cpus: 258-300,946-988
   node 6 size: 258025 MB
   node 6 free: 256415 MB
   node 7 cpus: 301-343,989-1031
   node 7 size: 250023 MB
   node 7 free: 240271 MB
   node 8 cpus: 344-386,1032-1074
   node 8 size: 258025 MB
   node 8 free: 257503 MB
   node 9 cpus: 387-429,1075-1117
   node 9 size: 250023 MB
   node 9 free: 249491 MB
   node 10 cpus: 430-472,1118-1160
   node 10 size: 258025 MB
   node 10 free: 257456 MB
   node 11 cpus: 473-515,1161-1203
   node 11 size: 250023 MB
   node 11 free: 249521 MB
   node 12 cpus: 516-558,1204-1246
   node 12 size: 258025 MB
   node 12 free: 257550 MB
   node 13 cpus: 559-601,1247-1289
   node 13 size: 250023 MB
   node 13 free: 249492 MB
   node 14 cpus: 602-644,1290-1332
   node 14 size: 258025 MB
   node 14 free: 257449 MB
   node 15 cpus: 645-687,1333-1375
   node 15 size: 248947 MB
   node 15 free: 248485 MB
   node distances:
   node   0   1   2   3   4   5   6   7   8   9  10  11  12  13  14  15
     0:  10  12  16  16  16  16  18  18  40  40  40  40  40  40  40  40
     1:  12  10  16  16  16  16  18  18  40  40  40  40  40  40  40  40
     2:  16  16  10  12  18  18  16  16  40  40  40  40  40  40  40  40
     3:  16  16  12  10  18  18  16  16  40  40  40  40  40  40  40  40
     4:  16  16  18  18  10  12  16  16  40  40  40  40  40  40  40  40
     5:  16  16  18  18  12  10  16  16  40  40  40  40  40  40  40  40
     6:  18  18  16  16  16  16  10  12  40  40  40  40  40  40  40  40
     7:  18  18  16  16  16  16  12  10  40  40  40  40  40  40  40  40
     8:  40  40  40  40  40  40  40  40  10  12  16  16  16  16  18  18
     9:  40  40  40  40  40  40  40  40  12  10  16  16  16  16  18  18
    10:  40  40  40  40  40  40  40  40  16  16  10  12  18  18  16  16
    11:  40  40  40  40  40  40  40  40  16  16  12  10  18  18  16  16
    12:  40  40  40  40  40  40  40  40  16  16  18  18  10  12  16  16
    13:  40  40  40  40  40  40  40  40  16  16  18  18  12  10  16  16
    14:  40  40  40  40  40  40  40  40  18  18  16  16  16  16  10  12
    15:  40  40  40  40  40  40  40  40  18  18  16  16  16  16  12  10

------------------------------------------------------------
9. /proc/meminfo
   MemTotal:       4159441668 kB

------------------------------------------------------------
10. who -r
```

(Continued on next page)

Platform Notes (Continued)

```
  run-level 3 Feb 18 15:55

------------------------------------------------------------
11. Systemd service manager version: systemd 254 (254.27+suse.179.g75eab961ea)
  Default Target  Status
  multi-user      running

------------------------------------------------------------
12. Services, from systemctl list-unit-files
  STATE            UNIT FILES
  enabled          YaST2-Firstboot YaST2-Second-Stage apparmor appstream-sync-cache auditd bluetooth chronyd
                   cpuset_cpunodemap cpuset_memory_spread cron dcd dcdchkgracefulshutdown dcdshutdown
                   display-manager getty@ hpe-auto-config hpe_irqbalance iscsi issue-generator kbdsettings
                   kdump kdump-early kdump-notify klog lvm2-monitor nscd postfix purge-kernels rollback
                   rsyslog smartd sshd systemd-pstore vgauthd vmblock-fuse vmtoolsd vsftpd wicked
                   wickedd-auto4 wickedd-dhcp4 wickedd-dhcp6 wickedd-nanny
  enabled-runtime  systemd-fsck-root systemd-remount-fs
  disabled         accounts-daemon amavis apache2 apache2@ autofs autoyast-initscripts blk-availability
                   bluetooth-mesh boot-sysctl ca-certificates certmonger chrony-wait clamd clamonacc
                   console-getty cups cups-browsed cxl-monitor debug-shell ebtables exchange-bmc-os-info
                   firewalld fsidd gpm grub2-once haveged ipmi ipmievd irqbalance iscsi-init iscsid
                   issue-add-ssh-keys kexec-load lunmask man-db-create mariadb mariadb@ multipathd named
                   ndctl-monitor nfs nfs-blkmap nfs-server nfsserver nmb ostree-remount ostree-state-overlay@
                   rpcbind rpmconfigcheck rsyncd rtkit-daemon samba-bgqd smartd_generate_opts smb snmpd
                   snmptrapd spamd spampd speech-dispatcherd srp_daemon srp_daemon_port@ sysstat
                   sysstat_collect sysstat_summary systemd-boot-check-no-failures systemd-confext
                   systemd-network-generator systemd-sysext systemd-time-wait-sync systemd-timesyncd tuned
                   udisks2 update-system-flatpaks upower vncserver@ winbind wsdd ypbind
  indirect         serial-getty@ systemd-userdbd tftp wickedd

------------------------------------------------------------
13. Linux kernel boot-time arguments, from /proc/cmdline
  BOOT_IMAGE=/boot/vmlinuz-6.4.0-150700.53.31-default
  root=UUID=bcaa5a07-b428-4eb8-82e6-8155bbbcd9db
  rd.auto=1
  console=ttyS0,115200n8
  selinux=0
  security=
  splash=silent
  mitigations=auto
  console=ttyS0,115200
  udev.children-max=512
  nmi_watchdog=0
  uv_nmi.action=kdump
  add_efi_memmap
  tsc=nowatchdog
  earlyprintk=ttyS0,115200
  log_buf_len=8M
  numa_balancing=disable
  crashkernel=1G,high
  watchdog_thresh=60
  workqueue.watchdog_thresh=120

------------------------------------------------------------
14. cpupower frequency-info
  analyzing CPU 704:
    current policy: frequency should be within 800 MHz and 3.80 GHz.
                    The governor "performance" may decide which speed to use
                    within this range.
    boost state support:
```

(Continued on next page)

Platform Notes (Continued)

```
      Supported: yes
      Active: yes

------------------------------------------------------------
15. tuned-adm active
  No current active profile.

------------------------------------------------------------
16. sysctl
  kernel.numa_balancing               0
  kernel.randomize_va_space           2
  vm.compaction_proactiveness        20
  vm.dirty_background_bytes           0
  vm.dirty_background_ratio          10
  vm.dirty_bytes                      0
  vm.dirty_expire_centisecs        3000
  vm.dirty_ratio                     20
  vm.dirty_writeback_centisecs      500
  vm.dirtytime_expire_seconds     43200
  vm.extfrag_threshold              500
  vm.min_unmapped_ratio               1
  vm.nr_hugepages                     0
  vm.nr_hugepages_mempolicy           0
  vm.nr_overcommit_hugepages          0
  vm.swappiness                      60
  vm.watermark_boost_factor       15000
  vm.watermark_scale_factor          10
  vm.zone_reclaim_mode                0

------------------------------------------------------------
17. /sys/kernel/mm/transparent_hugepage
  defrag          always defer defer+madvise [madvise] never
  enabled         [always] madvise never
  hpage_pmd_size  2097152
  shmem_enabled   always within_size advise [never] deny force

------------------------------------------------------------
18. /sys/kernel/mm/transparent_hugepage/khugepaged
  alloc_sleep_millisecs   60000
  defrag                      1
  max_ptes_none             511
  max_ptes_shared           256
  max_ptes_swap              64
  pages_to_scan            4096
  scan_sleep_millisecs    10000

------------------------------------------------------------
19. OS release
  From /etc/*-release /etc/*-version
  os-release             SUSE Linux Enterprise Server 15 SP7
  hpe-foundation-release HPE Foundation Software 2.5.9, Build 757.1570.260209T0200.a.sles15sp7hpe-260209T0200

------------------------------------------------------------
20. Disk information
SPEC is set to: /home/cpu2017_new
  Filesystem     Type  Size  Used Avail Use% Mounted on
  /dev/nvme1n1p2 xfs   1.5T   43G  1.5T   3% /

------------------------------------------------------------
21. /sys/devices/virtual/dmi/id
```

(Continued on next page)

Platform Notes (Continued)

```
     Vendor:          HPE
     Product:         Compute Scale-up Server 3250
     Product Family: 1590PID03030202
     Serial:          5UFD3H1634-000

 ------------------------------------------------------------
 22. dmidecode
   Additional information from dmidecode 3.6 follows.  WARNING: Use caution when you interpret this section.
   The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately
   determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the
   "DMTF SMBIOS" standard.
   Memory:
     64x Micron MTC40F2046S1RC64BD2 MWFF 64 GB 2 rank 6400


 ------------------------------------------------------------
 23. BIOS
 (This section combines info from /sys/devices and dmidecode.)
    BIOS Vendor:       HPE
    BIOS Version:      Bundle:1.0.306-20260122_103756 SFW:010.000.158.000.2601100246
    BIOS Date:         01/10/2026
```

Compiler Version Notes

```
==============================================================================================================
C       | 500.perlbench_r(base, peak) 502.gcc_r(base, peak) 505.mcf_r(base, peak) 525.x264_r(base, peak)
        | 557.xz_r(base, peak)
--------------------------------------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2025.2.0 Build 20250605
Copyright (C) 1985-2025 Intel Corporation. All rights reserved.
--------------------------------------------------------------------------------------------------------------

==============================================================================================================
C++     | 520.omnetpp_r(base, peak) 523.xalancbmk_r(base, peak) 531.deepsjeng_r(base, peak)
        | 541.leela_r(base, peak)
--------------------------------------------------------------------------------------------------------------
Intel(R) oneAPI DPC++/C++ Compiler for applications running on Intel(R) 64, Version 2025.2.0 Build 20250605
Copyright (C) 1985-2025 Intel Corporation. All rights reserved.
--------------------------------------------------------------------------------------------------------------

==============================================================================================================
Fortran | 548.exchange2_r(base, peak)
--------------------------------------------------------------------------------------------------------------
Intel(R) Fortran Compiler for applications running on Intel(R) 64, Version 2025.2.0 Build 20250605
Copyright (C) 1985-2025 Intel Corporation. All rights reserved.
--------------------------------------------------------------------------------------------------------------
```

Base Compiler Invocation

C benchmarks:
icx

C++ benchmarks:
icpx

(Continued on next page)

Base Compiler Invocation (Continued)

Fortran benchmarks:
ifx

Base Portability Flags

500.perlbench_r: -DSPEC_LP64 -DSPEC_LINUX_X64
502.gcc_r: -DSPEC_LP64
505.mcf_r: -DSPEC_LP64
520.omnetpp_r: -DSPEC_LP64
523.xalancbmk_r: -DSPEC_LP64 -DSPEC_LINUX
525.x264_r: -DSPEC_LP64
531.deepsjeng_r: -DSPEC_LP64
541.leela_r: -DSPEC_LP64
548.exchange2_r: -DSPEC_LP64
557.xz_r: -DSPEC_LP64

Base Optimization Flags

C benchmarks:
-w -std=c11 -m64 -Wl,-z,muldefs -xgraniterapids -O3 -ffast-math
-flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4
-L/home/specdev/intel-compilers/compiler/2025.2/lib -lqkmalloc

C++ benchmarks:
-w -std=c++14 -m64 -Wl,-z,muldefs -xgraniterapids -O3 -ffast-math
-flto -mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4
-fdelayed-template-parsing
-L/home/specdev/intel-compilers/compiler/2025.2/lib -lqkmalloc

Fortran benchmarks:
-w -m64 -Wl,-z,muldefs -xgraniterapids -O3 -ffast-math -flto
-mfpmath=sse -funroll-loops -qopt-mem-layout-trans=4
-nostandard-realloc-lhs -align array32byte -auto
-L/home/specdev/intel-compilers/compiler/2025.2/lib -lqkmalloc

Peak Compiler Invocation

C benchmarks:
icx

(Continued on next page)

Peak Compiler Invocation (Continued)

C++ benchmarks:
icpx

Fortran benchmarks:
ifx

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

500.perlbench_r: -w -std=c11 -m64 -Wl,-z,muldefs
-fprofile-generate(pass 1)
-fprofile-use=default.profdata(pass 2) -xCORE-AVX2(pass 1)
-flto -Ofast -xCORE-AVX512 -ffast-math -mfpmath=sse
-funroll-loops -qopt-mem-layout-trans=4
-fno-strict-overflow -fno-strict-aliasing
-L/home/specdev/intel-compilers/compiler/2025.2/lib
-lqkmalloc

502.gcc_r: basepeak = yes

505.mcf_r: basepeak = yes

525.x264_r: -w -std=c11 -m64 -Wl,-z,muldefs -xgraniterapids -Ofast
-ffast-math -flto -mfpmath=sse -funroll-loops
-qopt-mem-layout-trans=4 -fno-alias
-L/home/specdev/intel-compilers/compiler/2025.2/lib
-lqkmalloc

557.xz_r: basepeak = yes

C++ benchmarks:

520.omnetpp_r: basepeak = yes

523.xalancbmk_r: basepeak = yes

(Continued on next page)

Peak Optimization Flags (Continued)

531.deepsjeng_r: `basepeak = yes`

541.leela_r: `basepeak = yes`

Fortran benchmarks:

548.exchange2_r: `basepeak = yes`

The flags files that were used to format this result can be browsed at
`http://www.spec.org/cpu2017/flags/HPE-Platform-Flags-Intel-CSS-GNR-rev1.3.html`
`http://www.spec.org/cpu2017/flags/Intel-ic2025-official-linux64.html`

You can also download the XML flags sources by saving the following links:
`http://www.spec.org/cpu2017/flags/HPE-Platform-Flags-Intel-CSS-GNR-rev1.3.xml`
`http://www.spec.org/cpu2017/flags/Intel-ic2025-official-linux64.xml`

SPEC CPU and SPECrate are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU®2017 v1.1.9 on 2026-02-18 23:38:17-0500.
Report generated on 2026-04-22 06:55:21 by CPU2017 PS formatter v6716.
Originally published on 2026-04-21.