



# OMPM2001 Result

Copyright 1999-2008, Standard Performance Evaluation Corporation

Cisco  
C240 M3

SPECompMpeak2001 = 102641

SPECompMbase2001 = 94065

SPEC license #HPG9019 Tested by: Cisco Test site: San Jose Test date: Feb-2012 Hardware AvailApr-2012 Software AvailApr-2012

Benchmark	Reference Time	Base Runtime	Base Ratio	Peak Runtime	Peak Ratio	
310.wupwise_m	6000	36.9	162712	34.2	175322	
312.swim_m	6000	78.2	76677	71.6	83746	
314.mgrid_m	7300	101	72525	85.4	85435	
316.applu_m	4000	39.6	100937	42.4	94279	
318.galgel_m	5100	70.8	71994	54.8	93003	
320.earthquake_m	2600	35.4	73499	26.1	99490	
324.apsi_m	3400	34.8	97647	38.6	88037	
326.gafort_m	8700	89.9	96824	80.3	108409	
328.fma3d_m	4600	74.2	61965	64.4	71394	
330.art_m	6400	23.2	275543	23.4	273193	
332.ammp_m	7000	107	65393	107	65393	

### Hardware

CPU: Intel(R) Xeon(R) Processor E5-2690  
 CPU MHz: 2900  
 FPU: Integrated  
 CPU(s) enabled: 16 cores, 2 chips, 8 cores/chip, 2 thread/core  
 CPU(s) orderable: 1,2  
 Primary Cache: 32KB(I)+32KB(D) per core on chip  
 Secondary Cache: 256KB per core (I+D) on chip  
 L3 Cache: 20MB (I+D) per chip on chip  
 Other Cache: N/A  
 Memory: 128 GB (DDR3 RDIMM 16x8-GB 1600 MHz)  
 Disk Subsystem: LSI MR9266-8i (scsi) 299GB  
 Other Hardware:

### Software

OpenMP Threads: 32  
 Parallel: OpenMP  
 Operating System: SUSE Linux Enterprise Server 11 (x86\_64) 3.0.8-0.11-default  
 Compiler: Intel C/C++ Compiler 12.0.2 for Linux  
 Intel FORTRAN Compiler 12.0.2 for Linux  
 GNU C Compiler 4.4.6  
 File System: Linux ext4  
 System State: Default

## Notes/Tuning Information

### BIOS settings notes:

Intel Hyper-Threading Technology (SMT): Enabled (default is Enabled)  
 Intel Turbo Boost Technology (Turbo) : Enabled (default is Enabled) (Max 3.8GHz)

### Portability Flags:

318.galgel\_m: -FI -132

### Extra Flags:

330.art\_m: -DINTS\_PER\_CACHELINE=32 -DDBLS\_PER\_CACHELINE=16  
 all: -gcc-name=/usr/bin/gcc

### General Notes and environment variables

export KMP\_LIBRARY=turnaround  
 export KMP\_STACKSIZE=31M  
 export KMP\_BLOCKTIME=infinite  
 export OMP\_DYNAMIC=FALSE  
 ONESTEP=yes

ulimit -s unlimited

For compiler/openmp flags description please refer:

<http://www.spec.org/cpu2006/flags/Intel-ic12.0-linux64-revB.20120329.html>

### Base optimization flags and environment variables:

=====

### Medium:

OPTIMIZE = -O2 -xAVX -ipo -openmp -no-prec-div  
 COPTIMIZE = -ansi-alias  
 export KMP\_AFFINITY=compact,0



# OMPM2001 Result

Copyright 1999-2008, Standard Performance Evaluation Corporation

Cisco  
C240 M3

SPECompMpeak2001 = 102641

SPECompMbase2001 = 94065

SPEC license #HPG9019 Tested by: Cisco Test site: San Jose Test date: Feb-2012 Hardware AvailApr-2012 Software AvailApr-2012

## Notes/Tuning Information (Continued)

Peak optimization flags and environment variables:

Medium:

OPTIMIZE = -O2 -xAVX -ipo -openmp

COPTIMIZE = -ansi\_alias

export KMP\_AFFINITY=compact,0

Peak per-benchmark optimization flags and environment variables:

310.wupwise\_m

OPTIMIZE=-O3 -xSSE4.2 -ipo -openmp

312.swim\_m

OPTIMIZE=-O3 -xSSE4.2 -ipo -openmp -opt-streaming-stores always -align

srcalt = ompl.32

export KMP\_AFFINITY=compact,1

export OMP\_NUM\_THREADS=16

314.mgrid\_m

OPTIMIZE=-O3 -xSSE4.2 -ipo -openmp -fno-alias

export KMP\_AFFINITY=compact,1

export OMP\_NUM\_THREADS=16

316.applu\_m

OPTIMIZE=-O3 -xSSE4.2 -ipo -openmp -fno-alias

export KMP\_AFFINITY=compact,1

export OMP\_NUM\_THREADS=16

318.galgel\_m

FOPTIMIZE=-mkl

RM\_SOURCES=lapak.f90

export KMP\_AFFINITY=compact,1

export OMP\_NUM\_THREADS=16

320.equake\_m

export KMP\_AFFINITY=compact,1

export OMP\_NUM\_THREADS=16

324.appsi\_m

OPTIMIZE=-O3 -xSSE4.2 -ipo1 -openmp

326.gafort\_m

OPTIMIZE=-O3 -xSSE4.2 -ipo -openmp

srcalt = ompl.32

export KMP\_AFFINITY=scatter,0

328.fma3d\_m

FOPTIMIZE=-no-prec-sqrt -fp-model fast=2

srcalt = ompl.32

export ENV\_KMP\_AFFINITY=compact,1

330.art\_m

332.ammp\_m

basepeak=yes