SPEC CINT95rate Results

©Copyright 1995, Standard Performance Evaluation Corporation

Hewlett-Packard
HP 9000 Model K410

SPECint_rate95 = 39.7

SPECint_base_rate95 = 39.7

SPEC license # 3	Tested By: HP Cupertino, CA	Test Date: Oct-95	Hardware Avail: Jan-96	Software Avail: Aug-95



Hardware/Software Configuration for:
HP 9000 Model K410

Hardware

Model Name:	HP 9000 Model K410
CPU:	120 MHz PA-RISC 7200
FPU:	Integrated
Number of CPU(s):	1
Primary Cache:	256KBI+256KBD off-chip
Secondary Cache:	None
Other Cache:	None
Memory:	512MB
Disk Subsystem:	1 Fast/Wide SCSI-2 1.0 GB
Other Hardware:	Ethernet

Software

Operating System:	HP-UX B.10.01
Compiler:	HP92453-01 A.10.13 HP C Compiler
File System:	HP-UX
System State:	Multi-user
Kernel Extensions:	Increased: maxdsiz, maxssiz

Benchmark # and Name	Base Copies	Base Run Time	Base SPEC Ratio	Copies	Run Time	SPEC Ratio
099.go	1	630	65.7	1	630	65.7
124.m88ksim	1	496	34.5	1	496	34.5
126.gcc	1	346	44.2	1	346	44.2
129.compress	1	405	40.0	1	405	40.0
130.li	1	444	38.5	1	444	38.5
132.ijpeg	1	729	29.6	1	729	29.6
134.perl	1	500	34.2	1	500	34.2
147.vortex	1	618	39.3	1	618	39.3
SPECint_base_rate95 (G. Mean)			39.7			
SPECint_rate95 (G. Mean)						39.7

Notes/Tuning Information

```
PORTABILITY:
All: -Ae
126: -Ae -DUSG

BASE:
All: +Oall +Onoregionsched +DAK400 +P

PEAK:
Same as BASE.

Note: The +P indicates the use of profile based optimization
```

For More Information Contact:
SPEC
10754 Ambassador Drive, Suite 201
Manassas, VA 22110
(703) 331-0180
info@specbench.org
http://www.specbench.org