SPEC CFP95rate Results

©Copyright 1995, Standard Performance Evaluation Corporation

SGI Origin2000

SPECfp_rate95 = 390

SPECfp_rate_base95 = 359

SPEC license # 04 | Tested By: SGI | Test Date: Apr-98 | Hardware Avail: Apr-98 | Software Avail: Sep-97



Hardware/Software Configuration for: Origin2000

Hardware

Model Name:	Origin2000: 2X 250MHz R10k
CPU:	250 MHz MIPS R10000 Processor Chip Revision: 3.3
FPU:	MIPS R10010 Floating Point Chip Revision: 0.0
Number of CPU(s):	2
Primary Cache:	32KBI + 32KBD on chip
Secondary Cache:	4MB (I+D)
Other Cache:	None
Memory:	512MB
Disk Subsystem:	4 SCSI 4.4GB (striped)
Other Hardware:	none

Software

Operating System:	IRIX64 6.4 w/patch2694 and patch2509
Compiler:	MIPSpro Fortran 77 and 90 7.2
	IRIX Development Foundation 1.0 w/patch2687
File System:	XFS
System State:	Single-User

Benchmark # and Name	Base Copies	Base Run Time	Base SPEC Ratio	Copies	Run Time	SPEC Ratio
101.tomcatv	2	169	395	2	152	438
102.swim	2	297	521	2	254	609
103.su2cor	2	104	243	2	93	271
104.hydro2d	2	198	218	2	174	248
107.mgrid	2	126	357	2	120	374
110.applu	2	166	238	2	166	239
125.turb3d	2	241	306	2	221	333
141.apsi	2	104	362	2	100	378
145.fpppp	2	277	624	2	254	680
146.wave5	2	96.9	557	2	90	601
SPECfp_rate_base95 (G. Mean)			359			
SPECfp_rate95 (G. Mean)						390

Notes/Tuning Information

```
All benchmarks were built using f77 unless noted otherwise
Base Flags: -Ofast=ip27 -LNO:fusion=2
Peak Flags:
FEEDBACK:
.   PASS1 = -fb_create /tmp/FBDIR/$(EXENAME)
.   PASS2 = -fb_opt /tmp/FBDIR/$(EXENAME)
tomcatv: f90 -O3 -n32 -mips4 -LNO:prefetch_ahead=1:blocking=off
swim:    -O3 -n32 -mips4 -LNO:fusion=2:prefetch_ahead=1 -OPT:ieee_arith=3:ro=3:cs2=1m
su2cor:  -n32 -mips4 -O3 -TENV:X=3 -OPT:ro=3:ieee_arith=3:unroll_times_max=2:unroll_size=0 \
.        -OPT:unroll_analysis=off -LNO:prefetch=0:fusion=2 -TARG:platform=ip27
hydro2d: -Ofast=ip27 -n32 -mips4 -TENV:X=4 -OPT:ro=3:ieee_arith=3 -LNO:prefetch=2:fusion=2:blocking=off
mgrid:   -Ofast=ip27 -n32 -mips4 -LNO:fusion=2:prefetch=2:prefetch_ahead=1
applu:   -Ofast=ip27 -LNO:fusion=2
turb3d:  -Ofast=ip27 -IPA:inline=off -OPT:ieee_arith=3 -LNO:pf2=0:interchange=off:cs2=1m -OPT:unroll_times_max=2, FEEDBACK
apsi:    -O3 -n32 -mips4 -IPA -OPT:div_split -LNO:fusion=2:prefetch=0:interchange=off
fpppp:   -Ofast=ip27 -lfastm -LNO:fusion=2, FEEDBACK
wave5:   -Ofast -LNO:fusion=2:fission=2:prefetch=1:prefetch_ahead=1, FEEDBACK
.
Large pages were enabled for base and peak using:
.  systune -i ;  percent_totalmem_1m_pages = 30
.  setenv PAGESIZE_DATA 1m
.
Jobs submitted using "dplace -place submit.pf -mustrun "
```

For More Information Contact:
SPEC
10754 Ambassador Drive, Suite 201
Manassas, VA 20109
(703) 331-0180
info@specbench.org
http://www.specbench.org/

-- Prepared By: --