SPECweb96 Result

©Copyright 1996, Standards Performance Evaluation Corporation

Hewlett-Packard
HP 9000 Model D330

SPECweb96= 500

Test Date : Nov-96

Tested by : HP Cupertino, CA

Hardware Avail:	Jan-97	OS Avail:	Jan-97	HTTP Software Avail:	Nov-96	SPEC license #:	3

Throughput ops/sec	Response msec
50	6.5
101	6.5
151	7.1
202	7.4
252	8.9
303	11.5
344	14.2
397	21.9
451	46.8
500	168.4



Hardware

Model Name:	HP 9000 Model D330
Processor:	PA7300LC 160MHz
# of Processors:	1
Primary Cache:	64KBI+64KBD on chip
Secondary Cache:	1MB(I+D) off chip
Other Cache:	None
Memory:	512 MB
Disk Subsystem:	3 HP A3306A scsi Drives
Disk Controllers:	1 internal FWD SCSI
Other Hardware:	Fore ASX-200WG ATM switch

Software

Operating System:	HP-UX 10.20
File System:	HFS
Other Software:	None

HTTP Software

Vendor:	Zeus Technology Limited
HTTP Software:	Zeus 1.1.4
# of "threads":	1
Server Cache:	zeus -b 820000 -t 9000 -l 200 -q
Log Mode:	Common Log Format

Network

# of Controllers:	1
Network Controllers:	1 HP J2498A opt 001, 155Mbit OC3c ATM
# of Nets:	1
Type of Nets:	155Mbit OC3c ATM multi-mode fibre
Network Speed:	155Mbit
Time Wait (secs):	60 (Non RFC1122)

Load Generators

# of Load Generators:	3
# of Processes Each:	37
Model:	HP 9000/B160L
Processor:	160Mhz PA7300LC
# of CPUs:	1
Memory:	128Mbyte
OS:	HPUX 10.20
Compiler:	HP92453-01 A.10.32.03 HP C Compiler

Benchmark Configuration

Max Requested Load:	505
Max Fileset Size (MB):	493

Notes/Tuning Information

```
so_qlimit_max 0x100, dbc_max_pct 5, ninode 16000
workload files set to 0755 permissions
```

For More Information contact

SPEC
10754 Ambassador Drive, Suite 201
Manassas, VA 22110

(703) 331-0180
info@specbench.org
http://www.specbench.org/