SPECweb99_SSL Result

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company: HP ProLiant DL320 G3
Zeus Technology Limited: Zeus V4.3r1 (64 bit)

SPECweb99_SSL =1100

Test Date: Jun-2005
Tester: Hewlett-Packard Company

Hardware Avail:	Sep-2005	OS Avail:	Aug-2004	HTTPS Software Avail:	Nov-2003	Sup. Software Avail:	Nov-2003	SPEC license #:	3

Hardware

Vendor:	Hewlett-Packard Company
Model:	HP ProLiant DL320 G3
Processor:	3.6GHz Intel Pentium 4
# Processors:	1 core, 1 chip, 1 core/chip (Hyper-Threading enabled)
Primary Cache:	12KBI+16KBD
Secondary Cache:	2MB L2
Other Cache:	none
Memory:	4GB (4x1GB PC3200 DDR)
Disk Subsystem:	1x80GB Serial ATA 7,200 rpm HDD
Disk Controllers:	Integrated 2-port Serial ATA Controller
Other Hardware:	none

Software

Operating System:	SuSE Linux Enterprise Server 9 (x86_64)
File System:	ext3
Other Software:	none

HTTPS Software

Vendor:	Zeus Technology Limited
HTTPS Software:	Zeus V4.3r1 (64 bit)
API:	Zeus PEPP 0.9pre1 ISAPI for dynamic content
Server Cache:	none
Log Mode:	Binary Common Log Format

Test Sponsor

Test Date:	Jun-2005
Tested By:	Hewlett-Packard Company
SPEC License:	3

Network

# of Controllers:	2
Network Controllers:	Integrated NC7782
# of Nets:	2
Type of Nets:	Gigabit Ethernet
Network Speed:	1 Gb/s
MSL (sec):	30 (Non RFC1122)
Time-Wait (sec):	60 (Non RFC1122)
MTU:	1500

Clients

# of Clients:	2
Model:	HP ProLiant DL360 G3
Processor:	3.06GHz 1MB L3 cache Intel Xeon
# of Processors:	2 cores, 2 chips, 1 core/chip (Hyper-Threading enabled)
Memory:	1024MB
Network Controller:	Integrated NC7782
Operating System:	Windows Server 2003 Std. Edition
Compiler:	Microsoft Visual C++ 6.0

Notes/Tuning Information

SUT Notes

OS, access log and file-set on one Serial ATA drive

Operating System Notes

File system mounted with noacl,noatime,nodiratime - no inode access time updateing, no access control lists,
irq_balancer daemon disabled, default enabled
Each NIC IRQ bound to a seperate logical CPU, default round-robin
Each NIC's TX queue length set to 40000, default 100
ulimit -n 72720, sets number of open files, default 1024
/proc/sys/net/ipv4/conf/all/rp_filter= 1, enables source route verification, default 0
/proc/sys/net/ipv4/tcp_max_tw_buckets= 2000000, sets TCP time-wait buckets pool size, default 180000
/proc/sys/net/ipv4/tcp_rmem= 30000000 30000000 30000000, maximum TCP read-buffer space allocatable, default 4096 87380 174760
/proc/sys/net/ipv4/tcp_wmem= 30000000 30000000 30000000, maximum TCP write-buffer space allocatable, default 4096 16384 131072
/proc/sys/net/ipv4/tcp_mem= 30000000 30000000 30000000, maximum TCP buffer space allocatable, default 31744 32256 32768
/proc/sys/net/core/rmem_max= 10000000, maximum receive socket buffer size, default 65535
/proc/sys/net/core/rmem_default= 10000000, default receive socket buffer size, default 65535
/proc/sys/net/core/wmem_max= 10000000, maximum send socket buffer size, default 65535
/proc/sys/net/core/wmem_default= 10000000, default send socket buffer size, default 65535
/proc/sys/net/core/optmem_max= 10000000, default 10240
/proc/sys/fs/file-max= 291879, maximum number of open files, default 1024

HTTPS Software Notes

Zeus Web Server Tuneables ($ZEUSHOME/web/global.cfg)
tuning!bind_any no
tuning!unique_bind yes
tuning!cache_cooling_time 0
tuning!cache_files 282011
tuning!cache_flush_interval 360000

© Copyright 1999-2004, Standard Performance Evaluation Corporation

Notes/Tuning Information (Continued)

HTTPS Software Notes (Continued)

tuning!cache_small_file 40000
tuning!cache_large_file 1048576
tuning!cache_max_bytes 17179869184
tuning!cache_stat_expire 360000
tuning!cbuff_size 65536
tuning!clientfirst_optimise yes
tuning!keepalive yes
tuning!keepalive_max -1
tuning!keepalive_timeout 3600
tuning!listen_queue_size 8192
tuning!maxaccept 2048
tuning!modules!cgi!cleansize 0
tuning!sendfile no
tuning!sendfile_maxsize 0
tuning!sendfile_minsize 0
tuning!so_wbuff_size 1048576
tuning!softservers no
tuning!ssl_diskcache no
tuning!ssl_sessioncache_size 2617
tuning!ssl_cbuff_size 32840
tuning!modules!stats!enabled no
tuning!modules!nsapi!enabled no
runningsite/wstest: bindaddr IP address 1, IP address 2
See HP-20030414-tunings.txt for a description of these Zeus tuning parameters

HTTP API Notes

Dynamic API: HP-20020724-API.tgz
API configured with --ssl=yes

Client Notes

The alternate performance neutral alt.Win32 client was used.
TcpipParametersMaxUserPort = 0xfffe, sets maximum open ports to 65534
TcpipParametersTcpTimedWaitDelay = 60, sets TIME_WAIT parameter to 60 seconds (non-RFC 1122),default 240
TcpipParametersMaxFreeTwTcbs= 100000, sets maximum number of TIME_WAIT tcbs to 100,000
TcpipParametersTcpWindowSize= 65535, sets TCP receive window size, default 8192

Other Notes

Server kernel: default SLES 9 (2.6.5-7.97-smp)